

NOBLE CHEMICAL SIERRA FAST DRYING FLOOR FINISH

FOR USE ON:

Vinyl tile
Vinyl asbestos
Asphalt tile
Linoleum
Rubber tile
Terrazzo
Sealed wood
Quarry tile

DESCRIPTION:

This fast drying floor finish is easy to use, designed for high traffic areas. It is an excellent product for damp mopping and spray buffing with any speed buffing machine.

DIRECTIONS:

If stripping is necessary, use a high quality product and follow directions accordingly. If the floor is in good condition and stripping is not necessary, sweep up excess dirt and dust and then clean with a good quality cleaner to remove dirt and oils. Follow with a thorough rinsing and allow the floor to dry completely.

If the floor was stripped, use a good acrylic sealer to prepare the floor for finishing. Spread a liberal coat of finish evenly across the floor with a clean mop or applicator. Allow each coat to dry at least 45 minutes before applying the next coat. Two or three coats are desired initially, depending on the condition of the floor and gloss desired.

To maintain, use a high quality floor cleaner and damp mop regularly. Spray buffing or mop-on restoring may also be done after sweeping up loose dirt and dust. Follow directions for each product accordingly.

This product meets the maximum content requirements for Volatile Organic Compounds (VOCs) as established by state and federal regulations.