



# **HAND SINKS A.D.A COMPLIANT LAVATORIES**











## FRONT LOADING PAPER TOWEL DISPENSER UNITS







Optional A.D.A. Compliant Bubbler can be added to the 7-PS-25, 7-PS-26 & 7-PS-75 Only Use Model # K-47

## Standard Faucet conforms to NSF 61 Standard 9. Faucets Are AB1953 Lead Free Compliant.

For Replacement Faucets & Upgrades, Drains & Accessories visit our website at www.advancetabco.com

	Qty #:
<i>Model</i> #:	
<i>Project</i> #:	

#### **FEATURES:**

One piece Deep Drawn sink bowl design.

Sink bowl is 16" x 14" x 5".

All sink bowls have a large liberal radii with a minimum dimension of 2" and are rectangular in design for increased capacity.

Keyhole wall mount bracket.

1 1/2" stainless steel drain with strainer plate.

#### **Additional Specific Features:**

- 7-PS-25 6" Extended deck mounted gooseneck faucet with wrist handles & deck mounted liquid soap dispenser.
- 7-PS-26 includes a "Hands Free" AC/DC operated gooseneck faucet & deck mounted, liquid soap dispenser.
- **7-PS-75** Sink Only. Faucet not included. Three 1-3/8"dia. Holes Punched.
- 7-PS-41 includes a "Hands Free" AC/DC operated gooseneck faucet & deck mounted, liquid soap dispenser.

Front loading paper towel dispenser (Standard C-Fold Towels). Stainless Steel Skirt with Removable Access Panel and enclosed bottom for storage. Optional TA-14 lock available.

7-PS-46 6" Extended splash mounted gooseneck faucet with wrist handles & deck mounted liquid soap dispenser. Front loading paper towel dispenser (Standard C-Fold Towels). Stainless Steel Skirt with Removable Access Panel and enclosed bottom for storage. Optional TA-14 lock available.

### **CONSTRUCTION:**

All TIG welded.

Welded areas blended to match adjacent surfaces and to a satin finish.

Die formed Countertop Edge with a 3/8" No-Drip offset. Bowl made from One sheet of stainless steel - No Seams.

#### **MATERIAL:**

Heavy gauge type 304 series stainless steel.

Wall mounting bracket is Galvanized and of offset design.

All fittings are brass / chrome plated unless otherwise indicated.

## **MECHANICAL:**

Faucet supply is 1/2" IPS male thread hot and cold.



Customer Service Available To Assist You 1-800-645-3166 8:30 am - 8:00 pm E.S.T.

Email Orders To: customer@advancetabco.com. For Smart Fabrication™ Quotes, Email To: smartfab@advancetabco.com or Fax To: 631-586-2933

**NEW YORK** Fax: (631) 242-6900

**GEORGIA** Fax: (770) 775-5625

**TEXAS** Fax: (972) 932-4795 **NEVADA** 

Fax: (775) 972-1578

## **DIMENSIONS and SPECIFICATIONS**

TOL Overall: ± .500" Interior: ± .250"

FITTINGS SUPPLIED AS SHOWN

ALL DIMENSIONS ARE TYPICAL



