

3779 Champion Blvd., Winston-Salem, NC 27105 1-888-845-9800 Fax# 1-336-245-6453 http://www.Beverage-Air.com

Commercial Refrigeration Equipment General Specification

LUMAVUE SERIES—GLASS DOOR MERCHANDISER

Used for merchandising and storage of product.

CABINET CONSTRUCTION

Heavy duty construction includes white coated steel interior walls. Exterior finish is heavy-duty steel with a baked on durable paint. Choose from black or white finish.

Foamed-in-place CFC and HCFC-free polyurethane insulation enhances the structural strength of the cabinet and helps increase energy efficiency.

Modern, one-piece grille is easily removed for cleaning and servicing.

Double pane, lowE argon filled glass doors feature inside and outside panes that are tempered for added safety.

Three sliding glass doors feature integral door handles that provide low profile and are more aesthetically pleasing. Hold-open feature is standard.

Five white epoxy coated steel shelves per door are standard.

Brightly lighted sign panel.

REFRIGERATION


Whisper-quiet refrigeration system uses R134a refrigerant, which is CFC and HCFC-free for compliance with environmental safety concerns.

Product temperatures from 32°F to 40°F.

ELECTRICAL

Interior fluorescent lighting enhances product illumination. Optional LED lighting provides hidden light source for increased product visibility. LED bulbs last up to 10 times longer compared to fluorescent bulbs and renders additional energy savings due to reduced wattage load on compressor.

Units wired at factory and ready for connection to a 115/60/1 phase, 15 amp dedicated outlet. 8' long cord and plug set included.













SLIDING GLASS DOOR **LUMAVUE** MERCHANDISER SERIES LV66Y

MODEL: LV66Y



LV66Y (shown with 4 shelves per section)

SPECIAL FEATURES

- LV66Y has earned the ENERGY STAR®
- Whisper-quiet refrigeration system
- Sliding glass doors
- Brightly lighted sign panel
- Optional LED lighting
- 2010 Federal Energy Compliant
- Gravity Flo kits and Can Roller options available

ELECTRICAL CONNECTION



Units pre-wired at factory and include 8' long cord and plug set.

Available From:

Model Specified	Store#
Location	Quantity



LumaVue Glass Door Merchandisers Model: LV66Y

MODEL	LV66Y
EXTERNAL DIMENSIONAL DATA	
Length Overall (inches) Length Overall (mm)	75" 1905
Depth Overall (inches) Depth Overall (mm)	32" 813
Height Overall— (inches) Height Overall— (mm)	78" 1981
Number of doors	3
INTERNAL DIMENSIONAL DATA	
NET Capacity (cubic ft.) NET Capacity (Liters)	70 1982
Internal Length Overall (inches) Internal Length Overall (mm)	72" 1905
Internal Depth Overall (inches) Internal Depth Overall (mm)	27" 686
Internal Height Overall—(inches) Internal Height Overall—(mm)	61 3/4" 1569
*Internal Height to Evaporator Housing—(inches) *Internal Height to Evaporator Housing—(mm)	54" 1372
Number of shelves	15
ELECTRICAL DATA	
Full Load Amperes 115/60/1	9.9 A
ENERGY CONSUMPTION (KWH)	7.68 kWh/day
REFRIGERATION DATA	
Horsepower	1/2
WEIGHT DATA	
Gross Weight (Crated lbs)	681
Gross Weight (Crated kg)	309

32" 27" **INSIDE DEPTH** 61 3/4" **INSIDE** 78" HT

PLAN VIEWS














Note:

Not all markings may apply to all model variations. *Internal height to evaporator housing.



END

BEVERAGE-AIR® CORPORATION