

BUNN®

BrewWISE® Dual Soft Heat® DBC Brewer

ITEM#

PROJECT

DATE



Model Dual SH DBC with 1.5 gallon SH Servers

(servers sold separately)

Dimensions: 35.8" H x 18" W x 21.2" D
(90.9cm H x 45.7cm W x 53.8cm D)

Features

BrewWISE® Brewing System

- Brews 18.9 gallons (71.5 litres) of perfect coffee per hour.
- Brews ½, 1, or 1½ gallon (1.9, 3.8 or 5.7 litre) batches.
- Stores individual coffee and flavor profiles using adjustable water volume, bypass percentage, pulse brew, and pre-infusion timing.
- Operate any combination of BrewWISE equipment error-free with wireless brewer-grinder interface via Smart Funnel®.
- Reduce accidents with safety features that decrease hot splashes from funnel, eliminate brewing when funnel or server is not present.
- Troubleshoot all switches and electrical components from the front panel with advanced diagnostic service tools.
- Simplify installation and calibration by creating your own recipe cards and dedicated funnels with the BrewWISE Recipe Writer using your PC (Windows® compatible).
- International electrical configurations available.

For current specification sheets and other information, go to www.bunn.com.

Related Products

Easy Clear® EQHP-25L
Product No. : 39000.0002



Easy Clear® EQHP-25
Product No. : 39000.0005

Single/Dual Filter Pack
Product No. : 20138.0000
Packed per case: 500
Dimensions:
5¼" Base x 4¼" Sidewall
13.3 cm Base x 10.8 cm Sidewall




BrewWISE® Recipe Writer (BRW)
Product No.: 34444.0000



Recipe Card
Product No.: 34447.0000
• Program a recipe to be used
on brewer or grinder.



Ad Card
Product No.: 34448.0000
• Program a message to appear
on the brewer's display.



Two Position Drip Tray
Product No.: 27150.0000



SH Server
Product No. : 27850.0001



2SH Stand
Product No. : 27875.0000



MHG
Product No.: 35600.0000



G9-2T DBC
Product No.: 33700.0000

Model

Dual SH DBC

Agency Listing



Patents Apply

9/08

A2.9

Dimensions & Specifications

Model	Product #	Volts	Amps	Tank Heater Watts	Total Watts	Capacity	Cubic Measure	Shipping Weight	Cord Attached
Dual SH DBC	33500.0000	120/240	29.1	2@3300	6800	18.9 gal/hr	13.3 ft ³	90 lbs.	No
Dual SH DBC†	33500.0006	120/240	29.1	2@3300	6800	18.9 gal/hr.	13.3 ft ³	90 lbs.	No
Dual SH DBC*	33500.0004	120/240	29.1	2@3300	6800	18.9 gal/hr.	13.3 ft ³	90 lbs.	No
SH Server(1.5 gal.)	27850.0001	n/a	n/a	n/a	n/a	1.9 gal.	2.4 ft ³	17 lbs.	n/a
SH Server*(1.5 gal.)	27850.0004	n/a	n/a	n/a	n/a	1.9 gal.	2.4 ft ³	17 lbs.	n/a
1SH Stand	27825.0000	120	.8	n/a	90	1 SH Server	1.2 ft ³	13 lbs.	Yes
1SH Stand*	27825.0004	120	.8	n/a	90	1 SH Server	1.2 ft ³	13 lbs.	Yes
2SH Stand	27875.0000	120	1.5	n/a	180	2 SH Servers	2.1 ft ³	22 lbs.	Yes
2SH Stand*	27875.0003	120	1.5	n/a	180	2 SH Servers	2.1 ft ³	22 lbs.	Yes

* Models have black finish.

† Model has lower faucet.

Note: Soft Heat® Brewers and Servers are boxed and shipped separately.

Brewing capacity: based upon incoming water temp of 60°F/15°C (140°F/60°C rise).

Models listed as 120/208V or 120/240V must be connected to 208V or 240V electrical service respectively. Please refer to the installation manual.

Electrical: Brewer is 3-wires plus ground service rated 120/240V, single phase, 50/60Hz.

Plumbing: 20-90 psi (138-621 kPa). Machine supplied with ¼" male fitting. Tank capacity: 8.4 gallons (31.8 L)

