

Item #:

Model #: CPO-ED-24H

Product Name: Counter Top Double
Pizza Oven w/Hearths



Model CPO-ED-24H shown with optional windows.

Specifications:

Garland Model Number CPO-ED-24H, electric counter top double pizza oven. Compact 26 ½" W x 28 7/8" D size includes a total of four decks with hearths. All stainless steel construction. 650° F (343° C) adjustable electromechanical thermostat and two mechanical 15-minute timers. 208 or 240 volt, single or three phase, (please specify).

Standard Features:

- Incoloy tubular heating elements total 7200 Watts.
- 650° F (343° C) adjustable electromechanical thermostat, one per oven cavity.
- One fifteen (15) minute mechanical timer per oven cavity.
- 3" crown heights.
- Oven ready light indicates when oven has reached selected temperature, one per oven cavity.
- 1 ½" thick insulation in walls, top and doors.
- Two (2) removable baking hearths, per oven cavity.
- All stainless steel finish.
- Standard with 6 ft. (1.8m) long cord and plug (single-phase models only).
- 208 or 240 volts, single or three phase (please specify).
- One-year parts and labor warranty.

Capacity:

• · 4 - 20" pre-baked crust pizzas (not designed for pan pizza)

Optional Features:

- O Windows in doors and interior lights
- O 4" adjustable legs
- O 60-minute timers







For USA, Contact: Garland Commercial Industries Tel: 570-636-1000 Fax: 570-636-3903 For United Kingdom & Ireland, Contact:: Enodis

Tel: 0181-561-0433 Fax: 0181-848-0041 For Canada & the Rest of the World, Contact: Garland Commercial Ranges, Ltd. Tel: 905-624-0260

Fax: 905-624-5669



Item #:


Model #: CPO-ED-24H


Product Name: Counter Top Double


Pizza Oven w/Hearths

COMBUSTIBLE WALL CLEARANCE

SIDES: 1" (25MM) REAR: 1" (25MM)







Dimensions

Exterior			Hea	Woight	
Н	W	D	W	D	Weight
29"	26½"	28-7/8 "	21"	21"	293lbs.
(74cm)	(67cm)	(74cm)	(53cm)	(53cm)	(133kg)

Electrical Specifications

Voltage/Phase	Watts	(Amps)			NEMA Plug #	Connection
voitage/Filase		L1	L2	L3	NLWA Flug #	Туре
208/1	7200	34.6	34.6		14-50P	6' line cord
240/1	7200	32.6	32.6		14-50P	6' line cord
208/1	7200	30.0	17.3	17.3		Terminal Block
240/1	7200	28.3	16.3	16.3		Terminal Block

WITH LIGHTS

Voltage/Phase	Watts	(Amps)			NEMA	Connection Type	
		L1	L2	L3	Plug #	Connection Type	
208/1	7400	35.6	34.6		14-50P	6' line cord	
240/1	7400	33.6	32.6	-	14-50P	6' line cord	
208/1	7400	31	17.3	17.3		Terminal Block	
240/1	7400	29.3	16.3	16.3		Terminal Block	