



# Cappuccino & Hot Chocolate Dispensers

*Choose From Over 50 Styles of Automatic Hot Beverage Dispensers!*



*Keep Them Coming Back For More!*



## Full Line Catalog



**Cecilware Corporation** 43-05 20th. Avenue, LIC NY 11105  
Tel: 800.935.2211 / 718.932.1414 • Fax: 718.932.7860



[www.cecilware.com](http://www.cecilware.com)

**Standard Features Included On All Dispensers\***



- **Fast Flow** – Dispenses beverages 30% faster, reducing wear & tear on major dispenser components.
- **Vacuum Steam Removal System VSRS** – Ensures the powdered mix remains dry to eliminate clogging, caking and bridging.
- **Moisture & Powder Collection Tray** – Prevents excess moisture & product powder from reaching the vacuum motor.
- **Direct Drive Auger System** – Ensures perfect hopper alignment & “silent running”.
- **Power Whip** – Carefully whips the product into a delicious, creamy drink.
- **Self Cleaning** – Rinse system is touch button easy & rinses the entire whipper chamber with hot water at the end of each cycle.
- **Quick Change Transparency** – Simply lift up 2 tabs and pull out the graphic.

**Additional Features Found On Certain Dispensers.**



- **Vertical Lift Door** – Hinged on top, provides easy access to the inside of the dispenser.
- **FAST Service** – *Front Access Saves Time*, allows access to major components through the front of the dispenser.
- **Stainless Drip Trays** – Allows for easy cleaning.
- **Easy Bulb Access** – New style screw-in bulb.
- **Slanted Whipper Chamber** – Provides optimal mixing of product & keeps it flowing away from the motor seal.
- **Molded Fascia** – Attractive contemporary design with extra large P.O.S. display, draws customers to the dispenser.
- **Intelligent Technology 2** – Digital dispensers featuring touch pad control & large, two line LCD display. With IT2 you can:
  - Set water temperature.
  - Set low water temperature lockout.
  - Set gram throw.
  - Set serving size.
  - Set for free flow or portion control.
  - View the number of cups dispensed.
  - View the total ounces dispensed.
  - Set rinse time.
  - Set rinse-warning lockout.

**Optional Features Available On Certain Dispensers.**



- **Portion Control & Triple Portion Control** – Allows an operator to automatically dispense a beverage into 1 (PC) or 3 (3PC) predetermined cup sizes.
- **Smartsense** – Monitors cappuccino powder level, alerts operator when product hopper needs to be refilled, shuts off dispense mechanism on empty flavor hopper, and re-engages when hopper is refilled.
- **Hot Water Dispense Button** – Allows an operator to offer soup or tea.
- **Side Panel Graphics Package** – Beautiful color graphics attract attention from all sides of the dispenser.
- **Electrical** – Export electrical configurations available.

\* The standard feature set is not available on the Mini Whipper series.



**Budget K Series • 2/3/4/5 Flavor**

These models utilize the same reliable components currently available in all models and are designed to service low volume requirement locations using minimum counter space.

**Additional Features For This Series**



\* Except 2K & 3K. \*\* Except 2K.

**Options For This Series**



Portion control add “PC” suffix. Smartsense add “SMT” suffix. Electrical options available.

Model	2K-GB-LD	3K-GB-LD	4K-GB-LD	5K-GB-LD	5K-10-GB-LD
# of Hoppers	2	3	4	5	5
Hopper Capacity	4 lbs.	4 lbs.	4 lbs.	4 lbs.	(1) 10 lbs. (4) 5½ lbs.
Width	8½"	10"	15⅝"	15⅝"	18"
Depth	20"	20"	20"	20"	20"
Height	31½"	31½"	31½"	31½"	34"
Tank Capacity	2 gal.	2¾ gal.	3¾ gal.	3¾ gal.	6 gal.
Ship Weight	70 lbs.	81 lbs.	120 lbs.	125 lbs.	130 lbs.

**Plumbing:** ¼" Water line required. **Electrical:** 120V, 1.8KW, 15A std. 120/240V, 3KW, 15A, or 6KW, 25A opt. **Export Voltage:** 220 available.

**Budget K**

**CAPPUCCINO Dispensers**



## Space Saver Series • 1/2/3/4 Flavor

This family of dispensers is for operators who have limited counter space. The Space Savers are narrower than their Feature Flavor counterparts.

### Additional Features For This Series



\* GB4M-5.5-LD-U only. \*\* Except GB1M & GB2M.

### Options For This Series



Portion control add "PC" suffix. Smartsense add "SMT" suffix. Hot water dispense button add "W" before "LD" suffix. Electrical options available.

Model	GB1M-LD	GB2M-5.5-LD	GB3M-5.5-LD	GB4M-5.5-LD	GB4M-5.5-LD-U
# of Hoppers	1	2	3	4	4
Hopper Capacity	8 lbs.	5½ lbs.	5½ lbs.	5½ lbs.	5½ lbs.
Width	8½"	8½"	11"	14⅛"	14⅛"
Depth	22"	22"	22"	22"	22"
Height	31½"	34"	34"	34"	34"
Tank Capacity	2 gal.	2 gal.	2¾ gal.	3¾ gal.	3¾ gal.
Ship Weight	65 lbs.	86 lbs.	100 lbs.	120 lbs.	120 lbs.

Plumbing: ¼" Water line required. Electrical: 120V, 1.8KW, 15A std. 120/240V, 3KW, 15A, or 6KW, 25A opt. Export Voltage: 220 available.

Space Saver



## Feature Flavor Series • 3&5 Flavor

Cecilware's original, medium volume cappuccino dispenser allows you to double up on popular flavors. With extra large product hoppers, you can sell more cappuccino and refill hoppers less often. Save time, labor and increase sales.

### Additional Features For This Series



\* GB3M-10-LD-U & GB5M-210-LD-U only.

\*\* Except GB3M-10-LD.

### Options For This Series



Portion control add "PC" suffix. Smartsense add "SMT" suffix. Hot water dispense button add "W" before "LD" suffix. Electrical options available.

Model	GB3M-10-LD	GB3M-10-LD-U	GB5M-10-LD	GB5M-210-LD-U
# of Hoppers	3	3	5	5
Hopper Capacity	(1) 10 lbs. (2) 5 lbs.	(1) 10 lbs. (2) 5 lbs.	(1) 10 lbs. (4) 5 lbs.	(2) 10 lbs. (3) 5 lbs.
Width	11½"	11½"	18"	20"
Depth	22"	22"	22"	22"
Height	34"	34"	34"	34"
Tank Capacity	3.2 gal.	3.2 gal.	6 gal.	6 gal.
Ship Weight	90 lbs.	90 lbs.	130 lbs.	140 lbs.

Plumbing: ¼" Water line required. Electrical: 120V, 1.8KW, 15A std. 120/240V, 3KW, 15A, or 6KW, 25A opt. Export Voltage: 220 available.

Feature Flavor


# CAPPUCCINO Dispensers



**IT & Vista IT Series • 2/3/4/5 Flavor**


Cecilware's dispensers with the IT2 microprocessor provide total operating control. With IT2 there's no need to rely on blinking lights to set up or change the dispenser settings. The LCD display simply walks an operator through all functions. IT2 also displays diagnostic messages for easy servicing.

**Additional Features For This Series**



\* GB2M-5.5-IT & GB3M-10-IT only. \*\* "Vista IT" models only. \*\*\* GB3M & GB3MV only

**Options For This Series**



Triple portion control available on GB3M & GB3MV only, add "3PC" suffix. Vertical lift door available on GB2M & GB3M only, add "U" suffix. Side panel graphics package & electrical options available.

Model	GB2M-5.5-IT-LD	GB3M-10-IT-LD	GB3MV-310-IT-LD	GB4MV-210-IT-LD	GB5MV-10-IT-LD
# of Hoppers	2	3	3	4	5
Hopper Capacity	5½ lbs.	(1) 10 lbs. (2) 5 lbs.	10 lbs.	(2) 5½ lbs. (2) 10 lbs.	(4) 5 lbs. (1) 10 lbs.
Width	9"	11½"	18"	18"	18"
Depth	22"	22"	22"	22"	22"
Height	34"	34"	35"	35"	35"
Tank Capacity	2.2 gal.	3.2 gal.	6 gal.	6 gal.	6 gal.
Ship Weight	60 lbs.	90 lbs.	130 lbs.	130 lbs.	130 lbs.

Plumbing: ¼" Water line required. Electrical: 120V, 1.8KW, 15A std. 120/240V, 3KW, 15A, or 6KW, 25A opt. Export Voltage: 220 available.



**Vista Series • 3/4/5 Flavor**

The Vista series features a new contemporary design with extra large P.O.S. display(s) that provide maximum merchandising for your cappuccino sales! These models include all the features that brought Cecilware to the forefront of the industry.

**Additional Features For This Series**



**Options For This Series**



Portion control add "PC" suffix. Smartsense add "SMT" suffix. Side panel graphics package & electrical options available.

Model	GB3MV-310-LD	GB4MV-210-LD	GB5MV-10-LD
# of Hoppers	3	4	5
Hopper Capacity	10 lbs.	(2) 5½ lbs. (2) 10 lbs.	(4) 5 lbs. (1) 10 lbs.
Width	18"	18"	18"
Depth	22"	22"	22"
Height	35"	35"	35"
Tank Capacity	6 gal.	6 gal.	6 gal.
Ship Weight	130 lbs.	130 lbs.	130 lbs.

Plumbing: ¼" Water line required. Electrical: 120V, 1.8KW, 15A std. 120/240V, 3KW, 15A, or 6KW, 25A opt. Export Voltage: 220 available.



Vista

**CAPPUCCINO Dispensers**



## Destination Series • 6/8/10/12 Flavor

Turn your coffee island into a Destination for cappuccino! Cecilware now brings you 10 & 12 flavor dispensers.

### Additional Features For This Series



### Options For This Series



Portion control add "PC" suffix. Smartsense add "SMT" suffix. Hot water dispense button add "W" before "LD" suffix. Side panel graphics package & electrical options available.

Model	GB6M-10-LD-U	GB8M-10-LD-U	GB10M-210-LD-U	GB12M-210-LD-U
# of Hoppers	6	8	10	12
Hopper Capacity	(1) 10 lbs. (5) 5 lbs.	(1) 10 lbs. (7) 5 lbs.	(2) 10 lbs. (8) 5 lbs.	(2) 10 lbs. (10) 5 lbs.
Width	21½"	27"	34"	39½"
Depth	22"	22"	22"	22"
Height	34"	34"	35"	35"
Tank Capacity	6 gal.	(2) 4 gal.	(2) 4 gal.	(2) 4 gal.
Ship Weight	160 lbs.	180 lbs.	200 lbs.	220 lbs.

**Plumbing:** ¼" Water line required. **Electrical:** 120V, 1.8KW, 15A std. 120/240V, 3KW, 15A, or 6KW, 25A opt. **Export Voltage:** 220 available. **Note:** GB8M10, GB10M210, GB12M210 require 2 water lines and 2 separate circuit's.

Destination



## Panorama Series • 6&8 Flavor

Sleek, curvy and attracts attention, these models combine Cecilware's newest contemporary design with the industries leading features.

### Additional Features For This Series



### Options For This Series



Portion control add "PC" suffix. Smartsense add "SMT" suffix. Hot water dispense add "W" before "LD" suffix. Side panel graphics package & electrical options available.

Model	GB6MP-10-LD-U	GB8MP-10-LD-U
# of Hoppers	6	8
Hopper Capacity	(1) 10 lbs. (5) 5 lbs.	(1) 10 lbs. (7) 5 lbs.
Width	22½"	28"
Depth	22"	22"
Height	34"	34"
Tank Capacity	6 gal.	(2) 4 gal.
Ship Weight	160 lbs.	180 lbs.

**Plumbing:** ¼" Water line required. **Electrical:** 120V, 1.8KW, 15A std. 120/240V, 3KW, 15A, or 6KW, 25A opt. **Export Voltage:** 220 available. **Note:** GB8MP-10-LD-U requires 2 water lines and 2 separate circuit's.



Panorama

# CAPPUCCINO Dispensers



### Vending & Pour-Over Models • 3 Flavor

Sell Cappuccino 24 hours a day. . . 365 days a year with Cecilware's vending model.

Don't let a lack of water lines stand in the way of selling cappuccino. Cecilware has the answer - the "Pour-Over" beverage dispenser.

#### Additional Features For This Series



\* Except GB3V-CC-LD. CC = Coin Changer.

#### Options For This Series



Portion control add "PC" suffix. Smartsense add "SMT" suffix. Hot water dispense button add "W" before "LD" suffix. Electrical options available.

Model	GB3V-CC-LD	GB3P-LD
# of Hoppers	3	3
Hopper Capacity	5½ lbs.	4 lbs.
Width	15"	11"
Depth	22"	22"
Height	34"	34"
Tank Capacity	3.2 gal.	2½ gal. 2 gal. reservoir
Ship Weight	120 lbs.	95 lbs.



**Plumbing:** ¼" Water line required for vending model. Pour Over includes water line as a back up. **Electrical:** 120V, 1.8KW, 15A std. 120/240V, 3KW, 15A, or 6KW, 25A opt. **Export Voltage:** 220 available.



### SKI & Super SKI Series • 1&2 Flavor

Designed for anywhere unusually high volumes of hot beverages are sold: Ski Resorts, Sports Bars, Airports, Stadiums, & Casinos. These units are designed to accommodate continuous extra heavy volume dispensing.

#### Additional Features For This Series



\* Super SKI models only. \*\* Available only on GB1SKI-LD, GB2SKI-LD & GB2 Super SKI-BL-LD models.

#### Options For This Series



Portion control add "PC" suffix. Smartsense add "SMT" suffix. Hot water dispense button add "W" before "LD" suffix. Electrical options available.

Model	GB1SKI-LD	GB2SKI-LD	GB2 Super SKI	GB2 Super SKI-BL-LD
# of Hoppers	1	2	2	2
Hopper Capacity	14 lbs.	14 lbs.	14 lbs.	14 lbs.
Width	8½"	14½"	14½"	14½"
Depth	22"	23¾"	24¾"	24¾"
Height	37½"	38"	40½"	40½"
Tank Capacity	3½ gal.	8½ gal.	8½ gal.	8½ gal.
Ship Weight	85 lbs.	140 lbs.	155 lbs.	155 lbs.

**Plumbing:** ¼" Water line required. **Electrical:** SKI models - 120/240V, 6KW, 25A std. Super SKI models - 230V, 6KW, 26A std. 230V, 9KW, 39A · 230V, 18KW, 78A · 230V, 18KW, 45A 3 Phase opt. **Export Voltage:** 220 available.

# CAPPUCCINO Dispensers



### Compact Series • 1/2/3 Flavor

Don't let a lack of counter space prevent you from offering hot beverages and cappuccino. The Compact series of moderate volume dispensers provides new opportunities to capitalize on the growing demand for specialty hot beverages.


#### Additional Features For This Series



Slanted Whipper Chamber

Note: Compact series dispensers have non-lit displays.

#### Options For This Series



Portion Control

Electrical

Portion control add "PC" suffix. Electrical options available.

Model	GB1CP	GB2CP	GB3CP
# of Hoppers	1	2	3
Hopper Capacity	8 lbs.	4 lbs.	4 lbs.
Width	7¾"	7¾"	10"
Depth	19"	19"	19"
Height	24"	24"	27"
Tank Capacity	2 gal.	2 gal.	2 gal.
Ship Weight	30 lbs.	32 lbs.	40 lbs.



Compact

**Plumbing:** ¼" Water line required. **Electrical:** 120V, 1.8KW, 15A std. 120/240V, 3KW, 15A, or 6KW, 25A opt. **Export Voltage:** 220 available.



### Low Profile Series • 2/3/4 Flavor

Designed to fit "Spacially" challenged locations with height restrictions and counters with low overhangs. This series of dispensers is only 28½" in height but includes all the features and reliable performance of our standard size dispensers.

#### Additional Features For This Series



F.A.S.T. Service \*

Stainless Drip Tray

Easy Bulb Access \*\*

Slanted Whipper Chamber \*\*\*

\* GB4LP-LD model only. \*\* Except GB2LP-LD.

#### Options For This Series



Portion Control


SMARTSENSE

Electrical

Portion control add "PC" suffix. Smartsense add "SMT" suffix. Electrical options available.

Model	GB2LP-LD	GB3LP-LD	GB4LP-LD
# of Hoppers	2	3	4
Hopper Capacity	4 lbs.	4 lbs.	4 lbs.
Width	8½"	11"	14⅝"
Depth	20"	20"	20"
Height	28½"	28½"	28½"
Tank Capacity	2 gal.	2¾ gal.	2¾ gal.
Ship Weight	70 lbs.	75 lbs.	100 lbs.

**Only 28 ½" In Height!**



Low Profile

**Plumbing:** ¼" Water line required. **Electrical:** 120V, 1.8KW, 15A std. 120/240V, 3KW, 15A, or 6KW, 25A opt. **Export Voltage:** 220 available.

# CAPPUCCINO Dispensers



## Europa Series • 3 Flavor

**A**ttractive contemporary design with large back lit display, draws customers to the dispenser.

### Additional Features For This Series



\* Smartsense, Intelligent Technology 2, & Triple portion control available on GB3E-IT-LD only.

### Options For This Series



Triple portion control available on GB3E-IT-LD only, add "3PC" suffix. Portion control available on GB3E-LD, add "PC" suffix. Electrical options available.

Model	GB3E-LD	GB3E-IT-LD
# of Hoppers	3	3
Hopper Capacity	(1) 10 lbs. (2) 5 lbs.	(1) 10 lbs. (2) 5 lbs.
Width	14"	14"
Depth	25"	25"
Height	37½"	37½"
Tank Capacity	3½ gal.	3½ gal.
Ship Weight	120 lbs.	120 lbs.




**Plumbing:** ¼" Water line required. **Electrical:** 120V, 1.8KW, 15A std. 120/240V, 3KW, 15A, or 6KW, 25A opt. **Export Voltage:** 220 available.



## Multi-Flavor Series • 12 Flavor

**R**equiring only 14" of countertop space, the new Multi-Flavor dispenser offers 12 delicious hot beverages. Dispense lattes, steamers, & cappuccino all from one machine! *Highly concentrated flavors are required for use in these dispensers. Consult your local beverage purveyor for product details or contact Cecilware for more info.*

### Additional Features For This Series



### Options For This Series



Electrical options available.

Model	GB5MF-IT-LD
# of Hoppers	5
Hopper Capacity	(1) 10 lbs. (4) 2 lbs.
Width	14"
Depth	25"
Height	37½"
Tank Capacity	3½ gal.
Ship Weight	120 lbs.



**Plumbing:** ¼" Water line required. **Electrical:** 120V, 1.8KW, 15A std. 120/240V, 3KW, 15A, or 6KW, 25A opt. **Export Voltage:** 220 available.

# CAPPUCCINO Dispensers





## Mini Whipper Series • 1 Flavor


When it comes to dispensing hot chocolate... profit from the experts. With over 20 years experience, Cecilware has redefined and perfected its hot chocolate dispensers to suit all your requirements.

### Features For This Series\*



\* The standard feature set is not available on this series.

### Options For This Series



Portion control add "AT" suffix. Electrical options available.

Model	4914
# of Hoppers	1
Hopper Capacity	8 lbs.
Width	9"
Depth	16"
Height	24"
Tank Capacity	.6 gal.
Ship Weight	29 lbs.



Plumbing: ¼" Water line required. Electrical: 120V, 1.8KW, 15A std. 120/240V, 3KW, 15A, or 6KW, 25A opt. Export Voltage: 220 available.

Mini Whipper



## Compact Whipper Series • 1/2/3 Flavor

Limited counter space? – No Problem! Cecilware incorporates its leading technology into a hot chocolate dispenser for moderate volume locations.

### Additional Features For This Series



Note: Compact Whipper series dispensers have non-lit displays.

### Options For This Series



Portion Control add "PC" suffix. Electrical options available.

Model	GB1HC-CP	GB2HC-CP	GB3HC-CP
# of Hoppers	1	2	3
Hopper Capacity	8 lbs.	4 lbs.	4 lbs.
Width	7¾"	7¾"	10"
Depth	19"	19"	19"
Height	24"	24"	27"
Tank Capacity	2 gal.	2 gal.	2 gal.
Ship Weight	30 lbs.	32 lbs.	40 lbs.



Plumbing: ¼" Water line required. Electrical: 120V, 1.8KW, 15A std. 120/240V, 3KW, 15A, or 6KW, 25A opt. Export Voltage: 220 available.

Compact Whipper

# HOT CHOCOLATE Dispensers



## Whipper Series • 1 Flavor

By incorporating state-of-the-art technology, whipping chambers, direct drive auger systems and vacuum steam removal systems, you can insure your customers delicious, creamy hot chocolate.

### Additional Features For This Series



### Options For This Series



Portion control add "PC" suffix. Smartsense add "SMT" suffix. Hot water dispense button add "W" before "LD" suffix. Electrical options available.

Model	GB1HC
# of Hoppers	1
Hopper Capacity	8 lbs.
Width	9"
Depth	22"
Height	32"
Tank Capacity	2.2 gal.
Ship Weight	30 lbs.



Plumbing: ¼" Water line required. Electrical: 120V, 1.8KW, 15A std. 120/240V, 3KW, 15A, or 6KW, 25A opt. Export Voltage: 220 available.



## SKI Whipper Series • 1&2 Flavor

When It comes to dispensing in volume... Profit from the experts. Single flavor continuous extra heavy volume dispensers.

### Additional Features For This Series



### Options For This Series



Portion control add "PC" suffix. Smartsense add "SMT" suffix. Hot water dispense button add "W" before "LD" suffix. Electrical options available.

Model	GB1SKI-HC	GB2SKI-HC
# of Hoppers	1	2
Hopper Capacity	14 lbs.	14 lbs.
Width	8½"	14½"
Depth	22"	23¾"
Height	37½"	38"
Tank Capacity	3½ gal.	8½ gal.
Ship Weight	85 lbs.	140 lbs.



Plumbing: ¼" Water line required. Electrical: 120/240V, 6KW, 25A std. Export Voltage: 220 available.

Whipper

SKI Whipper

# HOT CHOCOLATE Dispensers



## Super SKI Series • 2 Flavor

Designed for anywhere unusually high volumes of hot beverages are sold: Ski Resorts, Sports Bars, Airports, Stadiums, & Casinos. These units are designed to accommodate continuous extra heavy volume dispensing.

### Additional Features For This Series



\* Available only on GB2 Super SKI-BL-LD-HC.

### Options For This Series



Portion control add "PC" suffix. Smartsense add "SMT" suffix. Hot water dispense button add "W" before "LD" suffix. Electrical options available.

Model	GB2 Super SKI-HC	GB2 Super SKI-BL-LD-HC
# of Hoppers	2	2
Hopper Capacity	14 lbs.	14 lbs.
Width	14 $\frac{1}{8}$ "	14 $\frac{1}{8}$ "
Depth	24 $\frac{1}{4}$ "	24 $\frac{1}{4}$ "
Height	40 $\frac{1}{2}$ "	40 $\frac{1}{2}$ "
Tank Capacity	8 $\frac{1}{2}$ gal.	8 $\frac{1}{2}$ gal.
Ship Weight	155 lbs.	155 lbs.



Plumbing:  $\frac{1}{4}$ " Water line required. Electrical: 230V, 6KW, 26A std. 230V, 9KW, 39A · 230V, 18KW, 78A · 230V, 18KW, 45A 3 Phase opt. Export Voltage: 220 available.

Super SKI



## Multi-Flavor Series • 12 Flavor

Requiring only 14" of countertop space, the new Multi-Flavor dispenser offers 12 delicious hot beverages. Dispense lattes, hot smoothies, & hot chocolate all from one machine! *Highly concentrated flavors are required for use in these dispensers. Consult your local beverage purveyor for product details or contact Cecilware for more info.*

### Additional Features For This Series



### Options For This Series



Electrical options available.

Model	GB5MF-HC-IT-LD
# of Hoppers	5
Hopper Capacity	(2) 5 lbs. (3) 2 lbs.
Width	14"
Depth	25"
Height	37 $\frac{1}{2}$ "
Tank Capacity	3 $\frac{1}{2}$ gal.
Ship Weight	120 lbs.



Plumbing:  $\frac{1}{4}$ " Water line required. Electrical: 120V, 1.8KW, 15A std. 120/240V, 3KW, 15A, or 6KW, 25A opt. Export Voltage: 220 available.

Multi-Flavor

# HOT CHOCOLATE Dispensers

# Hot Beverage Dispensers

Model	Description	Series	Page #	Hopper # & Capacity	Tank Capacity	Burst * Capacity	Dimensions W x D x H	Standard ** Electrical	Ship Weight
<b>1 Flavor Dispense Models</b>									
GB1M-LD	High Volume	Space Saver	3	(1) 8 lbs.	2 gal.	42	8½" x 22" x 31½"	120V, 1.8KW, 15A	65 lbs.
GB1SKI-LD	Extra High Volume	SKI & Super SKI	6	(1) 14 lbs.	3½ gal.	93	8½" x 22" x 37½"	120/240V, 6KW, 25A	85 lbs.
GB1CP	Low Volume	Compact	7	(1) 8 lbs.	2 gal.	38	7¾" x 19" x 24"	120V, 1.8KW, 15A	30 lbs.
4914	Low Volume HC	Mini Whipper	9	(1) 8 lbs.	.6 gal.	12	9" x 16" x 24"	120V, 1.8KW, 15A	29 lbs.
GB1HC-CP	Low Volume HC	Compact Whipper	9	(1) 8 lbs.	2 gal.	38	7¾" x 19" x 24"	120V, 1.8KW, 15A	30 lbs.
GB1HC	High Volume HC	Whipper	10	(1) 8 lbs.	2.2 gal.	42	9" x 22" x 32"	120V, 1.8KW, 15A	30 lbs.
GB1SKI-HC	Extra High Volume HC	SKI Whipper	10	(1) 14 lbs.	3½ gal.	93	8½" x 22" x 37½"	120/240V, 6KW, 25A	85 lbs.
<b>2 Flavor Dispense Models</b>									
2K-GB-LD	Medium Volume	Budget K	2	(2) 4 lbs.	2 gal.	42	8½" x 20" x 31½"	120V, 1.8KW, 15A	70 lbs.
GB2M-5.5-LD	High Volume	Space Saver	3	(2) 5½ lbs.	2 gal.	42	8½" x 22" x 34"	120V, 1.8KW, 15A	86 lbs.
GB2M-5.5-IT-LD	High Volume Digital	IT & Vista IT	4	(2) 5½ lbs.	2.2 gal.	42	9" x 22" x 34"	120V, 1.8KW, 15A	60 lbs.
GB2SKI-LD	Extra High Volume	SKI & Super SKI	6	(2) 14 lbs.	8½ gal.	131	14½" x 23¾" x 38"	120/240V, 6KW, 25A	140 lbs.
GB2 Super SKI	Extra High Volume	SKI & Super SKI	6	(2) 14 lbs.	8½ gal.	150	14½" x 24¼" x 40½"	230V, 6KW, 26A	155 lbs.
GB2 Super SKI-BL-LD	Extra High Volume	SKI & Super SKI	6	(2) 14 lbs.	8½ gal.	150	14½" x 24¼" x 40½"	230V, 6KW, 26A	155 lbs.
GB2CP	Low Volume	Compact	7	(2) 4 lbs.	2 gal.	38	7¾" x 19" x 24"	120V, 1.8KW, 15A	32 lbs.
GB2LP-LD	Low Volume	Low Profile	7	(2) 4 lbs.	2 gal.	32	8½" x 20" x 28½"	120V, 1.8KW, 15A	70 lbs.
GB2HC-CP	Low Volume HC	Compact Whipper	9	(2) 4 lbs.	2 gal.	38	7¾" x 19" x 24"	120V, 1.8KW, 15A	32 lbs.
GB2SKI-HC	Extra High Volume HC	SKI Whipper	10	(2) 14 lbs.	8½ gal.	131	14½" x 23¾" x 38"	120/240V, 6KW, 25A	140 lbs.
GB2 Super SKI-HC	Extra High Volume HC	SKI & Super SKI	11	(2) 14 lbs.	8½ gal.	150	14½" x 24¼" x 40½"	230V, 6KW, 26A	155 lbs.
GB2 Super SKI-BL-LD-HC	Extra High Volume HC	SKI & Super SKI	11	(2) 14 lbs.	8½ gal.	150	14½" x 24¼" x 40½"	230V, 6KW, 26A	155 lbs.
<b>3 Flavor Dispense Models</b>									
3K-GB-LD	Medium Volume	Budget K	2	(3) 4 lbs.	2¾ gal.	53	10" x 20" x 31½"	120V, 1.8KW, 15A	81 lbs.
GB3M-5.5-LD	High Volume	Space Saver	3	(3) 5½ lbs.	2¾ gal.	62	11" x 22" x 34"	120V, 1.8KW, 15A	100 lbs.
GB3M-10-LD	High Volume	Feature Flavor	3	(1) 10 (2) 5 lbs.	3.2 gal.	78	11½" x 22" x 34"	120V, 1.8KW, 15A	90 lbs.
GB3M-10-LD-U	High Volume	Feature Flavor	3	(1) 10 (2) 5 lbs.	3.2 gal.	78	11½" x 22" x 34"	120V, 1.8KW, 15A	90 lbs.
GB3M-10-IT-LD	High Volume Digital	IT & Vista IT	4	(1) 10 (2) 5 lbs.	3.2 gal.	78	11½" x 22" x 35"	120V, 1.8KW, 15A	90 lbs.
GB3MV-310-IT-LD	High Volume Digital	IT & Vista IT	4	(3) 10 lbs.	6 gal.	98	18" x 22" x 35"	120V, 1.8KW, 15A	130 lbs.
GB3MV-310-LD	High Volume	Vista	4	(3) 10 lbs.	6 gal.	98	18" x 22" x 35"	120V, 1.8KW, 15A	130 lbs.
GB3V-CC-LD	Medium Vol. Vending	Vending	6	(3) 5½ lbs.	3.2 gal.	62	15" x 22" x 34"	120V, 1.8KW, 15A	120 lbs.
GB3P-LD	Med. Vol. Pour-Over	Pour-Over	6	(3) 4 lbs.	2½ gal.***	50	11" x 22" x 34"	120V, 1.8KW, 15A	95 lbs.
GB3CP	Low Volume	Compact	7	(3) 4 lbs.	2 gal.	38	10" x 19" x 27"	120V, 1.8KW, 15A	40 lbs.
GB3LP-LD	Low Volume	Low Profile	7	(3) 4 lbs.	2¾ gal.	58	11" x 20" x 28½"	120V, 1.8KW, 15A	75 lbs.
GB3E-LD	High Volume	Europa	8	(1) 10 (2) 5 lbs.	3½ gal.	78	14" x 25" x 37½"	120V, 1.8KW, 15A	120 lbs.
GB3E-IT-LD	High Volume Digital	Europa	8	(1) 10 (2) 5 lbs.	3½ gal.	78	14" x 25" x 37½"	120V, 1.8KW, 15A	120 lbs.
GB3HC-CP	Low Volume HC	Compact Whipper	9	(3) 4 lbs.	2 gal.	38	10" x 19" x 27"	120V, 1.8KW, 15A	40 lbs.
<b>4 Flavor Dispense Models</b>									
4K-GB-LD	Medium Volume	Budget K	2	(4) 4 lbs.	3¾ gal.	78	15½" x 20" x 31½"	120V, 1.8KW, 15A	120 lbs.
GB4M-5.5-LD	High Volume	Space Saver	3	(4) 5½ lbs.	3¾ gal.	78	14½" x 22" x 34"	120V, 1.8KW, 15A	120 lbs.
GB4M-5.5-LD-U	High Volume	Space Saver	3	(4) 5½ lbs.	3¾ gal.	78	14½" x 22" x 34"	120V, 1.8KW, 15A	120 lbs.
GB4MV-210-IT-LD	High Volume Digital	IT & Vista IT	4	(2) 10 (2) 5½ lbs.	6 gal.	98	18" x 22" x 35"	120V, 1.8KW, 15A	130 lbs.
GB4MV-210-LD	High Volume Digital	Vista	4	(2) 10 (2) 5½ lbs.	6 gal.	98	18" x 22" x 35"	120V, 1.8KW, 15A	130 lbs.
GB4LP-LD	Low Volume	Low Profile	7	(4) 4 lbs.	2¾ gal.	58	14½" x 20" x 28½"	120V, 1.8KW, 15A	100 lbs.
<b>5 Flavor Dispense Models</b>									
5K-GB-LD	Medium Volume	Budget K	2	(5) 4 lbs.	3¾ gal.	78	15½" x 20" x 31½"	120V, 1.8KW, 15A	125 lbs.
5K-10-GB-LD	Medium Volume	Budget K	2	(1) 10 (4) 5½ lbs.	6 gal.	98	18" x 20" x 34"	120V, 1.8KW, 15A	130 lbs.
GB5M-10-LD	High Volume	Feature Flavor	3	(1) 10 (4) 5 lbs.	6 gal.	98	18" x 22" x 34"	120V, 1.8KW, 15A	130 lbs.
GB5M-210-LD-U	High Volume	Feature Flavor	3	(2) 10 (3) 5 lbs.	6 gal.	98	20" x 22" x 34"	120V, 1.8KW, 15A	140 lbs.
GB5MV-10-IT-LD	High Volume Digital	IT & Vista IT	4	(1) 10 (4) 5 lbs.	6 gal.	98	18" x 22" x 35"	120V, 1.8KW, 15A	130 lbs.
GB5MV-10-LD	High Volume Digital	Vista	4	(1) 10 (4) 5 lbs.	6 gal.	98	18" x 22" x 35"	120V, 1.8KW, 15A	130 lbs.
<b>6, 8, 10, &amp; 12 Flavor Dispense Models</b>									
GB6M-10-LD-U	High Volume	Destination	5	(1) 10 (5) 5 lbs.	6 gal.	98	21½" x 22" x 34"	120V, 1.8KW, 15A	160 lbs.
GB8M-10-LD-U	High Volume	Destination	5	(1) 10 (7) 5 lbs.	(2) 4 gal.	(2X) 60	27" x 22" x 34"	120V, 1.8KW, 15A	180 lbs.
GB10M-210-LD-U	High Volume	Destination	5	(2) 10 (8) 5 lbs.	(2) 4 gal.	(2X) 60	34" x 22" x 35"	120V, 1.8KW, 15A	200 lbs.
GB12M-210-LD-U	High Volume	Destination	5	(2) 10 (10) 5 lbs.	(2) 4 gal.	(2X) 60	39½" x 22" x 35"	120V, 1.8KW, 15A	220 lbs.
GB6MP-10-LD-U	High Volume	Panorama	5	(1) 10 (5) 5 lbs.	6 gal.	98	22½" x 22" x 34"	120V, 1.8KW, 15A	160 lbs.
GB8MP-10-LD-U	High Volume	Panorama	5	(1) 10 (7) 5 lbs.	(2) 4 gal.	(2X) 60	28" x 22" x 34"	120V, 1.8KW, 15A	180 lbs.
GB5MF-IT-LD	Med. Volume Digital	Multi-Flavor	8	(1) 10 (4) 2 lbs.	3½ gal.	112	14" x 25" x 37½"	120V, 1.8KW, 15A	120 lbs.
GB5MF-HC-IT-LD	Med. Vol. Digital HC	Multi-Flavor	11	(2) 5 (3) 2 lbs.	3½ gal.	112	14" x 25" x 37½"	120V, 1.8KW, 15A	120 lbs.

Specifications subject to change without notice. \*Based on 6 oz. cups. \*\*Export voltage available. \*\*\*Additional 2 gal. reservoir. HC = Hot Chocolate