



Indigo™ Series 850 Ice Cube Machine

Model: ID-0852A IY-0854A ID-0853W IY-0855W ID-0892N IY-0894N Designed for operators who know that ice is critical



Ice Machine Electric

208-230/60/1

(208-230/60/3 and 230/50/1 also available)

Minimum circuit ampacity:

11.9 1ph 9.2 3ph Air-cooled: Water-cooled: 10.9 1ph 8.2 3ph Remote: 11.9 1ph 9.2 3ph

Maximum fuse size:

20 1ph 15 3ph Air-cooled: Water-cooled: 20 1ph 15 3ph Remote: 20 1ph

Specifications

BTU Per Hour:

13,000 (average) 16,000 (peak)

Refrigerant:

R-404A CFC-free

Operating Limits:

- Ambient Temperature Range: 35° to 110°F (1.7° to 43.3°C) Water Temperature Range: 35° to 90°F (1.7° to 32.2°C)
- · Water Pressure Ice Maker Water In: Min. 20 psi (137.9 kPA) Max. 80 psi (551.1 kPA)

to their business, the Indigo™ Series ice machine's preventative diagnostics continually monitor itself for reliable ice production. Improvements in cleanability and programmability make your ice machine easy to own and less expensive to operate.

- Space-Saving Design Up to 940 lbs. (426 kgs.) daily ice production and only 30" (76.20 cm) wide.
- Intelligent Diagnostics provide 24 hour preventative maintenance and diagnostic feedback for trouble free operation.
- Acoustical Ice Sensing Probe for reliable operation in challenging water conditions.
- EasyRead Display communicates operating status, cleaning reminders, and asset information through a blue illuminated display.
- Programmable Ice Production by On/Off Time, Ice Volume or Bin Level (with accessory bin level control) further improves energy efficiency and savings.
- Easy to Clean Foodzone Hinged front door swings out for easy access. Removable water-trough, distribution tube, curtain, and sensing probes for fast and efficient cleaning. Select components made with AlphaSan® antimicrobial.
- DuraTech™ Exterior provides superior corrosion resistance. Stainless finish with innovative clear-coat resists fingerprints and dirt.
- Available LuminIce[™] Growth Inhibitor controls the growth of bacteria and yeast within the foodzone.



Ice Shape



Half Dice (.95 x 2.86 x 2.22 cm)



Dice ½" x ½" x ½" (2.22 x 2.22 x 2.22 cm)













= ISO 9001:2008 =

2110 South 26th Street PO Box 1720 Manitowoc, WI 54221-1720 USA Tel: 1.920.682.0161 Fax: 1.920.683.7589 www.manitowocice.com







i-850 on B-570 Storage Bin (A) Electrical Entrance (2) Options (B) 3/8" (0.95 cm) F.P.T. Water Condenser Inlet (water-cooled units) (C) 1/2" (1.27 cm) F.P.T. Water Condenser Outlet (water-cooled units) (D) 1/2" (1.27 cm) Auxillary Base Drain Socket 26.50" (67.3 cm) A (E) 3/8" (0.95 cm) F.P.T. Ice Making Water Inlet (F) 1/2" (1.27 cm) F.P.T. Ice Making Water Drain **B** @ 3/4" (1.91 cm) Bin Drain 44.00" (111.76 cm) **Installation Note** Minimum installation 34.00" (86.30 cm) clearance: Top/sides: 8" (20.32 cm): Back is 5" (12.7 cm)

Space-Saving Designs





	B-570	B-970*
Height	76.50" 194.30 cm	76.50" 194.30 cm
Width	30.00" 76.20 cm	48.00" 121.92 cm
Depth	34.00" 86.30 cm	34.00" 86.30 cm
Bin Storage	430 lbs. 195 kgs.	710 lbs. 322.2 kgs.

Height includes adjustable bin legs 6.00" to 8.00", (15.24 to 20.32 cm) set at 6.00" (15.24 cm).

* For comparison purposes multiply ARI capacity by 1.3 (30%) to arrive at approximate "Application Rating Capacity."

Specifications

			1	Ice Production 24 Hours		Power Usage kWh/100 lbs. @90°Air/70°F		Water Usage/ 100 lbs. 45.4 kgs. of Ice	ENERGY
		Model	Ice Shape	70°Air/ 50°F Water	90°Air/ 70°F Water	1 Ph	3 Ph	Potable Water	STAR*
		ID-0852A dice	dice	785 lbs.	575 lbs.	6.25	6.25	20.0 Gal.	
	OOLE			356 kgs.	261 kgs.			75.7 L	
	AIR-COOLED	IY-0854A half-dice	half-dice	940 lbs.	650 lbs.	5.54	5.54	20.0 Gal.	*
	A			426 kgs.	295 kgs.			75.7 L	
			dice	835 lbs.	640 lbs.	4.07	4.87	20.0 Gal.	NA
	CED	ID-0853W		379 kgs.	290 kgs.	4.87	4.87	75.7 L	INA
	WATER-COOLED	IY-0855W half-dice	875 lbs.	730 lbs.	4.52	4.52	20.0 Gal.	- NA	
	YER		397 kgs.	331 kgs.			75.7 L		
	/M	* Water-cooled Condenser Water Usage / 100 lbs. /45.4 kgs. Of Ice: 150 gal/568 L. * Water-cooled models are excluded from ENERGY STAR qualification.							
	COOLEC	ID-0892N	dice	750 lbs.	610 lbs.	6.07	6.07	20.0 Gal.	
		ID-0037M		340 kgs.	277 kgs.			75.7 L	
		IY-0894N	half-dice	860 lbs.	645 lbs.	5.78	5.78	20.0 Gal.	_
			The state of the s						

Order ice storage bin separately, Ice storage bin and JC-0895 remote condenser must be ordered separately. Consult remote condenser specification sheet for details. To order 3 phase add "3" suffix to model # (ID-0852A3).

390 kgs.

Accessories

LuminIce™ **Growth Inhibitor** reduces yeast and

bacteria growth for a cleaner ice machine.



Bin Level Control

Allows ice bin level to be automatically set. Built-in LED light illuminates bin.



293 kgs.

Arctic Pure® Water Filters

Reduces sediment and chlorine odors for better tasting ice.



AuCS®

schedules and performs routine ice machine cleaning automatically.



2110 South 26th Street PO Box 1720 Manitowoc, WI 54221-1720 USA Tel: 1.920.682.0161 Fax: 1.920.683.7589 www.manitowocice.com



4771 (replaces 2708F S-850) ©2011 Manitowoc 1/11 Continuing product improvement may necessitate change of specifications without notice