

Blixers®

**Blixer 8****Blixer 10****Blixer 15****Blixer 20 -
Special Order Item**

**Stainless Steel Bowl designed
for vertical cutting and mixing:
puree, mix, chop, and blend.**

- "Stock-pot" shaped stainless steel bowl with bowl and lid scraper and adjustable stainless steel knife assembly:

Blixer 8 - 8 Qt.
Blixer 10 - 10 Qt.
Blixer 15 - 15 Qt.
Blixer 20 - 20 Qt.
- Adjustable patented 2-blade knife assembly for the Blixer 8 and 3-blade knife assembly for the Blixer 10, 15 and 20 provides efficient processing from 16 oz to 14 lbs.
- Advanced Self Diagnostic Safety Control System with motor brake prohibits operation unless bowl and lid are properly locked in position.
- Transparent lid allows observation of the contents being processed and greater control. Lid funnel allows liquids or ingredients to be easily added during processing. Lid is dishwasher safe.
- Brushed stainless steel bowl with handles has high bowl shaft for greater volume processing.
- 3 to 5.5 HP (varies by model) on high speed, 3 phase, 2 speed motor.
- 1 year parts and labor warranty.



Robot Coupe U.S.A., Inc.

P.O. Box 16625

Jackson, MS 39236-6625

1-800-824-1646 • (601) 898-8411

FAX: (601) 898-9134

www.robotcoupeusa.com • e-mail: info@robotcoupeusa.



"The Inventor & World Leader in Food Processors"

Blixer 8-10-15-20

Commercial Food Processor

Specifications

STANDARD MODEL:

Stainless steel bowl with handles, sealed lid equipped with bowl and lid scraper assembly, and adjustable patented 2-blade knife assembly for the Blixer 8 and 3-blade knife assembly or the Blixer 10, 15 and 20.

ELECTRICAL REQUIREMENTS: 208-240V, 60 HZ,

Blixer 8: 9.9 Amps

Blixer 10 : 11.8 Amps

Blixer 15: 17.8 Amps

Blixer 20: 21.3 Amps,

Includes built-in overload protection.

Blixer 8/10/15: Minimum branch circuit protection recommended: 20 Amps. Nema #L15-20P.
Blixer20: Minimum branch circuit protection recommended: 30 Amps. Nema #L15-30P.

SWITCHING: Magnetic safety switch, two speed control, push-button "ON-OFF", and power indicator lights.

Specifications

MOTOR: Blixer 8: 3 HP, Three phase, 2 speed
1800/3600 RPM,
Blixer 10: 3.5 HP, Three phase, 2 speed
1800/3600 RPM,
Blixer 15: 4 HP, Three phase, 2 speed
1800/3600 RPM,
Blixer 20: 5.5 HP, Three phase, 2 speed
1800/3600 RPM,

WEIGHT: Blixer 8 - 115 lbs. approximate shipping weight.
Blixer 10 - 126 lbs. approximate shipping weight.
Blixer 15 - 137 lbs. approximate shipping weight
Blixer 20 - 194 lbs. approximate shipping weight.

STANDARDS: ETL electrical & sanitation

Robot Coupe U.S.A., Inc.
P.O. Box 16625
Jackson, MS 39236-6625
1-800-824-1646
(601) 898-8411
FAX: (601) 898-9134
www.robotcoupeusa.com
e-mail: info@robotcoupeusa.com

Distributed by: