

1250 Victoria St Carson, CA 90746 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Project :		
Model #:		
Item #:	Qty:	
Available W/H :		
Approval :		

## Combination Bakery Case

Display Cases Dry/Refrigerated Combination Cases

**Model: TCB-5R** 



#### \_\_\_FEATURES / BENEFITS =\_\_

■ ENVIRONMENTALLY FRIENDLY, EFFICIENT REFRIG-ERATION SYSTEM

Turbo Air's refrigerators are designed with oversized and balanced environmentally friendly R-134A (CFC Free) refrigeration. Theses include large evaporators and condensers for faster cooling and balanced temperature throughout the cabinet.

- FRAMELESS GLASS AND ELEGANT EURO DESIGN
  The frameless all sided glass display cases provide full product visibility
  to optimize display effects and increase impulse sales. Its elegant
  contemporary euro design will not only enhance any store atmosphere
  but also will keep product presentation at its best and beautiful.
- LIFT-UP, PNEUMATIC CYLINDER-ASSISTED CURVED TEMPERED FRONT GLASS
- SLOPED REAR DOORS FOR PRODUCT ACCESS
- INDEPENDENTLY WIRED SHELF LIGHTS
- CANTILEVERED WIRED SHELVES ADJUSTABLE UP AND DOWN, TILTED
- 304 STAINLESS STEEL FLOOR AND AIR FLOW GRILLE

■ HIGH-DENSITY POLYURETHANE INSULATION

The entire cabinet structure is foamed-in-place using high density, CFC free polyurethane insulation.

- Four Point Leveling System
- **EASY ACCESS CONTROL PANEL**
- REFRIGERATED BAKERY CASE HOLDS AVG. 38°F ~ 40°F FOR FRESHER BAKERY PRODUCTS
- REAR ACCESS OF COMPRESSOR COMPART-MENT FOR QUICK AND EASY SERVICE
- 5" CASTERS STANDARD
- RECOMMENDED OPERATING CONDITIONS

TB models are designed to operate in environments where temperature & humidity do not exceed 75°F and 55% relative humidity.









Model	CU./FT.	# of Shelves	НР	AMPS	Crated Weight (lbs.)	L x D*x H† (inches)
TCB-5R	18.6	4	1/3	9	1,004	591/4 x 373/8 x 471/4

# Combination Bakery Case

### **Model: TCB-5R**

ELECTRICAL DATA				
Voltage	115/60/1			
Plug Type	<ul><li>○ NEMA-5-20P</li></ul>			
Full Load Amperes	9			
Compressor HP	1/3			
Refrigerant	R-134A			
Cord Length (ft.)	9			
DIMENSIONAL DATA				
Net Capacity cu. ft.	18.6 (D-9.3, R-9.3)			
Ext. Length Overall in.	59 <sub>1/4</sub> (1505mm)			
Ext. Depth Overall in.*	373/8 (950mm)			
Ext. Height Overall in.†	47 <sub>1/4</sub> (1200mm)			
Int. Length Overall in.	(D)271/8(690mm) (R)271/4(692mm)			
Int. Depth Overall in.	261/2 (673mm)			
Int. Height Overall in.	261/8 (665mm)			
Crated Weight lbs.	754			
# of Shelves	4			
Self Size	(Top) 261/4 x 167/8			
	(Bottom) 263/4 x 255/8			

Design and specifications subject to change without notice.


Actual shipping weight may differ due to extra packing materials for product protection.

† Height does not include 5-1/4" caster height.

# 2 Year Parts and Labor Warranty Additional 3 Year Warranty on Compressor

- SELF-CONTAINED SYSTEM, NO PLUMBING REQUIRED
- SIMPLE PLUG-IN INSTALLATION

#### **PLAN VIEW** (unit: inch)



38 (964mm) 373/8 (950mm) 285/8 (726mm) 183/4 (475mm) 51/4

SIDE VIEW


Ver.201301











■ Warranty: 800-381-7770 ■ AC: 888-900-1002











<sup>\*</sup>Depth does not include 2-5/8" for door handle.