



Project:

Item Number:

Quantity:

Rethermalizers: Heat 'N Serve 4/3 Rectangle

The Vollrath Company, L.L.C.

RETHEMALIZERS: HEAT 'N SERVE 4/3 RECTANGLE



Item 72050



72050 with
19188 Adaptor Plate,
78184 Insets and
47488 Covers.



Item 72051

Heat 'N Serve 4/3 Rectangle Rethermalizer

MODELS:	72050	120V AC, 1600W
	72051	120V AC, 1600W
	72055	120V AC, 1600W (Canada Only)
	72056	120V AC, 1600W (Canada Only)

FEATURES

- Thermoset fiber-reinforced, self-insulating resin well provides maximum energy efficiency.
- Low water indicator light eliminates guesswork.
- 33% greater capacity than full-size warmers – holds four 1/3 size pans up to 6" (15.24 cm) deep.
- Capillary tube thermostat for more accurate temperature control.
- Two 800 watt elements for rethermalization and faster recovery.
- Elements have non-stick surface to prevent scale build-up and reduce cleaning time.
- Wide no-drip lip keeps countertop dry and returns condensation to well.
- Lighted ON/OFF switch.
- Bottom exit cord - 6-ft. (183 cm) length.
- Optional adaptor plate available with three 8 3/8" (21.3 cm) diameter holes for 7 1/4 qt. round insets.
- Optional adapter bars recommended to conserve energy.
- Stainless steel exterior for easy cleaning.

DESCRIPTION

This countertop merchandiser is designed for maximum capacity within a minimum footprint.



PERFORMANCE CRITERIA

The Heat 'N Serve 4/3 Rethermalizers are designed to take a container of cooked food from a chilled state (below 40.0° F [4.4° C]) through the HACCP "danger zone" of 165° F (73.9° C) in less than 90 minutes. The performance standard is measured using the NSF mixture chilled to 35° F (1.7° C). The electric unit will raise the temperature of this product above 165° F (73.9° C) in less than 90 minutes. The temperature will be maintained above 150° F (65.6° C) when the food product and pan or inset are used with a standard pan or inset cover, the proper water level is maintained in the well, and the food product is stirred regularly.

DIMENSIONS AND RATINGS

Item	Description	Maximum Dimensions (L X W X H) IN (CM)	Voltage	Watts	Amps	Plug	Case Lot
72050	Without Drain	28 3/4 x 13 3/4 x 9 3/4 (73 x 34.9 x 24.8)	120V AC	1600	13.3	5-15P	1
72051	With Drain	28 3/4 x 13 3/4 x 13 9/32 (73 x 34.9 x 33.7)	120V AC	1600	13.3	5-15P	1
72055	Without Drain (Canada Only)	28 3/4 x 13 3/4 x 9 3/4 (73 x 34.9 x 24.8)	120V AC	1600	13.3	5-20P	1
72056	With Drain (Canada Only)	28 3/4 x 13 3/4 x 13 9/32 (73 x 34.9 x 33.7)	120V AC	1600	13.3	5-20P	1
19188	Adaptor Plate with three 8 3/8" (21.3 cm) diameter holes for 7 1/4 qt. round insets.						1
75012	Adaptor Bars, 12 15/16" x 1" x 1/4" (32.9 x 2.5 x 0.6 cm)						12

Receptacles



Agency Listings



Approvals

Date:



Setting the Standard™

www.vollrathco.com

The Vollrath Company, L.L.C.
1236 North 18th Street
Sheboygan, WI 53082-0611
U.S.A.
Main Tel: 800.624.2051
Service Tel: 800.628.0832
FAX: 800.752.5620

Vollrath of Canada, Co.
Tel: 800.695.8560
FAX: 800.752.5620