



Project:

Item Number:

Quantity:

Rethermalizers: Nitro™ Power Rethermalizer

The Vollrath Company, L.L.C.

RETHEMALIZERS: NITRO™ POWER RETHEMALIZER

MODELS: 72090 120V AC, 1440 W



Nitro™ Power Rethermalizer

FEATURES

- 18-8 stainless steel well
- High-efficiency 1440 watt element that operates on 15A circuit
- Almost twice the water capacity of other countertop models, reducing need to refill the well as often
- Holds with wet or dry heat – moist heat always recommended for best performance and preserving food quality.
- Recommended using full or fractional size pans up to 4" (10.2 cm) deep
- Heavy-duty bulb and capillary thermostat with overtemp protection
- Adjustable 1" (2.5 cm) feet
- Meets NSF4 performance standards when using moist heat
- 6-ft. (183 cm) cord and plug

DESCRIPTION


Rethermalizer is sized to hold one full-size pan or equivalent fractional pans (adaptor bars recommended with fractional pans). The 1440 watt element is designed to operate on 120V, 15A service. Unit has a deeper stainless steel well for greater water capacity. Bulb and capillary thermostat for precise temperature control.

PERFORMANCE CRITERIA

Nitro Cookers are designed to take a container of cooked food from a chilled state (below 40.0° F [4.4° C]) through the HACCP “danger zone” of 165° F (73.9° C) in less than 90 minutes. The performance standard is measured using the NSF mixture chilled to 35° F (1.7° C). The electric unit will raise the temperature of this product above 165° F (73.9° C) in less than 90 minutes. The temperature will be maintained above 150° F (65.6° C) when the food product and pan or inset are used with a standard pan or inset cover, the proper water level is maintained in the well, and the food product is stirred regularly.

DIMENSIONS AND RATINGS

Receptacle



Item	Description	Dimensions			Voltage	Watts	Amps	Plug	Case Lot
		(L X W X H) IN (CM)							
72090	PC-21, full-size rethermalizer	22 x 14 x 9½ (55.9 x 35.6 x 24.1)			120V AC	1440	12.0	5-15P	1

Agency Listings



Approvals

Date:



Setting the Standard™

www.vollrathco.com

The Vollrath Company, L.L.C.
1236 North 18th Street
Sheboygan, WI 53082-0611
U.S.A.
Main Tel: 800.624.2051
Service Tel: 800.628.0832
FAX: 800.752.5620

Vollrath of Canada, Ltd.
Tel: 800.695.8560
FAX: 800.752.5620