

Project:

Item Number:

Quantity:

# Warmers: Cayenne® Models 3001D, 3002D



Drop-in Warmers

## **DESCRIPTION**

Drop-ins are designed with a self-insulating, energy efficient thermoset well for ease of installation in solid-surface, laminate, or metal countertops. Minimal heat transfer to the work surface allows the drop-ins to be installed without a thermal breaker strip.

All thermoset well drop-ins have a high-efficiency cast aluminum dome element positioned in the bottom of the well for direct energy transfer. Dome element requires that the unit must be used with water in the well. All units include a standard drain and drain valve.

## PERFORMANCE CRITERIA

Drop-in warmers are designed to hold heated prepared foods at temperatures above the HACCP "danger zone" of  $140^{\circ}$  F ( $60^{\circ}$  C). The performance standard is measured using the NSF mixture preheated to  $165^{\circ}$  F ( $73.9^{\circ}$  C). The unit will hold the temperature of this product above  $150^{\circ}$  F ( $65.6^{\circ}$  C). The temperature will be maintained best when the food product is held using pans with covers, the proper water level is maintained in the well, and the food product is stirred regularly.

#### **Agency Listings**





MODELS: 72105 120V AC, 700W 72107 120V AC, 700W

### **FEATURES**

- □ Self-insulating thermoset well with exclusive direct-contact heating system provides the optimum design for energy-efficient operation and lower operating costs
- ☐ Thermoset fiber-reinforced, self-insulating resin wells provide maximum insulation
- ☐ Low water indicator light eliminates guesswork
- ☐ 6-ft. (183 cm) cord and plug
- □ Top mounting installation
- □ Standard drain for easy cleaning
- □ Recommend using full or fractional size pans up to 4" (10.2 cm) deep
- Meets NSF4 performance standards
- ☐ Thermostatic temperature control
- ☐ Cast aluminum non-stick dome element

<b>Approvals</b>		
	Date:	



The Vollrath Company, L.L.C. 1236 North 18th Street Sheboygan, WI 53081-3201 U.S.A.

Main Tel: 800.628-0830 Service Tel: 800.628.0832 FAX: 800.752.5620 Vollrath of Canada, Co. Tel: 800.695.8560 FAX: 800.752.5620

MODELS:	72105 72107	120V AC, 120V AC,								
DIMENSIO	NS AND R	ATINGS		Cutout	Dimensions					
Item		Description	1	Dimensions IN (CM)	(L X W X H) IN (CM)	Voltage	Watts	Amps	Plug	Case Lot
72105 Model 3001D drop-in warmer with drain, unit-mounted temperature control			121/8 x 201/8 (32.7 x 53)	21¾ x 13¾ x 9 (55 x 33 x 23)	120V AC	700	5.8	5-15P	1	
front i Contro	mounted con ol Panel Dime	trol panel wit ensions: 4½"	vith drain, remote h flexible conduit. x 6" (11.4 x 15.2 cm) .9 x 12.7 cm)	13¾6 x 21¾6 (33.5 x 53.8)	21¾ x 13¾ x 9 (55 x 33 x 23)	120V AC	700	5.8	Hard Wire	1
			,					Re	ecepta	cle
Model 721	05								120V	
-	13.655 (34.684)	-	-		(55.004) .759) INS INT. —	-	-		5-15F	/
							9.01:			
	11.613 (29.497)				1.905 cm) NPT / ded drain tube					
Model 72	107 - 13.655 - (34.684) -		-		55.004) ———— .759) INS INT. —					
A A		H III				2	.015 2.898			
	6.0 (15.24)						28.			



11.613 (29.497)

The Vollrath Company, L.L.C. 1236 North 18th Street Sheboygan, WI 53081-3201 U.S.A.

Control panel with lighted switch

and temperature control

Main Tel: 800.628-0830 Service Tel: 800.628.0832 FAX: 800.752.5620

Vollrath of Canada, Co. Tel: 800.695.8560 FAX: 800.752.5620

4.5 (11.43)

24" (60.96 cm) flexible conduit