

# Drop-in Refrigerated Cold Wells

PRODUCT: QUANTITY:

### **Designed Smart**

### **Compact Design with High Output**

The Drop-In Cold Well provides an economic solution to the cost of in-counter refrigeration.

- Uses R-134a refrigerant.
- Can hold cold food at 34 F to 40 F for extended periods.
- Interior temperature is factory set, but can be field adjusted depending on unit's application.

### **APW Wyott Design Features**

- Holds standard steam table pans
- Energy saving
- Field adjustable temperature
- · Stainless steel construction with fully insulated walls
- Supplied with 6 ft. cord and NEMA 5-15P plug
- Drain provided with stopper

## **Option and Accessories**

- COMP-5 5-year compressor warranty
- Pan dividers standard; special adaptor top for pans available



Model: Drop-In Cold Well

# Reliability backed by APW Wyott's Warranty

APW Wyott Drop-In Cold Wells are backed by a 1-year parts and labor warranty, including on-site service calls within 50 miles of authorized service technicians.

## Certified by the following agencies:








See reverse side for product specifications.





# Drop-in Refrigerated Cold Wells



#### PRODUCT SPECIFICATIONS

#### Construction:

Interior is stainless steel; exterior is aluminized steel

Freight Class: 100 FOB: Cheyenne, 82007

INSIDE DIMENSIONS					
Model	Width	Length			
CW-1	13 1/2" (34.3cm)	22" (55.9cm)			
CW-2	22" (55.9cm)	26 13/16" (68.1cm)			
CW-3	22" (55.9cm)	40 1/8" (101.9cm)			
CW-4	22" (55.9cm)	53 7/16" (135.7cm)			
CW-5	22" (55.9cm)	66 3/4: (169.5cm)			
CW-6	19 7/8"	80 1/2"			

#### **Electrical SPECIFICATIONS**

MODEL	VOLTS	Hz	PHASE	AMPS	COMPRESSOR	CHARGE
CW-1	120	60	1	4	1/5 HP	8.75 ozR134A
CW-1	230	50	1	2	1/5 HP	8.75 ozR134A
CW-2	120	60	1	4	1/4 HP	9.50 ozR134A
CW-2	230	50	1	2	1/4 HP	9.50 ozR134A
CW-3	120	60	1	4	1/4 HP	10.0 ozR134A
CW-3	230	50	1	2	1/4 HP	10.0 ozR134A
CW-4	120	60	1	4	1/4 HP	11.0 ozR134A
CW-4	230	50	1	2	1/4 HP	11.0 ozR134A
CW-5	120	60	1	5.5	1/3 HP	12.0 ozR134A
CW-5	230	50	1	2.8	1/3 HP	12.0 ozR134A
CW-6	115	60	1	15.3	3/4HP	54 oz. – R404A

#### **DIMENSIONS**

MODEL	DIMENSIONS	RECOMMENDED CUT OUT
CW-1	28"L x 19 1/2"W x 23 13/16"H	26 1/2" x 18"
CW-2	32 13/16"L x 28"W x 23 13/16"H	26 1/2" x 31 5/16"
CW-3	46 1/8"L x 28"W x 23 13*16"H	26 1/2" x 44 5/8"
CW-4	59 7/16"L x 28"W x 23 13/16"H	26 1/2" x 57 15/16"
CW-5	72 3/4"L x 28"W x 23 13/16"H	26 1/2" x 71 1/4"
CW-6	86"L x 25 3/8" x 24.5"H	23 7/8" x 841/2"

<sup>\*</sup>APW Wyott reserves the right to modify specifications or discontinue models without incurring obligation.

