

MATERIAL SAFETY DATA SHEET

This MSDS complies with OSHA'S Hazard Communication Standard 29 CFR 1910.1200 and OSHA Form 174

IDENTITY AND MANUFACTURER'S INFORMATION	
NFPA Rating: Health-2; Flammability-3; Reactivity-0; Special---	HMIS Rating: Health-2; Flammability-3; Reactivity-0; Personal Protection-B
Date Prepared: 08/26/05 Prepared By: IB	DOT Hazard Classification: ORM-D Identity (trade name as used on label): <b style="text-align: center;">LUBRI-QUIK SILICONE SPRAY
Information Calls: (770)422-2071 EMERGENCY RESPONSE NUMBER: 1(800)255-3924	MSDS Number: A00329 Revision- 1 NOTICE: JUDGEMENT BASED ON INDIRECT TEST DATA

SECTION 1 - MATERIAL IDENTIFICATION AND INFORMATION					
COMPONENTS-CHEMICAL NAMES AND COMMON NAMES (Hazardous Components 1% or greater; Carcinogens 0.1% or greater)	CAS Number	SARA III LIST	OSHA PEL (ppm)	ACGIH TLV (ppm)	Carcinogen Ref. Source **
ACETONE	67-64-1	No	1000	750	d
HEPTANE	142-82-5	No	500	400	d
ISOBUTANE/PROPANE BLEND	75-28-5	No	800	800	d
	74-98-6	No	1000	1000	d

SECTION 2 - PHYSICAL/CHEMICAL CHARACTERISTICS	
Boiling Point: (Concentrate Only) not determined Vapor Pressure: PSIG @ 70°F (Aerosols): 60 max Vapor Density (Air = 1): not determined Solubility in Water: partially	Specific Gravity (H2O=1): Concentrate Only = 0.751 Vapor Pressure (Non-Aerosols)(mm Hg and Temperature): N/A Evaporation Rate (water= 1): greater than 1 Water Reactive: No
Appearance and Odor: Clear, colorless spray with solvent odor.	

SECTION 3 - FIRE AND EXPLOSION HAZARD DATA		
FLAMMABILITY as per USA FLAME PROJECTION TEST (aerosols) est.greater than 18", flashback to tip; categorized: EXTREMELY FLAMMABLE	Auto Ignition Temperature N/E	Flammability Limits in Air by % in Volume: % LEL: N/E % UEL: N/E
FLASH POINT AND METHOD USED (non-aerosols): N/A SPECIAL FIRE FIGHTING PROCEDURES: Self-contained breathing apparatus.		
EXTINGUISHER MEDIA: Foam, dry chemical, carbon dioxide.		
Unusual Fire & Explosion Hazards: Do not expose aerosols to temperatures above 130°F or the container may rupture. Product contains silicone and can result in slippery walking surfaces if leakage occurs.		

SECTION 4 - REACTIVITY HAZARD DATA	
STABILITY [X] STABLE [] UNSTABLE Incompatibility (Mat. to avoid): Strong oxidizing agents.	HAZARDOUS POLYMERIZATION [] WILL [X] WILL NOT OCCUR Conditions to Avoid: Open flame, welding arcs, heat, sparks.
Hazardous Decomposition Products: Carbon dioxide, carbon monoxide.	

SECTION 5 - HEALTH HAZARD DATA	
PRIMARY ROUTES OF ENTRY: [X] INHALATION [] INGESTION [X] SKIN ABSORPTION [] EYE [] NOT HAZARDOUS	
ACUTE EFFECTS Inhalation: Excessive inhalation of vapors can cause nasal & respiratory irritation, dizziness, weakness, nausea, headache, possible unconsciousness or asphyxiation. Eye Contact: Slight irritation. Eye Contact: Slight irritation. Ingestion: Irritation.	
CHRONIC EFFECTS: (Effects due to excessive exposure to the raw materials of this mixture) Excessive inhalation may result in central nervous system effects. Medical Conditions Generally Aggravated by Exposure: May aggravate existing eye, skin, or upper respiratory conditions.	

EMERGENCY FIRST AID PROCEDURES	
Eye Contact: Flush with water for 15 minutes. If irritated, seek medical attention.	
Skin Contact: Wash with soap and water. If irritated, seek medical attention.	
Inhalation: Remove to fresh air. Resuscitate if necessary. Get medical attention.	
Ingestion: DO NOT INDUCE VOMITING. Drink two large glasses of water. Get immediate medical attention.	

SECTION 6 - CONTROL AND PROTECTIVE MEASURES	
Respiratory Protection (specify type): If vapor concentration exceeds TLV, use respirator approved by NIOSH for organic vapors.	
Protective Gloves: Neoprene gloves recommended. Eye Protection: Safety glasses recommended.	
Ventilation Requirements: Adequate ventilation to keep vapor concentration below TLV.	
Other Protective Clothing & Equipment: None	
Hygienic Work Practices: Wash with soap and water before handling food. Remove contaminated clothing.	

SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE	
Steps To Be Taken If Material Is Spilled Or Released: Absorb with suitable medium. Incinerate or landfill according to local, state or Federal regulations. Allow to evaporate if small spill. DO NOT FLUSH TO SEWER.	
Waste Disposal Methods: Aerosol cans when vented to atmospheric pressure through normal use, pose no disposal hazard.	
Precautions To Be Taken In Handling & Storage: Do not puncture or incinerate containers. Do not store at temperatures above 130°F.	
Other Precautions &/or Special Hazards: KEEP OUT OF REACH OF CHILDREN. Avoid food contamination. Avoid inhalation of vapors.	

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind.
 ** Chemical Listed as Carcinogen or Potential Carcinogen. [a] NTP [b] IARC Monograph [c] OSHA [d] Not Listed [e] Animal Data Only