



Item# _____

Job _____



Standard



5MB Wheel Brake



5M Resilient

Stainless Steel, Cart Washable



5MDBGSA



5MDGSA

Polymer Casters



5PC



5PCB

METRO™ STEM CASTERS

- **Metro Stem-Type Casters** are designed to fit Super Erecta Shelf® posts to form shelf carts and other mobile units.
- **Stainless Steel, Cart-Washable Casters** offer grease seals and zerk fittings. Can withstand high-pressure washings.
- **Polymer Casters:** Innovative polymer stem casters offer total corrosion resistance and enhanced durability. For all medium-duty applications.
- **Resilient Rubber Tread:** A molded, soft tread that provides good floor protection along with quiet operation. Non-marking.
- **Polyurethane Tread:** Long-wearing; resists abrasion. Non-marking, shock absorbing.
- **Wheel Brakes:** Foot-operated. Available on all caster models.
- **Caster Load Ratings:** From 125 lbs. to 300 lbs. (57 to 136kg).
- **Donut Bumpers:** Furnished standard on all Metro stem casters.
- **Additional Caster Types Available.**

Note: SPECIAL WHEELS — V-groove, Conductive, Steel and Phenolic — are available on request. For additional information, contact InterMetro Industries Corporation or your InterMetro representative.



InterMetro Industries Corporation
North Washington Street
Wilkes-Barre, PA 18705
www.metro.com

METRO™ STEM CASTERS



DIMENSIONS: Standard Casters — Stem-Type

| Cat. No. | Type | Wheel Dia. | | Face | | Wheel Tread | Load Rating | | Approx. Pkd. Wt. | |
|----------|-------------|------------|------|-------|------|--------------------|-------------|------|------------------|------|
| | | (in.) | (mm) | (in.) | (mm) | | (lbs.) | (kg) | (lbs.) | (kg) |
| 4LD | Stem/Swivel | 4 | 102 | 1/2 | 12 | Resilient | 125 | 56 | 1 1/2 | .6 |
| 5LD | Stem/Swivel | 5 | 127 | 1/2 | 12 | Resilient | 125 | 56 | 2 | .9 |
| 5M | Stem/Swivel | 5 | 127 | 1 1/4 | 32 | Resilient | 200 | 90 | 2 1/2 | 1.1 |
| 5MB | Stem/Brake | 5 | 127 | 1 1/4 | 32 | Resilient | 200 | 90 | 2 3/4 | 1.2 |
| 5MR | Stem/Rigid | 5 | 127 | 1 1/4 | 32 | Resilient | 200 | 90 | 3 1/2 | 1.5 |
| 5MDA | Stem/Swivel | 5 | 127 | 1 1/4 | 32 | High Modulus Donut | 250 | 111 | 2 1/2 | 1.1 |
| 5MDBA | Stem/Brake | 5 | 127 | 1 1/4 | 32 | High Modulus Donut | 250 | 111 | 2 5/8 | 1.17 |
| 5MDRA | Stem/Rigid | 5 | 127 | 1 1/4 | 32 | High Modulus Donut | 250 | 111 | 2 3/8 | 1.08 |
| 5MP | Stem/Swivel | 5 | 127 | 1 1/4 | 32 | Polyurethane | 300 | 135 | 2 1/8 | .94 |
| 5MPB | Stem/Brake | 5 | 127 | 1 1/4 | 32 | Polyurethane | 300 | 135 | 2 1/4 | 1 |
| 5MPR | Stem/Rigid | 5 | 127 | 1 1/4 | 32 | Polyurethane | 300 | 135 | 2 | .9 |

NOTE 1: Stem casters are shipped with donut bumper **at no additional charge**.

NOTE 2: Rigid casters are held in position by a connecting channel. When ordering rigid casters, shelf width must be known.

NOTE 3: Load Height for all 5M, 5MD and 5MP casters — 6 7/32" ± 1/16" (155 ± 1.5mm).

NOTE 4: Load Height for 4LD caster — 4 5/8" ± 1/16" (118 ± 1.5mm).

NOTE 5: Load Height for 5LD caster — 5 5/8" ± 1/16" (143 ± 1.5mm).

NOTE 6: Brakes are foot-operated.

DIMENSIONS: Stainless Steel Cart-Washable Casters — Stem-Type

| Cat. No. | Type | Wheel Dia. | | Face | | Wheel Tread | Load Rating | | Approx. Pkd. Wt. | |
|----------|--------|------------|------|-------|------|--------------------|-------------|------|------------------|------|
| | | (in.) | (mm) | (in.) | (mm) | | (lbs.) | (kg) | (lbs.) | (kg) |
| 5MDGSA | Swivel | 5 | 127 | 1 1/4 | 32 | High Modulus Donut | 150 | 68 | 2 1/2 | 1.1 |
| 5MDBGSA | Brake | 5 | 127 | 1 1/4 | 32 | High Modulus Donut | 150 | 68 | 2 5/8 | 1.17 |
| 5MDRGSA | Rigid | 5 | 127 | 1 1/4 | 32 | High Modulus Donut | 150 | 68 | 2 3/8 | 1.08 |
| 5MPGSA | Swivel | 5 | 127 | 1 1/4 | 32 | Polyurethane | 300 | 135 | 2 1/8 | .94 |
| 5MPBGSA | Brake | 5 | 127 | 1 1/4 | 32 | Polyurethane | 300 | 135 | 2 1/4 | 1 |
| 5MPRGSA | Rigid | 5 | 127 | 1 1/4 | 32 | Polyurethane | 300 | 135 | 2 | .9 |

NOTE 1: Stem casters are shipped with donut bumper **at no extra charge**.

NOTE 2: Rigid casters are held in position by a connecting channel. When ordering rigid casters, shelf width must be known.

NOTE 3: Load Height for all 5MD and 5MP casters — 6 7/32" ± 1/16" (155 ± 1.5mm).

NOTE 4: All casters are grease sealed with zerk fittings in swivel and axle.

NOTE 5: Brakes are foot-operated.

NOTE 6: "D" in model number designates donut wheel made of high-modulus rubber.

DIMENSIONS: Polymer Casters — Stem-Type

| Cat. No. | Type | Wheel Dia. | | Face | | Wheel Tread | Load Rating | | Approx. Pkd. Wt. | |
|----------|--------|------------|------|-------|------|--------------|-------------|------|------------------|------|
| | | (in.) | (mm) | (in.) | (mm) | | (lbs.) | (kg) | (lbs.) | (kg) |
| 5PC | Swivel | 5 | 127 | 1 1/4 | 32 | Polyurethane | 300 | 135 | 2 | .9 |
| 5PCB | Brake | 5 | 127 | 1 1/4 | 32 | Polyurethane | 300 | 135 | 2 | .9 |
| 5PCR | Rigid | 5 | 127 | 1 1/4 | 32 | Polyurethane | 300 | 135 | 2 | .9 |

NOTE 1: Optional thread guards (blue) may be ordered by adding "-TG" to the desired model number (eg. 5PC-TG, 5PCB-TG, 5PCR-TG)

NOTE 2: Stem casters are shipped with donut bumpers **at no extra charge**.

NOTE 3: Rigid casters are held in place by a connecting channel. When ordering, shelf depth **must be** provided.

Manufactured by:
InterMetro Industries Corp.
North Washington Street
Wilkes-Barre, PA 18705

Phone 717-825-2741
FAX 717-825-2852
For Product Information, call 1-800-433-2232
For Customer Service, call 1-800-992-1776



InterMetro Industries Corporation
North Washington Street
Wilkes-Barre, PA 18705
www.metro.com

L02-041
Rev. 9/98 BJ
Printed in U.S.A.
Information and specifications are subject to change
without notice. Please confirm at time of order.