

6•10EsiN SERIES COMBITHERM® COMBIOVEN



MODEL 6•10EsiN WITH COMBITOUCH CONTROL
CAPACITY OF SIX (6) FULL-SIZE OR GN 1/1 PANS,
SIX (6) HALF-SIZE SHEET PANS



- EcoSmart design uses less electricity and water than competitive models. Reduced energy setting further minimizes electricity use.
- Exclusive Gold-n-Brown™ features gives the operator the ability to achieve the ideal cooking environment for the ideal finish.

- Expandable system to meet your specific requirements.
- Cook with the included product temperature probe (not included as standard on S-control models) or by time.
- Cooks with variable steam, convection heat, or a combination of both to roast, steam, bake, or oven-fry. Cooking speeds are increased by as much as 70% compared to conventional cooking methods.
- CombiClean® feature uses jets of water for fully automated cleaning. Use either commercial-strength CombiClean Tablets or Combitherm Cleaning Liquid Spray.
- Boiler-free flash-steam generation increases reliability by eliminating boiler maintenance and boiler heating element burnout. Steam levels are maintained without a water reservoir.
- Optional CombiSmoker® oven with smoking technology smokes any product, hot or cold.
- **CombiTouch®**
 - Intuitive CombiTouch control is fully operable from the touch screen.
 - Store up to 250 recipes, each with up to 9 steps. CombiTouch comes standard with more than 100 preprogrammed recipes and photos.
 - Six precise and consistent Gold-n-Brown™ browning levels.
 - Multi-shelf Timers track cooking time of seven different food items in the same oven.
 - Advance reversing fan design provides excellent baking results and prevents excessive water and power consumption.



Provide Alto-Shaam Combitherm® counter-top Model 6•10EsiN flash-steam electric CombiOven designed with EcoSmart® technology for reduced energy and water usage and include operational modes for steam, convection, and a combination of steam and convection heat. Standard features to include patented automatic steam venting; Gold-n-Brown™ browning function and a self-adjusting, flush-mounted rotary door handle. Oven is to be constructed of 18 gauge stainless steel, include an attached spray hose with backflow preventer, cool-down function, automatic cleaning function, and four (4) adjustable legs. Each oven is to accommodate up to 6 half-size sheet pans or 6 full-size hotel pans, include standard right-hand door hinging, six (6) non-tilt support rails (13" (330mm) horizontal width between rails, and 3" (76mm) vertical spacing between rails), and three (3) stainless steel shelves.

- | | | |
|--------------------------|-----------------------------|--|
| ☐ | CombiTouch® Control: | includes six different browning levels; two-speed reversing fan with coordinated venting system, USB port for data access, quick-connect single-point internal product temperature probe in the oven interior. |
| ☐ | Deluxe Control: | includes a quick-connect single-point internal product temperature probe in the oven interior and programming capability with Rapid-Touch™ operational quick-keys. |
| ☐ | Standard Control: | includes a quick-connect single-point internal product temperature probe in the oven interior. |
| ☐ | S-Control: | with quick-connect single-point internal product temperature probe in the oven interior as an option. |

FACTORY INSTALLED


- | | | | |
|---|---|--|--|
| <ul style="list-style-type: none"> • Electrical Choices <ul style="list-style-type: none"> ➔Specify voltage: <ul style="list-style-type: none"> ☐ 208-240 1ph ☐ 208-240 3ph ☐ 380-415 3ph ☐ Smoking Function, optional ☐ CombiHood® VHes-5, (not available on smoker models, left hand door hinging, or stacked combinations) | <ul style="list-style-type: none"> • Door Swing <ul style="list-style-type: none"> ➔Specify choice <ul style="list-style-type: none"> ☐ Right-hand Door Hinging, standard ☐ Left-hand Door, optional increases oven width by 1" (25mm) ☐ Recessed Door, optional increases oven width by 4" (102mm) | <ul style="list-style-type: none"> • Probe <ul style="list-style-type: none"> ➔Specify choice <ul style="list-style-type: none"> ☐ Multi-point, hard-wired temperature probe [5005678] - not available on ovens with S-Control • Single-point, removable temperature probe - included on Touch, Deluxe and Standard controls <ul style="list-style-type: none"> ☐ S-Control oven without smoker [5005679] ☐ S-Control oven with smoker [5011457] | <ul style="list-style-type: none"> • Security Devices for correctional facility use. <ul style="list-style-type: none"> ☐ Base package: excludes temperature probe ➔Specify additional choices <ul style="list-style-type: none"> ☐ Anti Entrapment Device [5011081] ☐ Control Panel Security Cover [5012224] ☐ Hasp Door Lock (padlock not included) [5011680] ☐ Tamper-Proof Screw Package for oven [5013924] ☐ Seismic Feet Package [5011135] |
|---|---|--|--|



6•10esiN SERIES

COMBITHERM[®]

COMBIOVEN



STACKING COMBINATION DIMENSIONS: H x W x D		DIMENSIONS: H x W x D																	
☐ 6.10esiN over 6.10esiN 67" x 35-13/16" x 38-3/16" (1690 x 909 x 970mm) ☐ 6.10esiN over 10.10esiN 73-1/8" x 35-13/16" x 38-3/16" (1856 x 909 x 970mm) ☐ 6.10esiN over 7.14es 67" x 44" x 43" (1701 x 1117 x 1090mm) ☐ 6.10esiN over 10.18es 73-1/8" x 44" x 43" (1856 x 1117 x 1090mm) ☐ Mobile option with 5" (127mm) casters will add 2" (51mm) to the overall height ☐ 6.10esiN over ASC-4E 71" x 35-13/16" x 35-9/16" (1803 x 909 x 903mm) ☐ 6.10esiN over ASC-4G 73-1/4" x 38" x 44-5/8" (1860 x 966 x 1134mm)		EXTERIOR: 35-3/16" x 35-13/16" x 35-9/16" (893mm x 909mm x 903mm) EXTERIOR WITH RECESSED DOOR: 35-3/16" x 39-13/16" x 35-9/16" (893mm x 1011mm x 903mm) INTERIOR: 17-3/4" x 13-1/4" x 26-1/4" (450mm x 387mm x 665mm)																	
WATER REQUIREMENTS		WATER QUALITY MINIMUM STANDARDS																	
TWO (2) COLD WATER INLETS - DRINKING QUALITY ONE (1) TREATED WATER INLET: 3/4" NPT* * Can manifold off of ONE (1) UNTREATED WATER INLET: 3/4" NPT* one 3/4" line. LINE PRESSURE: 30 to 90 psi 2.8 to 6.2 bar WATER DRAIN: 1-1/2" CONNECTION WITH A 2" MINIMUM AIR GAP INSTALLED AS CLOSE TO THE OVEN AS POSSIBLE		USING A WATER SUPPLY NOT MEETING ALTO-SHAAM'S MINIMUM WATER QUALITY STANDARDS WILL VOID THIS WARRANTY. It is the responsibility of the purchaser to ensure that incoming water supply is compliant with the specifications listed through adequate treatment measures. Installation of the CombiGuard™ Water Filtration System is recommended, but this system may not address all water quality issues present.																	
CLEARANCE REQUIREMENTS																			
LEFT 6" (152mm) RECOMMENDED SERVICE ACCESS: 18" (457mm) 20" (508mm) FROM HEAT PRODUCING EQUIPMENT RIGHT 4" (102mm) TOP: 20" (508mm) FOR AIR MOVEMENT BACK 4" (102mm) BOTTOM: 5-1/8" (130mm) FOR LEGS		<table><tr><th>Contaminant</th><th>Inlet Water Requirements (untreated water)</th></tr><tr><td>Free Chlorine</td><td>Less than 0.1 ppm (mg/L)</td></tr><tr><td>Hardness</td><td>Less than 3 gpg (52 ppm)</td></tr><tr><td>Chloride</td><td>Less than 30 ppm (mg/L)</td></tr><tr><td>pH</td><td>7.0 to 8.5</td></tr><tr><td>Alkalinity</td><td>Less than 50 ppm (mg/L)</td></tr><tr><td>Silica</td><td>Less than 12 ppm (mg/L)</td></tr><tr><td>Total Dissolved Solids (tds)</td><td>Less than 60 ppm</td></tr></table>		Contaminant	Inlet Water Requirements (untreated water)	Free Chlorine	Less than 0.1 ppm (mg/L)	Hardness	Less than 3 gpg (52 ppm)	Chloride	Less than 30 ppm (mg/L)	pH	7.0 to 8.5	Alkalinity	Less than 50 ppm (mg/L)	Silica	Less than 12 ppm (mg/L)	Total Dissolved Solids (tds)	Less than 60 ppm
Contaminant	Inlet Water Requirements (untreated water)																		
Free Chlorine	Less than 0.1 ppm (mg/L)																		
Hardness	Less than 3 gpg (52 ppm)																		
Chloride	Less than 30 ppm (mg/L)																		
pH	7.0 to 8.5																		
Alkalinity	Less than 50 ppm (mg/L)																		
Silica	Less than 12 ppm (mg/L)																		
Total Dissolved Solids (tds)	Less than 60 ppm																		

INSTALLATION REQUIREMENTS	
- Oven must be installed level. - Water supply shut-off valve and back-flow preventer when required by local code. - Hood installation is required.	

ELECTRICAL (DEDICATED CIRCUIT REQUIRED)								CombiSmoker®
MODEL	VOLTAGE	PH	HZ	AMPS	kW	AWG	CORD & PLUG	Additional kW
6•10ESiN Touch	208 – 240	1*	60	44.0 - 50.0	9.1 - 12.0	AWG 6	no cord or plug	+ .7 kw
	208 – 240	3	60	25.2 - 27.0/ph	9.1 - 11.3	AWG 8	no cord or plug	+ .7 kw
	380 – 415	3	50	14.0 - 16.3/ph	9.0 - 11.7	AWG 12	no cord or plug	+ .7 kw
6•10ESiN	208 – 240	1*	60	43.4 - 48.7	9.0 - 11.7	AWG 6	no cord or plug	+ .7 kw
	208 – 240	3	60	25.0 - 28.2/ph	9.0 - 11.7	AWG 8	no cord or plug	+ .7 kw
	380 – 415	3	50	14.0 - 16.3/ph	9.0 - 11.7	AWG 12	no cord or plug	+ .7 kw

*ELECTRICAL SERVICE CHARGE APPLIES

WEIGHT			CAPACITY		
NET	285 lb	(129 kg)	FULL-SIZE PANS:	20" x 12" x 2-1/2"	Six (6)
SHIP	415 lb	(188 kg)	GN 1/1:	530 x 325 x 65mm	Six (6)
CRATE DIMENSIONS: (L x W x H)			HALF-SIZE SHEET PANS:*	18" x 13" x 1"	Six (6)
53" x 45" x 49"			ON WIRE SHELVES ONLY		
(1346 x 1143 x 1245mm)			72 lb (33 kg) MAXIMUM		
			VOLUME MAXIMUM: 45 quarts (57 liters)		

*ADDITIONAL WIRE SHELVES REQUIRED FOR MAXIMUM CAPACITY



CombiTouch



Deluxe



Standard



S-Control

6•10ESiN SERIES

COMBITHERM®

COMBIOVEN



Steam Mode

- Automatic steaming at 212°F (100°C).
- Quick steaming.
Touch — 213°F to 250°F (101°C to 121°C).
Deluxe, Standard, S-Control — 213°F to 248°F (101°C to 120°C).
- Low temperature steaming for poaching or proofing.
Touch — 85°F and 211°F (29°C and 99°C).
Deluxe, Standard, S-Control — 86°F and 211°F (30°C and 99°C).



Combination Mode

- Combines steam and convection modes for faster production and better moisture retention.
- Improves yield, quality and shelf life.
- Automatic humidity control.
Touch — 212°F to 485°F (100°C to 252°C).
Deluxe, Standard, S-Control — 212°F to 482°F (100°C to 250°C).



Convection Mode

- Cooking, roasting, baking and finishing applications.
Touch — 85°F to 485°F (29°C to 252°C).
Deluxe, Standard, S-Control — 86°F to 482°F (30°C to 250°C).



Retherm Mode

- Bulk food or plated meal reheating with automatic steam injection.
Touch — 245°F to 320°F (118°C to 160°C).
Deluxe, Standard, S-Control — 248°F to 320°F (120°C to 160°C).
- Automatic humidity control.



Gold-n-Brown™

- Gold-n-Brown vents just the right amount of humidity in the oven cavity for perfect browning.
Touch — Six levels of Gold-n-Brown are featured.



Moisture Injection

- A quick burst of moisture can be added with a touch of a button at any time when cooking in the convection mode.




HACCP Data Access (CombiTouch only)

- Records cooking mode, time and temperature completed within a two week time period. The information is captured in a text format and can be downloaded to a USB device.



CombiSmoker® (option)

- Smoke any product, hot or cold, utilizing real wood chips.
- Functions in both combination and convection mode.
- Function can be programmed into operating procedure.
- Sample bag of wood chips included.



6•10esiN SERIES

COMBITHERM[®]

COMBIoven



OPTIONS & ACCESSORIES		
☐	CHICKEN GREASE TRAY WITH DRAIN: 1-1/2" (38mm) DEEP	5003463
CHICKEN ROASTING RACKS:		
☐	6 CHICKEN CAPACITY — FITS FULL-SIZE PAN: 2 RACKS PER OVEN	SH-23000
☐	8 CHICKEN CAPACITY — FITS FULL-SIZE PAN: 2 RACKS PER OVEN	SH-23619
☐	COMBIGUARD™ BWS BLENDED WATER SYSTEM (INCLUDES 50 GALLON TANK, 1 MEMBRANE & 3 FILTERS)	FI-28727
☐	COMBIGUARD™ BWS REPLACEMENT FILTER CARTRIDGE AMS-QT	FI-29316
☐	COMBIGUARD™ BWS REPLACEMENT FILTER CARTRIDGE SCLX2-Q	FI-29317
☐	COMBIGUARD™ BWS REPLACEMENT PREFILTER FILTER CARTRIDGE CTO-Q	FI-29318
☐	COMBIGUARD™ 10 TRIPLE-GUARD WATER FILTRATION SYSTEM (INCLUDES 1 CARTRIDGE)	FI-23014
☐	COMBIGUARD™ 10 TRIPLE-GUARD REPLACEMENT FILTER	FI-26356
☐	COMBIGUARD™ 20 TRIPLE-GUARD WATER FILTRATION SYSTEM (FOR STACKED UNITS, INCLUDES 1 CARTRIDGE)	FI-28728
☐	COMBIGUARD™ 20 TRIPLE-GUARD REPLACEMENT FILTER (FOR STACKED UNITS)	FI-28744
☐	COMBITHERM CLEANING LIQUID — SPECIALLY FORMULATED FOR COMBITHERM OVENS	
	➔ TWELVE (12) CONTAINERS/CASE, 1 QUART (C. 1 LITER) EACH [SPECIAL HANDLING REQUIRED]	CE-24750
☐	COMBICLEAN® TABLETS — SPECIALLY FORMULATED FOR COMBITHERM OVENS	
	➔ 90 PACKETS EACH CONTAINER	CE-28892
☐	EXTENDED ONE-YEAR WARRANTY	CONTACT FACTORY
☐	FRY BASKET, 12" x 20" (325mm x 530mm)	BS-26730
☐	GRILLING GRATE, 12" x 20" (325mm x 530mm)	SH-26731
☐	PROBE, SOUS VIDE	PR-34747
☐	SCALE FREE™ (CITRUS BASED, NON-CORROSIVE DELIMING PRODUCT)	CE-27889
☐	SERVICE START-UP CHECK AVAILABLE THROUGH AN ALTO-SHAAM FASTEAM CENTER	SPECIFY AS REQUIRED
☐	SHELF, STAINLESS STEEL WIRE	SH-2903
STAND, STAINLESS STEEL (H x W x D):		
☐	➔ STATIONARY WITH SHELF 29-1/2" x 27-3/8" x 24" (749mm x 695mm x 610mm)	5005713
☐	➔ STATIONARY WITH PAN SLIDES & SHELF 29-1/2" x 27-3/8" x 24" (749mm x 695mm x 610mm)	5005714
☐	➔ MOBILE WITH SHELF 32-1/8" x 27-15/16" x 24-9/16" (815mm x 709mm x 624mm)	5005717
☐	➔ MOBILE WITH PAN SLIDES & SHELF 32-1/8" x 27-15/16" x 24-9/16" (815mm x 709mm x 624mm)	5005718
☐	➔ STATIONARY 38-13/16" x 33-15/16" x 37-1/2" (986mm x 861mm x 952mm)	5007698
☐	➔ STATIONARY (FOR STACKING OVER ASC-2E) 36-13/16" x 35" x 36" (935mm x 889mm x 914mm)	5009045
WOOD CHIPS — BULK PACK 20 lb (9 kg)		
☐	➔ Apple..... WC-22543	
☐	➔ Cherry..... WC-22541	
☐	➔ Hickory.....WC-2829	
☐	➔ Maple..... WC-22545	