



Features

- 304 series stainless steel interior
- 430 series stainless steel exterior
- Recessed handles
- 2 plastic coated steel shelves included
- Foamed in place polyurethane insulation
- Removable door gasket for easy cleaning
- Self closing doors
- Automatic defrosting
- 4 casters (two locking)
- ETL Sanitation Listed

With its compact size and all stainless steel interior and exterior, this double door undercounter freezer is a perfect addition to snack bars, concession stands, pizzerias, sandwich shops, and restaurant kitchens with limited space. Built in casters, two of which are locking, allow you to pull the freezer out from under your counter-tops, for easy cleaning and service.

Two plastic coated steel shelves are included. Adjustable mounting brackets give you complete control over the freezer's shelving configuration, to accommodate a variety of toppings, garnishes, or condiments.

The 48" undercounter freezer's 1/2 hp compressor uses R404a refrigerant. Foamed in place polyurethane cell insulation helps maintain interior temperatures between -7° and 0° Fahrenheit. A top mounted cooling fan circulates air quickly throughout the freezer, regulating the internal temperature even when the freezer's self-closing doors are opened.

With its durable, 430 series stainless steel exterior and 304 series stainless steel interior, the double door undercounter freezer is strong enough to stand up to the daily demands of your busy restaurant kitchen. The double door undercounter freezer has a 120V, 6.2 amp, 60 Hz. electrical rating, and is ETL Sanitation Listed and NSF Compliant.

Technical Data

Dimensions

Exterior Dimensions (W x D x H)	47" x 29.5" x 35"
Interior Dimensions (W x D x H)	42.5" x 22.75" x 23.5"
Net Volume (cu. ft.)	6.25 cu. ft.
Net Weight	158.5 lbs
Packaging Dimensions (W x D x H)	49.5" x 31.75" x 36.25"

Cooling

Temperature Range	-7° - 0° F
Refrigerant	R404a
Maximum Ambient Temperature Rating	100.4° F
Defrosting	Automatic
Temperature Display	No
Temperature Controller	Mechanical
H/P	1/2

Construction

Exterior Material	430 series stainless steel
Interior Material	304 series stainless steel
Insulation Material	Foamed in place polyurethane
Shelf Material	Plastic coated steel
Shelf Load Capacity	132.25 lbs

Electrical

Voltage	120
Amps	6.2
Hz	60
Phase	1

Plan View

