

SINGLE BUILT-IN HEATED WELLS

Models HWBL-FUL, -FULD HWB-FUL, -FULD HWBH-FUL, -FULD HWBL-43, -43D HWB-43, -43D HWBH-43, -43D, -43DA HWB-4QT, -4QTD HWB-7QT, -7QTD HWBH-7QT, -7QTD HWB-11QT, -11QTD HWBH-11QT, -11QTD

Hatco Built-In Heated Wells provide flexibility and quality, with many options to choose from. These units hold steam table food hot and fresh with self-adjusting thermostats that read the actual temperatures and add heat only when needed.

FLEXIBILITY

UL approved Built-In Heated Wells are available in five sizes: rectangular full size, rectangular 4/3 size, round 4-Quart (4 l) round 7-Quart (7 l), and round 11-Quart (10 l). Choose from a model with or without a drain, in low, standard, or high watt. The standard compact controls, or optional recessed controls can be conveniently placed where needed.

QUALITY

The following features assure the finest performance for years to come:

- Superior thermostat controls that read the actual temperature of the well and add heat only if needed.
- Controls feature a separate lighted on/off rocker switch and temperature dial, allowing preset temperatures to be maintained.
- 50% larger drain with flat screen simplifies cleaning and holds pans level.
- Easy service access to heating elements and thermostats.
- Mounting kits for combustible countertops available.
- EZ locking hardware for quick installation.
- Thicker stainless steel construction and solid braised joints for durability.



Model HWB-43D with accessory food pans

Model HWB-FULD with accessory food pan

Model HWB-7QT with accessory food pan (notched lid not shown)

Model

HWB-11QT

Model HWB-4QT with accessory food pan (notched lid not shown)

Ordering Instructions

(single unit holding

4 third-size pans)

Please specify the following with each order:

1. Desired Voltage: 120, 208, or 240V (export voltage available)

2. Base Size of Heated Well:

A. Rectangular: Full (12" x 20" (305 x 508 mm) or 4/3 (12" x 27" (305 x 686 mm)

B. Round: 4-Quart (4-Liter), 7-Quart (7-Liter) or 11-Quart (10-Liter)

3. Choose With or Without Drain

4. Mounting Style:

A. Top Mounted

B. Bottom Mounted (rectangular full size units only)

5. Wattage:

A. High Watt

B. Standard Watt

C. Low Watt (120V only)

NOTE: Round Heated Wells are only available in standard and high watt configurations

(4-Quart (4-Liter) available in standard watt only)

6. Agency:

A. UL and CUL

B. UL-EPH (sanitary listing)

C. CE Mark available on standard and high watt units



with accessory food pan

(notched lid not shown)



Quick access heating element and thermostat, for easy service

Built-in Heated Wells Countertop Cutout Dimensions

Model	Minimum Width	Maximum Width	Minimum Depth	Maximum Depth	Below Counter
HWB-FUL	12.63" (321 mm)	12.94" (329 mm)	20.63" (524 mm)	20.94" (532 mm)	8.57" (218 mm)
HWB-FUL®	14" (356 mm)	14.25" (362 mm)	22" (559 mm)	22.25" (565 mm)	8.57" (218 mm)
HWB-43	12.69" (322 mm)	12.94" (329 mm)	27.69" (703 mm)	28" (711 mm)	8.56" (217 mm)
HWB-43°	14" (356 mm)	14.25" (362 mm)	29" (737 mm)	29.25" (743 mm)	8.56" (217 mm)
HWB-4QT	Ø 7.125" (181 mm)	Ø 7.56" (192 mm)	_	_	9.52" (242 mm)
HWB-4QT•	9" (229 mm)	9.25" (286 mm)	9" (229 mm)	9.25" (286 mm)	9.52" (242 mm)
HWB-7QT	Ø 9.125" (232 mm)	Ø 9.56" (243 mm)		_	8.7" (221 mm)
HWB-7QT°	11" (279 mm)	11.25" (286 mm)	11" (279 mm)	11.25" (286 mm)	8.7" (221 mm)
HWB-11QT	Ø 11" (279 mm)	Ø 11.375" (289 mm)			8.7" (221 mm)
HWB-11QT•	13" (330 mm)	13.25" (337 mm)	13" (330 mm)	13.25" (337 mm)	8.7" (221 mm)

[•] Indicates cutout dimensions for a combustible countertop surface.

Control Cutout Dimensions

A. Standard Compact Control Panel Cutout: 3.25"W (83 mm) x 3.75"H (95mm) B. Optional Recessed Control Panel Cutout: 5.88"W (149 mm) x 6.38"H (162mm)




HATCO CORPORATION P.O. Box 340500 Milwaukee, WI 53234-0500 U.S.A. (800) 558-0607 • (414) 671-6350 • Fax (800) 543-7521 • Int'l. Fax (414) 671-3976 www.hatcocorp.com • E-mail: equipsales@hatcocorp.com



SINGLE BUILT-IN HEATED WELLS

Models HWBL-FUL, -FULD HWB-FUL, -FULD HWBH-FUL, -FULD HWBL-43, -43D HWB-43, -43D HWBH-43, -43D, -43DA HWB-4QT, -4QTD HWB-7QT, -7QTD HWBH-7QT, -7QTD HWB-11QT, -11QTD HWBH-11QT, -11QTD



SPECIFICATIONS

3.55" (90 mm)

FRONT VIEW

Full Size Rectangular Models – Low Watt

Model*	Volts	Watts	Amps	Shipping Weight
HWBL-FUL HWBL-FULD	120	750	6.3	21 lbs. (10 kg) 24 lbs. (11 kg)

FLEXIBLE CONDUIT SIDE VIEW

Model HWB-43 Series

Full Size Rectangular Models – Standard Watt

Model*	Volts	Watts	Amps	Shipping Weight
HWB-FUL HWB-FULD	120 208 240	1200	10.0 5.8 5.0	21 lbs. (10 kg) 24 lbs. (11 kg)

Full Size Rectangular Models - High Watt

Model*	Volts	Watts	Amps	Shipping Weight
HWBH-FUL HWBH-FULD	120 208 240	1650	13.8 7.9 6.9	21 lbs. (10 kg) 24 lbs. (11 kg)

4/3 Size Rectangular Models - Low Watt

Model*	Volts	Watts	Amps	Shipping Weight
HWBL-43 HWBL-43D HWBL-43DA	120	750	6.3	30 lbs. (14 kg) 33 lbs. (15 kg) 36 lbs. (16 kg)

4/3 Size Rectangular Models – Standard Watt

Model*	Volts	Watts	Amps	Shipping Weight
HWB-43	120	1200	10.0	30 lbs. (14 kg)
HWB-43D	208		5.8	33 lbs. (15 kg)
HWB-43DA	240		5.0	36 lbs. (16 kg)

4/3 Size Rectangular Models - High Watt

Model*	Volts	Watts	Amps	Shipping Weight
HWBH-43	120	1650	13.8	30 lbs. (14 kg)
HWBH-43D	208		7.9	33 lbs. (15 kg)
HWBH-43DA	240		6.9	36 lbs. (16 kg)

^{* &}quot;D" added to model number indicates unit with drain.

Model*	Volts	Watts	Amps	Shipping Weight
HWB-4QT HWB-4QTD	120 208 240	500 536 600	4.2 2.6 2.5	9 lbs. (4 kg) 12 lbs. (5 kg)

7 Quart (7 Liter) Round Models - Standard Watt

Model*	Volts	Watts	Amps	Shipping Weight
HWB-7QT HWB-7QTD	120 208 240	500 536 600	4.2 2.6 2.5	10 lbs. (5 kg) 13 lbs. (6 kg)

7 Quart (7 Liter) Round Models - High Watt

Model*	Volts	Watts	Amps	Shipping Weight
HWBH-7QT HWBH-7QTD	120 208 240	800 715 800	6.7 3.4 3.3	10 lbs. (5 kg) 13 lbs. (6 kg)

11 Quart (10 Liter) Round Models - Standard Watt

Model*	Volts	Watts	Amps	Shipping Weight
HWB-11QT HWB-11QTD	120 208 240	500 536 600	4.2 2.6 2.5	11 lbs. (5 kg) 14 lbs. (6 kg)

11 Quart (10 Liter) Round Models - High Watt

I	Model*	Volts	Watts	Amps	Shipping Weight
	BH-11QT BH-11QTD	120 208 240	800 715 800	6.7 3.4 3.3	11 lbs. (5 kg) 14 lbs. (6 kg)

[&]quot;D" added to model number indicates unit with drain.

DIMENSIONS

HWB-FUL Series: 13.7"W x 21.77"D x 8.57"H (348 x 553 x 218 mm). HWB-43 Series: 13.58"W x 28.58"D x 8.56"H (345 x 726 x 217 mm). HWB-4QT Series: 8.25" Diameter x 9.51"H (209 x 241 mm). HWB-7QT Series: 10.31" Diameter x 8.71"H (262 x 221 mm). HWB-11QT Series: 12.25" Diameter x 8.37"H (311 x 213 mm).

Standard Compact Control Panel: 3.55"W x 2.11"D x 4.77"H (90 x 54 x 121 mm)

Optional Recessed Control Panel: 6.33"W x 3.63"D x 7.73" (161 x 92 x 196 mm).

VOLTAGE

120, 208, and 240 volts, single phase. Export voltages available.

OPTIONS (NOT FOR RETROFIT)

- ☐ Flush Mount Control Box Bezel in Designer Colors: Warm Red, Black, Gray Granite, White Granite, Navy Blue, Hunter Green.
- Additional Lead Wire Links available in one foot increments (Lead wire only – conduit not included) (Models are shipped with 1' (305 mm) of lead wire - no conduit)
- Thermostat with 6' (1829 mm) Capillary
- Larger Recessed Thermostat Control

ACCESSORIES

Mounting Kit for Combustible Countertops (All Models)

☐ 12" (305 mm) and 20" (508 mm) Pan Support Bars

- ☐ Adapter to Convert Warmer to Hold Two 7 Quart (7 Liter) Inserts (Model HWB-FUL Series only)
- Adapter to Convert Warmer to Hold Three 4 Quart (4 Liter) Inserts (Model HWB-FUL Series only)
- ☐ Adapter to Convert Warmer to Hold Two 11 Quart (10 Liter) Inserts (Model HWB-43 Series only)
- Stainless Steel Food Pans
- Round Pans with Notched Lids
- 3/4" NPT Ball Valve for Unit with Drains.

PRODUCT SPECS **Built-in Heated Well**

The Built-in Heated Well shall be a Modelas manufactured by the Hatco Corporation, Milwaukee, WI 53234 U.S.A. With 24/7 parts and service assistance (U.S. and Canada only),

the Built-in Heated Well shall be rated atwatts,volts, and

beinches (millimeters) in overall width and beinches (millimeters) in overall depth. It shall consist of stainless and aluminized steel housing with a metal sheathed heating element, EZ locking hardware for installation, and a remote thermostat with lighted power switch.

Accessories may include stainless steel mounting kit, adapter bars, and adapter top.

HATCO CORPORATION P.O. Box 340500 Milwaukee, WI 53234-0500 U.S.A. • (800) 558-0607 • (414) 671-6350 Fax (800) 543-7521 • Int'l. Fax (414) 671-3976 • www.hatcocorp.com • E-mail: equipsales@hatcocorp.com

[&]quot;A" added to model number indicates autofill.

[&]quot;A" added to model number indicates autofill.