F-1501M H MODULAR FLAKER ICE MACHINE


Item#_ Project:


Qty: _ *AutoCad available on KCL

> F-1501M H 12/14 Item #13339

FLAKER DIMENSIONS

F-1501M H $30 \times 27^{1/2} \times 34^{7/16}$





F-1501MWH Water-Cooled

F-1501MAH Air-Cooled Shown on an optional B-900

F-1501MRH

Remote Air-Cooled



Also available on Large Bins: B-1150SS B-1500SS

- Up to 1590 lbs. of ice production per 24 hours
- Durable stainless steel exterior
- Advanced CleanCycle24[™] Design



- Removes sediment
- Cleaner ice
- Longer life and easy maintenance
- R-404A Refrigerant
- * The F-1501MAH and F-1501MRH are ENERGY STAR qualified.

*FLAKED ICE DIMENSIONS

*approximate size, image not to scale






Warranty

Valid in United States, Canada, Puerto Rico, & U.S. Territories. Contact factory for warranty in

Three Year - Parts & Labor on entire machine. (Serial numbers Vxxxxx) and after.)





DIMENSIONS WxDxH F-1501M_H 30 x 27^{1/2} x 34^{7/16}

F-1501M H FLAKER ICE MACHINE **MODULAR SERIES**

- Air-cooled
- Water-cooled
- Remote Air-cooled

AIR-COOLED

Water Temp' F.		50°	70°	90°
o° F.	70°	1590	1514	1447
Temp	80°	1382	1321	1262
Air	90°	1206	1110	1100

WATER-COOLED

Water Temp° F.		50°	70°	90°
۰° F.	70°	1460	1446	1409
Temp°	80°	1374	1340	1306
Αï	90°	1273	1265	1210

REMOTE AIR-COOLED

Water Temp° F.		50°	70°	90°
П.	70°	1585	1532	1484
Temp° F.	80°	1439	1394	1351
Ą	90°	1309	1237	1230

UTILITY CONSUMPTION

Model Number	KWH per 100 LBS. 90/70	Potable Water Gal. per 100 lbs.
F-1501MAH	4.03	12.0
F-1501MWH	3.40	12.0
F-1501MRH	3.85	12.0

SPECIFICATIONS

Model Number	Condenser	Amperage	Min. Circuit Ampacity	Shipping Weight
F-1501MAH	Air-Cooled	15.93	20	325 lbs.
F-1501MWH	Water-Cooled	15.44	20	325 lbs.
F-1501MRH	Remote Air-Cooled	18.44	20	315 lbs.

STORAGE BINS

Model Number	Application Capacity	ARI-Rated Capacity	
B-500	500 lbs.	360 lbs.	
B-700	700 lbs.	550 lbs.	
B-800	800 lbs.	600 lbs.	
B-900	900 lbs.	660 lbs.	
B-1150	1150 lbs.	N/A	
B-1300	1275 lbs.	N/A	
B-1500	1490 lbs.	N/A	
B-1650	1605 lbs.	N/A	

ELECTRICAL & PLUMBING/F-1501M_H


- 208-230V/60/I (3 wire with dedicated neutral for II5V)
- Icemaker Water Supply Line: Minimum 1/4" Nominal ID Copper Water Tubing or Equivalent
- Icemaker Drain Line: Minimum 3/4" Nominal ID Hard Pipe or Equivalent









© HOSHIZAKI AMERICA, INC.









FRONT VIEW

SIDE VIEW

ICE DROP ZONE






AIR-COOLED UNIT

WATER-COOLED UNIT

ser (Sold Separately) For Use with F-1501MRH-C



REMOTE AIR-COOLED UNIT

2 3/4 3 URC-14F Electrical Conduit Discharge Line 37 13/16 -Charged Tubing Kits (Sold Separately) 20' R404-2068-2 35' R404-3568-2 55' R404-5568-2

Voltage supply for the URC Remote Condenser is supplied from the Ice Maker. No additional circuit is required.

OPERATING LIMITS

- Ambient Temp Range
- Water Temp Range 45 - 90°F
- Water Pressure
- 10 113psig 104 - 127V • Voltage Range

SERVICE

- · Panels easily removed and all components accessible for service.
- · Removable/cleanable air filter. (Air-Cooled models only)



45 - 100°F