

Wet/Dry Vacuums

For quick pick-up, Pacific's wet/dry vacuums deliver plenty of power for the job.



Gulper 12P
(shown w/ tool kit as standard)



Gulper 18P
(w/ tool kit as standard
or optional squeegee)



Gulper 16SV



Gulper 615 SS



Gulper 600 SS



Whether you're cleaning up light construction, pooled water or a combination of wet and dry debris, Pacific has a wet/dry vac for your application. Available with either a stainless steel or molded polyethylene tank, our wet/dry vacs come with various motor sizes and capacities ranging from six to 20 gallons.

Our polyethylene wet/dry vacs feature easy-rolling front casters and large stair-climbing wheels, an inte-

grated push handle, a dual or triple-stage bypass motor, drop down drain hose with tethered cap and quiet 68 dBA operation. A front squeegee comes standard with the 16SV and 18PS models.

The stainless models are both durable and easy to sanitize, making them ideal for health care use. The 615 model includes a cart with a convenient "tip and pour" emptying feature.

Gulper 18PS shown above



PACIFIC

The Next Wave of Clean™

2259 South Sheridan, Muskegon, MI 49442
1.800.968.1332
Ph: 231.773.1330 • Fax: 231.773.1642
www.pacificfloorcare.com
www.nextwaveofclean.com

Wet/Dry Vac Specifications



	Gulper 600SS	Gulper 615SS
Motor	1.2 hp	(2) 1.2 hp
Water Lift	82"	80"
CFM	96	175
Tank Capacity	7 gal.	20 gal.
Front Casters	(4) 2"	(2) 3"
Rear Wheels	—	8"
Filter Area	385 sq. in.	677 sq. in.
dB	68 dB @ 10 ft.	68 dB @ 10 ft.
Cord	35', 16-3SJT	35', 16-3SJT
Tool Kit	standard metal	standard metal
Diameter	11-1/8"	16-3/8"
Height	26"/31"	37"
Weight	22 lbs.	50 lbs.
Shipping Weight	34 lbs.	70 lbs.
Squeegee	—	30" optional

	Gulper 12P	Gulper 16SV	Gulper 18PS	Gulper 18P
Motor	2-stage bypass / 1.2 hp	2-stage bypass / 1.3 hp	3-stage bypass / 1.75 hp	2-stage bypass / 1.2 hp
Water Lift	80"	84"	117"	80"
CFM	96	120	99	96
Tank Capacity	12 gal.	16 gal.	18 gal.	18 gal.
Filter Area	677 sq. in.	677 sq. in.	677 sq. in.	677 sq. in.
dB	68 dB @ 10 ft.	68 dB @ 10 ft.	68 dB @ 10 ft.	68 dB @ 10 ft.
Cord	35', 16-3SJT	38', 16-3SJT	50', 16-3SJT	35', 16-3SJT
Tool Kit	standard metal	optional	optional	standard metal
Dump Valve	30" dump hose w/tethered cap	30" dump hose w/tethered cap	30" dump hose w/tethered cap	30" dump hose w/tethered cap
Handle	integral push	integral push	integral push	integral push
Front Casters	3"	3"	3"	3"
Rear Wheels	8"	8"	8"	8"
Squeegee Length	optional	25"	28"	optional
Length	25"	25"	25"	25"
Height	36"	36"	36"	36"
Width	18"	18"	18"	18"
Shipping Weight	66 lbs.	60 lbs.	86 lbs.	80 lbs.