

SUBMITTAL DATA: DUCTLESS MINI SPLIT A/C



JOB NAME:	LOCATION:			
PURCHASER:				
ENGINEER:				
SUBMITTED TO:	FOR:	REFERENCE	APPROVAL	CONSTRUCTION

SPECIFICATIONS	TAS-09EH
SEER	19
EER	13.5
HSPF	9
Voltage	115V/60HZ/1PHASE
Breaker Size (A)	20
RLA Cool/Heat (A)	5.5/9.3
Operating Ambient Temperature Range for Cooling	5°F - 125°F
Operating Ambient Temperature Range for Heating	5°F - 125°F
Indoor Unit	
Airlow Hi/Medium/Low Speed (CFM)	315/270/212
Noise Level Hi Speed (Db)	42
Width (Inches)	31.5
Depth (Inches)	7.5
Height (Inches)	11
Unit Weight (lbs)	22
Outdoor Unit	
Noise Level (dB)	55
Width (Inches)	31.3
Depth (Inches)	10
Height (Inches)	21.3
Unit Weight (lbs)	66

Line Sets	
Refrigerant	R410A
Pipe Size	1/4" 3/8"
Maximum Length	82
Maximum Vertical	33
Factory Charge for (Ft)	25
Additional Charge (Oz/Ft)	0.2

Controls	
Control Method	Wired & wireless remote control with temp sensor in indoor unit
Communication Control Voltage	208-230V

Certification	
Safety	ETL
Performance	ARI 3081763

*All specification subject to change without notice.