



Star Manufacturing
International Inc.

10 Sunnen Drive
P.O. Box 430129
St. Louis, MO 63143

Phone: (800) 264-7827
(314) 781-5353 (Int'l)
FAX: (800) 264-6666
(314) 781-4344 (Int'l)
www.star-mfg.com

Star-Max™ Gas Griddles with Manual Controls

Model 615MB
Model 624MB
Model 636MB
Model 648MB

Manual Control Gas Griddles from Star... Value and Performance

Features/Benefits:

- ★ Highly polished 3/4" thick hot rolled steel griddle plate with a 3" high wrap-around stainless steel splash guard
- ★ Adjustable manual valve for every 12" of griddle width.
- ★ Aluminized steel 20,000 BTU burner every 12" provides superior cooking performance.
- ★ Standing pilot
- ★ Spatula wide 3-1/4" front grease trough
- ★ 4-1/2 quart stainless steel grease drawer

Applications:

For breakfast, lunch or dinner, Star's Star-Max™ manual control griddles out-perform the competition. These versatile griddles, available in 4 widths can handle all your grilling requirements with ease.

Construction:

Star-Max™ manual control griddles are constructed to provide years of heavy duty performance. The body of the griddle is constructed of double wall aluminized steel side panels and a stainless steel front panel with black polycarbonate trim. The stainless steel bull nose protects the control knobs.

Warranty:

Star-Max™ gas griddles are covered by Star's one year parts and labor warranty.

Model 636MB





Star Manufacturing
International Inc.

10 Sunnen Drive
P.O. Box 430129
St. Louis, MO 63143

Phone: (800) 264-7827
(314) 781-5353 (Int'l)
FAX: (800) 264-6666
(314) 781-4344 (Int'l)
www.star-mfg.com

Star-Max™
Gas Griddles with
Manual Controls

Model 615MB
Model 624MB
Model 636MB
Model 648MB

Manual Control Gas Griddles from Star... Value and Performance

Specifications

Model No.	Dimensions			No. Controls	BTU	Grid Area	Plate Thickness	Approximate Weight	
	Width(A)	Depth	Height					Installed	Shipping
615MB	15" (38.1 cm)	27-3/4" (70.5 cm)	13-1/2" (34.3 cm)	1	20,000	304 sq. in. (1961.4 sq cm)	3/4" (1.9 cm)	83 lbs. (37.6 kg)	90 lbs. (40.8 kg)
624MB	24" (61 cm)	27-3/4" (70.5 cm)	13-1/2" (34.3 cm)	2	40,000	498 sq. in. (3213.4 sq cm)	3/4" (1.9 cm)	165 lbs. (74.8 kg)	175 lbs. (79.4 kg)
636MB	36" (91.4 cm)	27-3/4" (70.5 cm)	13-1/2" (34.3 cm)	3	60,000	747 sq. in. (4819.6 sq cm)	3/4" (1.9 cm)	247 lbs. (112 kg)	262 lbs. (118.8 kg)
648MB	48" (121.9 cm)	27-3/4" (70.5 cm)	13-1/2" (34.3 cm)	4	80,000	996 sq. in. (6426.2 sq cm)	3/4" (1.9 cm)	330 lbs. (144.7 kg)	350 lbs. (158.8 kg)

Units operate on Natural or Propane Gas.

Typical Specifications

Gas griddle are constructed with a stainless steel front panel with black polycarbonate trim and double wall aluminized steel side panels. Griddle plate is 3/4" (1.9 cm) thick highly polished steel plate with 3" (7.6 cm) high wrap-around stainless steel splash guard. Unit has 3-1/4" (8.3 cm) wide front grease trough with grease chute and a 4-1/2 qt. (4.257 L) stainless steel grease drawer. Unit is equipped with a 20,000 BTU aluminized steel burner for every 12" (30.5 cm) of width and is controlled by a manual control valve. Valve knobs are protected by a stainless steel bull nose front. A standing pilot is provided. Griddles are supplied with 4" (10.2 cm) high die cast nickel plated legs that shall have a 1-3/4" (4.5 cm) adjustment. Gas connection shall be 1/2" (1.3 cm) N.P.T. male and a convertible pressure regulator is provided. Units are for installation within 6" (15.2 cm) of combustible surfaces and are AGA Certified NSF and CGA listed. Printed in the U.S.A.