



Star Manufacturing
International Inc.

10 Sunnen Drive
P.O. Box 430129
St. Louis, MO 63143

Phone: (800) 264-7827
(314) 781-5353 (Int'l)
FAX: (800) 264-6666
(314) 781-4344 (Int'l)

Star-Max™ Gas Griddles with Thermostat Controls

Model 615TB
Model 624TB
Model 636TB
Model 648TB

Thermostatically Controlled Gas Griddles from Star... Heavy Duty Performers

Features/Benefits:

- ★ A highly polished 3/4" hot rolled steel griddle plate with stainless steel 3" high wrap-around splash guard
- ★ 20,000 BTU aluminized steel burners and throttling type thermostats every 12" for precision temperature control
- ★ Spatula wide 3-1/4" grease trough
- ★ 4-1/2 quart stainless steel grease drawer
- ★ Double wall construction allows for installation within 6" of combustible surfaces.

Applications:

When your grilling requirements call for heavy duty performance, Star's Star-Max™ thermostatically controlled griddles will do the job. Breakfast, lunch or dinner, Star has a griddle to fit your menu and production needs.

Heavy Duty

Star-Max™ griddles are constructed to provide years of heavy duty performance. The double wall aluminized steel side panels, nickel plated die cast 4" high legs, stainless steel front control panel with black poly carbonate trim, and stainless bull nose front for control knob protection offer years of easy maintenance. Models are available in 15" (38.1 cm), 24" (61 cm), 36" (91.4 cm), and 48" (121.9 cm) widths.

Warranty:

Star-Max gas griddles are covered by Star's one year parts and labor warranty.

Model 636TB





Star Manufacturing
International Inc.

10 Sunnen Drive
P.O. Box 430129
St. Louis, MO 63143

Phone: (800) 264-7827
(314) 781-5353 (Int'l)
FAX: (800) 264-6666
(314) 781-4344 (Int'l)

Star-Max™
Gas Griddles with
Thermostat Controls

Model 615TB
Model 624TB
Model 636TB
Model 648TB

Thermostatically Controlled Gas Griddles from Star... Heavy Duty Performers

Specifications

Model No.	Dimensions			No. Thermostats	BTU	Grid Area	Plate Thickness	Weight	
	Width(A)	Depth	Height					Installed	Shipping
615TB	15"	27-3/4"	13-1/2"	1	20,000	304 sq. in. 1961.4 sq cm	3/4" 1.9 cm	83 lbs.	90 lbs.
	38.1 cm	70.5 cm	34.3 cm					37.7 kg	40.8 kg
624TB	24"	27-3/4"	13-1/2"	2	40,000	498 sq. in. 3213.1 sq cm	3/4" 1.9 cm	165 lbs.	175 lbs.
	61 cm	70.5 cm	34.3 cm					74.8 kg	79.4 kg
636TB	36"	27-3/4"	13-1/2"	3	60,000	747 sq. in. 4819.6 sq cm	3/4" 1.9 cm	247 lbs.	262 lbs.
	91.4 cm	70.5 cm	34.3 cm					112 kg	118.8 kg
648TB	48"	27-3/4"	13-1/2"	4	80,000	996 sq. in. 6426.2 sq cm	3/4" 1.9 cm	330 lbs.	350 lbs.
	121.9 cm	70.5 cm	34.3 cm					149.7 kg	159 kg

Units operate on Natural or Popane Gas.

Typical Specifications

Gas griddles are constructed with stainless steel front panel with black poly carbonate trim and double wall aluminized steel side panels. Griddle plate is 3/4" (1.9 cm) thick highly polished steel plate with 3" (7.6 cm) high wrap-around stainless steel splash guard. Unit has a 3-1/4" (8.3 cm) wide front grease trough with grease chute and a 4-1/2 qt. (4.26 L) stainless steel grease drawer. Unit has a 20,000 BTU aluminized steel burner for every 12" (30.5 cm) of width and shall be controlled by a throttling type thermostat. Thermostat knobs are protected by stainless steel bull nose front. A standing pilot is provided. Griddles are supplied with 4" (10.2 cm) high die cast nickel plated legs that have a 1-3/4" (4.5 cm) adjustment. Gas connection is 1/2" (1.3 cm) N.P.T. male and a convertible pressure regulator is provided. Units are approved for installation within 6" (15.2 cm) of combustible surfaces and are AGA Certified and NSF Listed. Printed in the U.S.A.