



Conveyers

The entire unit boasts stainless steel construction for extended durability. Adjustable bullet feet and legs keep the unit directly off the ground, and an exhaust vent fan control keeps external temperatures at an appropriate level.



495NO44HLRC

- Proudly made in America for quality and durability
- High temperature sanitizing and low temperature chemical sanitizing options; exclusive EnergyGuard electromechanical controls
- Can clean up to 225 racks per hour; 25" standard clearance
- Adjust-A-Peak adjustable conveyor can be used to extend wash time
- Built-in splash shields and front dress panel; stainless steel exterior with legs

Base Item	Racks Per Hour	Water Gal. Per Rack	Energy Star	Interior Clearance	Delimiting Function	Conveyor Speed	Configurations	Additional Features
44" Conveyor High Temperature Dishwasher	225	0.68	No	25"	Yes	6.2' per minute	Left or Right and Right to Left	
44" Conveyor Low Temperature Dishwasher	225	0.68	No	25"	Yes	6.2' per minute	Left or Right and Right to Left	
66" Conveyor High Temperature Dishwasher	225	0.68	No	25"	Yes	6.2' per minute	Left or Right and Right to Left	22" Prewash Section
66" Conveyor Low Temperature Dishwasher	225	0.68	No	25"	Yes	6.2' per minute	Left or Right and Right to Left	22" Prewash Section

