



**IDEAL WAREHOUSE**  
INNOVATIONS INC®

Protecting Your People

## OVERHEAD DOOR TRACK PROTECTION



Protect Door Tracks  
Reduce Maintenance Costs

The loading dock door is literally the gateway to the supply chain, and protecting its operation is key to keeping goods coming and going. Overhead doors, installed on most docks, run along a thin metal track that can be easily dinged, or buckled, often by the pallet on a forklift in a hurry to load/offload.

Protect overhead door tracks from damage by forklifts and other motorized warehouse equipment with Ideal Warehouse Innovations' line-up of Track Protectors.

### CONSIDER THE RISKS OF HAVING EXPOSED DOOR TRACKS:

- Costly maintenance requirements
- Security, climate and contamination control risks if the door can't be closed properly while awaiting repair
- Lowered productivity
- Difficulty getting replacement parts in a timely manner

Avoid these costly and time consuming problems with Track Protectors.

### TRACK PROTECTORS

Ideal Warehouse Innovations' line-up of Overhead Door Track Protectors feature:

- Formed steel construction with a 45° angle leading flange to offer strong impact resistance (tougher than composite materials) and keep impact away from the door track
- An angled top to prevent hand injury
- Durable yellow powder-coat paint finish which acts as both a visual deterrent and corrosion inhibitor



# OVERHEAD DOOR TRACK PROTECTION

## STANDARD TRACK PROTECTOR CHOICES INCLUDE:

- Steel thicknesses of 1/8" (3.17mm), 3/16" (4.76mm), 3/8" (9.52mm), and 1/4" (6.35mm)
- Height choices of 36" (914.5mm) or 48" (1219mm)
- 7" (177mm) projection from the wall mounting surface
- Integral L-shaped floor mounting plates for extra resistance to impact 9" (228mm) wide and 8" (203mm) projection), or no floor mounting plates for easier installation
- Optional anchor kits - the wall flange and floor plate are drilled for 1/2" (13mm) anchors
- Most sizes are in stock and ready-to-ship

OPTIONAL ANCHOR KITS  
(6 anchors per kit)



WITH FLOOR MOUNTING PLATE



NO FLOOR MOUNTING PLATE

## SLIM TRACK PROTECTORS

- Narrow "slim" design for installation in areas where obstructions and tight door centerlines are a concern.
- 3/16" (4.76mm) x 48" (1219mm) high, with custom sizes available.
- Project 5-1/2" (140mm) from the wall.
- Single unit construction permits installation on either side of the door.

For detailed specifications, drawings and installation information, please visit [idealwarehouse.com](http://idealwarehouse.com).



48" (1219mm)



SLIM

## MORE SAFETY SOLUTIONS



Forklift Safety Products



Knuffi Edge Guards



Wheel Chock Safety Systems



Guarding Systems



**IDEAL WAREHOUSE  
INNOVATIONS INC.**  
Protecting Your People

Toll-Free Phone: **1-866-828-6737**  
Toll-Free Fax: **1-844-899-0088**

**IdealWarehouse.com**  
[info@idealwarehouse.com](mailto:info@idealwarehouse.com)

Many Ideal Warehouse Innovations Inc Safety Products are trademarked and covered by U.S. or international patents. Products may change without prior notice.  
Form [TrackProtection-EN-HI-IW-L-202207]