

Premium Duty Spring Retractable Hose Reels

Series 3000 - Air/Water - 1/4", 3/8" I.D.

- Ultra-compact for a wide range of bench mount or mobile applications with critical space requirements
- Compact size - reel easily fits within a 1 ft. x 1 ft. space
- Multiple slotted mounting holes to accommodate many configurations
- Inlet located on base eliminating the possibility of hose interfering with spool operation

NEW!



S602805 -
Optional guide
arm accessory

B3425 OLP

Additional Series 3000 Models

Cord Reels - Page 29

Model with hose & bumper	Shipping Weight	Hose I.D.	Hose O.D.	Hose Length	Max Pressure	NPT(M) Hose Outlet	NPT(F) Reel Inlet	NPT(F) Reel Outlet
	lbs kg	in mm	in mm	ft m	psi bar	in	in	in
Low Pressure Air / Water Hose Reels Maximum temperature 150 °F (65 °C)								
B3425 OLP	18 8.2	1/4 6	.475 12	25 7.6	300 21	1/4	3/8	3/8
B3610 OLP	17 7.7	3/8 10	.600 15	10 3.0	300 21	1/4	3/8	3/8
B3620 OLP	18 8.2	3/8 10	.600 15	20 6.1	300 21	1/4	3/8	3/8
S602805	1.1 0.5	Optional guide arm accessory for multiple adjustment positions						

Low pressure reels furnished standard with PVC hose.

Under Bench Mount		Dimensions	
		in	mm
A	11 ³ / ₁₆	284	
B	11 ¹ / ₁₆	281	
C	6	152	
D	8	203	
E	4 ³ / ₁₆	106	
F	6	152	
G	2 ¹ / ₂	64	

Premium Duty Spring Retractable Reels

Series 4000 - Air/Water - 1/4", 3/8" I.D.



- Compact for a wide range of applications with critical space requirements
- Guide arm adjusts to two positions
- Inlet hose is plumbed into the base to eliminate the risk of stress on the swivel

Additional Series 4000 Models

Cord Reels - Page 29-32

Single Line Welding Reels - Page 34



4625 OLP

Series 4000 reels include a speed latch mechanism that uses a cam and disc for quiet operation. Series B4000 reels includes a ratchet latch mechanism that produces a distinct "clicking" noise while in use.

Model with hose & bumper	Shipping Weight	Hose I.D.	Hose O.D.	Hose Length	*Max Pressure	NPT(M) Hose Outlet	NPT(F) Reel Inlet	NPT(F) Reel Outlet
	lbs kg	in mm	in mm	ft m	psi bar	in	in	in
Low Pressure Air/Water Reels Maximum Temperature 150 °F (65 °C)								
4420 OLP	18 8	1/4 6	.475 12	20 6	300 21	1/4	3/8	1/4
4425 OLP	19 9	1/4 6	.475 12	25 8	300 21	1/4	3/8	1/4
B4425 OLP	19 9	1/4 6	.475 12	25 8	300 21	1/4	3/8	1/4
4435 OLP	19 9	1/4 6	.475 12	35 11	300 21	1/4	3/8	1/4
4615 OLP	19 9	3/8 10	.600 15	15 5	300 21	1/4	3/8	1/4
4617 OLP	19 9	3/8 10	.600 15	17 5	300 21	1/4	3/8	1/4
4625 OLP**	20 9	3/8 10	.600 15	25 8	300 21	1/4	3/8	1/4
B4625 OLP	20 9	3/8 10	.600 15	25 8	300 21	1/4	3/8	1/4

Low pressure reels supplied standard with PVC hose. See operating instructions for optimum mounting configuration. *Maximum working pressure at 70 °F (20 °C) **Side mount configuration available; visit reelcraft.com for more information.

Dimensions		in	mm
A	12 ⁷ / ₈	327	
B	12 ⁵ / ₈	321	
C	8	203	
D	2 ¹ / ₂	64	
E	5 ⁵ / ₈	143	



Interactive Reel Catalog

Visit reelcraft.com/catalog for complete product specifications, available parts, and accessories.



Pivot Bases & Swing Brackets

See page 43

Model without hose & bumper	Shipping Weight	Hose Capacity			Max Pressure	NPT(F) Reel Inlet	NPT(F) Reel Outlet
		I.D.	O.D.	Length			
	lbs kg	in mm	in mm	ft m	psi bar	in	in
Low Pressure Air/Water Reels Maximum Temperature 210 °F (99 °C)							
4400 OLP	17 8	1/4 6	.475 12	35 11	500 35	3/8	1/4
4600 OLP	17 8	3/8 10	.600 15	25 8	500 35	3/8	1/4