

OWNER'S MANUAL 9 gallon Wet/Dry Vacs

For model: 457PR09GAL

CONGRATULATIONS!

You have just purchased a Lavex™. Vacuum Cleaner. Please read this manual carefully before operating the machine. Model and serial number may be found on the side of your vac. You should record both model and serial numbers and keep them in a safe place for future use.

Save these instructions for future reference.

Electrical Rating: 120 V~ 10 A 60 Hz

CONTENT

Important safety instructions Warning Product description Polarized connection Vac assembly

Caster / Caster foot assembly Storage Filter assembly Filter maintenance Operation Trouble shooting Hose clamp assembly Warranty Cleaning the tank

IMPORTANT SAFETY INSTRUCTIONS


When using an electric vacuum cleaner, basic precautions should be followed

Read all instructions before using this vacuum cleaner.

This vacuum cleaner is for domestic use only; it may be used for vacuuming wet or dry materials and as a blower

WARNING

- To reduce the risk of fire, electric shock or injury:
- 1. Do not use to pick up flammable or combustible liquids, such as gasoline or use in areas where such items may be present.
- 2. Use product only as described in this manual, use only manufacturer's recommended attachments.
- 3. Do not pick up anything that is burning or smoking; such as cigarettes, matches or hot ashes. 4. Do not leave vacuum plugged in. Unplug from outlet when not in use and before servicing.
- 5. Turn unit off before unplugging
- 6. Do not put any object into openings. Do not use with any opening blocked.
- Keep free of dust, lint, hair and anything that may reduce air flow. Do not use without filter in place.
- 8. Do not allow vacuum to be used as a toy, or to run unattended at any time. If used near children, close supervision is necessary
- 9. Do not store outdoors.
- 10. Do not use with a damaged cord or plug. If vacuum is not working as it should, or if it has been dropped, damaged, or submerged into water, return it to an authorized service center.
- Do not pull or carry by cord, use cord as a handle, close a door on a cord or pull cord around sharp edges or corners, do not run vacuum over cord. Keep away from heated surfaces.
- 12. Do not unplug by pulling on cord. To unplug, grasp the plug, not the cord. 13. Do not unplug or vacuum with wet hands. Use extra care when cleaning stairs.
- 14. Keep hair, loose clothing, fingers and all parts of body away from openings and moving parts.
- 15. Never use vacuum cleaner as a pump.
- 16. If the line cord is damaged it must be replaced by the manufacturer or an authorized service center
- Connect to a properly grounded outlet only. See grounding instructions.
 Do not use without filter in place. See filter instructions
- 19. Do not pick up soot, cement, plaster or drywall dust. These are very fine particles that may pass through the filter and affect te performance of the motor or be exhausted back into the
- 20. Use special care when emptying heavily loaded tanks. 21. WARNING! Do NOT use this vacuum cleaner to vacuum lead paint debris because this may disperse fine lead particles into the air.



POLARIZED CONNECTION

This appliance is for use on a 120 V~ circuit, and has a polarized plug as shown in figure A. A temporary adapter may be used to connect this plug to Non-polarized outlet. Temporary adapter should be used only until a properly polarized outlet can be installed by a gualified electricity. qualified electrician.



NOTE: In Canada, the use of a temporary adapter is not permitted by the Canadian Electrical Code.

WARNING



Improper connection of the equipment grounding conductor can result in a risk of electric shock. Check with a qualified electrician or service person if you are in doubt as to whether the outlet is properly grounded. Do not modify the plug provided with the appliance if it does not fit the outlet, have a proper outlet installed by a qualified electrician.

VAC ASSEMBLY



Always unplug the vacuum from the outlet current, before performing any maintenance.

Fig. 1

Fig. 2


- 1. Line up the motor head with the tank. Pull the side latches out and lower the head. Snap the latches into place. (fig.1)
- 2. To connect the hose push on the vacuum port while inserting. Press the end of the hose into the suction point. (fig.2)
- 3. To release the hose, pull out.
- 4. Place the desired accessory on the other end of the hose.
- 5. Plug power cord.
- 6. To turn on se switch on motor head.
- 7. Familiarize yourself with the control and features of your vacuum cleaner.

Not all accessories are included with all models. Check panel on box for more information.

CASTER/CASTER FO

To assamble the casters on the unit:

- 1. Turn dust drum upside down on the floor.
- 2. Insert plastic caster foot into the bottom of drum.
- 3. Push until it is flush, with bottom of the dust drum.
- 4. Turn drum upright.



I AVE)

FILTER ASSEMBLY

Slide over cage until the filter stops against the lid.

FILTER USE

1. This vacuum includes a paper filter for fine dust pick up. 2. The paper filter should always be removed for wet pick ups

3. When vacuuming liquids the unit has a float that will rise to the top and shut off suction when the tank is full. This will increase the motor's rpm's.

4. Turn off the vac and dump out liquids to continue using the unit.

OPERATION

TO VACUUM SOLIDS

Never vacuum solids WITHOUT THE FILTER, this will damage the machine and invalidate the warrant

Follow the instructions in "Filter Assembly" on this page.

AIR EXPULSION SYSTEM

Never eject air WITHOUT THE FILTER, this will damage the machine and invalidate the warranty.

This Lavex[™] vacuum cleaner also functions as an air blower. It has the capability to blow sawdust and other debris. It is excellent to use to blow dust and debrisout of garages or off patios and driveways.

WARNING:

To avoid injury to by standers, keep them clear of blowing debris. The operation of any utility vac can result in foreign objects being blown into the eyes, which can result in severe eye damage. Always wear safety goggles.

To use your Lavex vacuum as a blower:

- Locate the blowing port of your vac.
 Insert flexible end of the hose into the blowing port.
- Turn vac "ON" and you are ready to use your vac as a blower.

IMPORTANT:

To avoid damage to the unit do not let the motor run with a full tank.

TO VACUUM LIQUIDS Never vacuum liquids **WITH THE FILTER PLACED**, this will damage the filter and invalidate the warranty.

- Never vacuum liquids whith the filter
- 1. Separate the top part of the vacuum cleaner.
- Remove the filter from the motor grille.
 Place the top part in its place, until you hear the click of the sides.
- Place the hose in the suction port, then the accessory, turn on and go.



HOSE CLAMPS ASSEMBLY

- 1. Make sure the vacuum head is correctly assembly to the tank.
- 2. Place the hose clamp slightly at an angle in the space allotted
- to the accessory.
- 3. Afterwards, center the accessory and push it down (As shown in image)
- 4. Verify that the accessory is properly placed.



CLEANING THE TANK

- 1. Unplug power cord.
- 2. Remove the hose.
- 3. Unlock the side latches.
- 4. Place cover upside down on a clean surface.
- 5. Dump tank contents into a waste container.

WARNING

To avoid back injury or falls, do not lift a vac heavy with liquid or debris. Scoop or drain enough contents out to make the vac light enough to lift comfortably.



STORAGE

VAC AND ACCESSORIES

Before storing your vac, the dust tank should be emptied and cleaned. Accessories should be stored on the tool caddy.

The vac should be stored in doors.

Always use the unit with the filter when vacuuming dry debris and dust.

Manufactured for: Fabricado para:

Lavex Janitorial 2205 Old Philadelphia Pike Lancaster, PA 17602 P. (717) 392-7550 www.webstaurantstore.com



FILTER MAINTENANCE

WARNING: To avoid injury from accidental starting, unplug power cord before changing or cleaning filter.

CLEANING:

Your filter should be changed often to maintain peak vac performance.

NOTE: This filter is made of high quality materials designed to stop very small particles of dust. Handle the filter carefully when removing to clean or installing it. Creases in the filter pleats may occur from installation but creases will not affect the performance of the filter.

Always use the unit with the filter when vacuuming dry debris and dust.

IMPORTANT: After cleaning the paper filter, check for holes. If any holes are foundreplace the filter immediately. Even small holes will permit dust to come out of the vac.

GENERAL MAINTENANCE

To keep your wet / dry vac looking its best, clean the outside with a cloth dampened with water and mild soap.

To clean the tank:

Dump out debris.
 Wash drum thoroughly.
 Wipe out with dry cloth.



To assure product SAFETY AND RELIABILITY, repairs and adjustments **WARNING** contact your distributor or call (717) 392.75.50, always using Lavex replacement parts.

TROUBLE SHOOTING

PROBLEM	POSSIBLE CAUSE	POSSIBLE SOLUTION
Vacuum does not start	Not firmly plugged in.	Plug in firmly.
Low suction	Tank full.	Empty the tank.
	Filter is dirty.	Shake dust out of filter. Shake dust out of filter. See "Filter Maintenance" section.
	Obstruction in hose	Connect the hose to the blowing port until hoseis clear.
	Motor head not installed correctly	Be sure that the motorhead seats properlyon the tank.

WARRANTY

This warranty gives you specific legal rights, and you may also have other rights, which vary from state to state.

This product is warranted against malfunctions and defects in material and workmanship for a period of 1 (one) year and 5 (five) years on motor and transmission.

THIS WARRANTY SHALL NOT APPLY to any products or parts there of which have been damaged by tampering, misuse or abuse or which have been altered or repaired by an unauthorized person or service center.

THIS WARRANTY SHALL NOT APPLY to brushes, since length of their life depends upon the amount of use.

FOR REPAIR, the inoperative machine must be delivered with shipping and delivery charges prepaid, together with satisfactory evidence of the purchase date to the dealer from whom it was purchased. Lavex will either repair or replace, at its election, all defective machines during the warranty period.

THE FOREGOING OBLIGATIONS ARE IN LIEU OF ALL OBLIGATIONS AND LIABILITIES INCLUDING NEGLIGENCE AND STATE LAVEX'S ENTIRE AND EXCLUSIVELY LIABILITY AND PURHCASER'S EXCLUSIVE REMEDY LAVEX WILL IN NO EVENT BE LIABLE FOR ANY DIRECT, INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES OR LOSSES WHATSOEVER, AND LAVEX LIABILITY UNDER NO CIRCUMSTANCES WILL EXCEED THE CONTRACT PRICE FOR THE GOODS OR PARTS FOR WHICH LIABILITY IS CLAIMED.

Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you.