

## LUBRIQUIK Food Grade Silicone Lubricant

LUBRIQUIK Food Grade Silicone Lubricant is designed to lubricate equipment used in the packaging and processing industry. Leaves a non-staining dry pure silicone film to lubricate moving parts, reducing friction and wear. Product is heat stable from -35°F to 350°F. Also formulated as a release agent on seals and gaskets of tank closures. Lubricates all sliding surfaces except those you wish to paint. Excellent on RV slide outs. Use on sticking metal, wood, rubber and plastic. Apply to cutting tables, conveyors, heat sealing equipment and slicing equipment. Waterproofs leather, canvas, rubber and chrome surfaces. Safe on all plastics. Complies with FDA regulations, CFR Title 21, paragraph 178.3570 when fully cured. Contains no methylene chloride. Won't melt, freeze, gum or become rancid.

### DIRECTIONS:

Read cautions and directions carefully before use. Area to be lubricated should be clean and dry. Shake well before use. Hold can 6-8 inches from surface. Spray in short bursts. Spray no more than required to lubricate surface. Do not spray electrical equipment while in use. Wait 5-10 minutes before operating electrical equipment after using. Spray is dry. Do not expect a liquid. Used as directed, it will not harm most surfaces.

### DANGER:

Extremely Flammable Aerosol. Contains gas under pressure; may explode if heated. Causes skin and serious eye irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways. Keep away from heat,

sparks, open flames, and hot surfaces. —No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Wash hands thoroughly after handling. Wear protective gloves and eye protection. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. Avoid breathing fumes, mist, vapors, and spray. Use only outdoors or in a well-ventilated area. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell. If swallowed: Immediately call a poison center or doctor. Do NOT induce vomiting. Dispose of contents and container in accordance with local, state, and national regulations.

### CONTAINS (CAS#):

Acetone (67-64-1), Propane/n-Butane (68476-86-8), Heptane (142-82-5), Polydimethylsiloxane (63148-62-9).

Made in USA



Nonfood Compounds  
H1

999LUBRIQUIK



4 000101 02180 2

Distributed by:



2205 Old Philadelphia Pike  
Lancaster, PA 17602  
1-888-256-6400

# LUBRIQUIK

## Food Grade Silicone Lubricant

- Multipurpose
- Colorless, Odorless
- Non-Toxic & Heat Stable
- Precise Fan Spray Control
- Hexane Free, VOC Compliant
- No Sticky Residue



**DANGER: EXTREMELY FLAMMABLE  
AEROSOL. CONTAINS GAS UNDER  
PRESSURE; MAY EXPLODE IF HEATED.**  
See back panel for additional precautions.

NET WT. 11.5 OZ. (326 GRAMS)