NORLAKE®





FAST-TRAK®

Walk-In Coolers and Freezers


Easy installation with the flexibility of additional options

Features

- Available in widths of 6'-12' in 1' increments
- Depths of 6'-20' in 1' increments
- Heights: 6'7", 7'7" and 8'7" with floor, 7'4" and 8'4" floorless
- Indoor or outdoor models
- Combination cooler/freezers are offered as:
  - >All with-floor or all less-floor
  - >Both compartments equal size (6'-20' width for each in 1' increments)
- Corrosion resistant stucco embossed coated steel exterior
- Full 4" panel foamed-in-place with HFC free
- HFO polyurethane insulation
- 26", 30" or 36" wide self-closing doors
- Doors are shipped with (2) 2-foot wide filler panels for field-configurable installation along any wall
- Digital thermometer and light switch
- Adjustable spring loaded hinge
- Spring actuated door closer
- Deadbolt locking handle for security
- Refrigeration system choices include remote Split-Pak A2L™ and self-contained Capsule Pak ECO™ (for compartments under 14' in length)
- Temperatures: +38°F, +37°F, -10°F
- 15 year panel warranty
- 18 months parts and labor warranty

OPTIONS & ACCESSORIES

- Heavy-duty floor with 1/2" plywood underlayment for heavy foot traffic and light rolling carts, rated load 1000 psf
- Interior and/or exterior 30" high stainless steel or aluminum diamond tread door kick plates
- Interior and exterior ramps for with-floor models
- Non-skid strips (shipped loose)
- Extra LED lights (shipped loose)
- Outdoor membrane roof systems
- 14" x 24" viewports (freezer ports heated)
- Strip curtains (shipped loose)
- Door rain hoods
- Leak detector/alarm (may be a requirement in some areas)
- Specially designed shelving kits
  - Flexible shelf adjustment in 1" increments
  - Shelving layouts utilize maximum space for storage leaving the door opening clear of end standards
  - Green Kote™ special epoxy-coated finish provides extra protection from acidic foods
  - Quick and easy assembly
  - Rigid construction
  - Optional U-shaped systems




Viewports allow visibility of products stored inside.



Door and frame kickplates add protection to entry doors.




Roll items directly into your walk-in with interior or exterior ramps.



Heavy-duty flooring supports high-volume foot traffic and light rolling carts.

REFRIGERATION SYSTEM OPTIONS

R290 REFRIGERANT



PATENTED TECHNOLOGY U.S. Patent No. 11,859,885

CAPSULE PAK ECO™ SELF-CONTAINED SYSTEMS*



R449A REFRIGERANT

SPLIT-PAK™ REMOTE SYSTEMS**



A2L REFRIGERANT

SPLIT-PAK A2L™ REMOTE SYSTEMS**

* Capsule Pak ECO systems are intended for compartments 14' long and under.
** Dedicated medium temp condensing units meet the DOE requirement of a minimum AWEF rating of 5.61 (Btu/W-h) for indoor models and 7.6 for outdoor models.

NORLAKE®
891 County Road U • Hudson, WI 54016
800-955-5253 • www.norlake.com

RSG Refrigerated Solutions Group®

101625 Rev. H All specifications within this publication subject to change without notice. ©2026 Norlake, Inc. All rights reserved.