

## ANCHORAGE CONNECTORS AND SYSTEM KITS

## TEMPORARY ANCHORAGE CONNECTORS

## DISPOSABLE CONCRETE ANCHOR STRAP

Uniquely designed to provide temporary anchorage on concrete forms. Constructed of 1-3/4 in wide, abrasion-resistant webbing.

SKU	Description
8185C/2FTGN	Concrete anchor strap with steel d-ring 2 ft model
8185C/3FTGN	Concrete anchor strap with steel d-ring 3 ft model
8185C/4FTGN	Concrete anchor strap with steel d-ring 4 ft model



8185C/3FTGN

## CONCRETE D-BOLT ANCHORAGE CONNECTOR

417C/ includes a 5/8 in stud-type expansion anchor that is ideal for applications with concrete and lightweight concrete that meet required specifications, min. 13.8 MPa (2,000 psi). Can be installed on a vertical wall or overhead for versatility. Concrete Expansion Bolt (417CBOLT/) available separately.

SKU	Description
417C/	Concrete D-bolt Anchorage Connector with Hardware
417CBOLT/	Concrete Expansion Bolt



417C/



8815-12/



8816-14/

## MILLER SHADOW®

## Lightweight Sliding and Fixed Adjustable Beam Anchors

Miller Shadow Sliding and Fixed Adjustable Beam Anchors connect horizontally to a wide range of I- and H-beam flanges from 3 in to 24 in wide and up to 2-1/2 in thick. Once attached, the beam anchor (SKUs 8814 and 8816) slides along the beam with the worker to provide increased safety, mobility, and productivity.

The fixed beam anchors (SKU 8815) are designed to be tightened horizontally or vertically, firmly gripping the beam or column to provide a temporary or permanent anchorage attachment.

SKU	Application	Description	Fits Flange Sizes	Maximum Flange Thickness
8814-12/	Horizontal	Sliding Shadow Beam Anchor – stainless steel & high-strength aluminum	4 in to 12 in	1-1/4 in
8814-24/	Horizontal	Sliding Shadow Beam Anchor – stainless steel & high-strength aluminum	12 in to 24 in	2-1/2 in
8815-12/	Vertical/Horizontal	Fixed Beam Anchor – stainless steel & high-strength aluminum	4 in to 12 in	1-1/4 in
8815-24/	Vertical/Horizontal	Fixed Beam Anchor – stainless steel & high-strength aluminum	12 in to 24 in	2-1/2 in
8816-14/	Horizontal	Sliding ShadowLite™ Beam Anchor – high-strength aluminum & bronze, 4.2 lb	3 in to 14 in	1-1/4 in