

Corrosion Resistant • Light Weight • Aluminum Rolling Ladders

Aluminum ladders are lightweight, weather resistant, durable & easy to transport, with noncorrosive properties that make them the ideal choice for many applications in both outdoor and indoor environments.

# OF STEPS INCLUDING TOP STEP	Height Inches		SPRING LOADED CASTERS MODEL #	TILT & ROLL MODEL #	BASE W" x L"	WGT Lbs.
	TOP STEP	OVER ALL				
18" WIDE STEPS						
2 STEP NO RAILS	19	19	A2S*	-	20 x 19	15
3 STEP NO RAILS	28.5	28.5	A3S*	-	20 x 25	20
4 STEP NO RAILS	38	38	A4S	-	20 x 31	29
2 STEP	19	49	A2SH	A2SH-TR	20 x 19	21
3 STEP	28.5	58.5	A3SH	A3SH-TR	20 x 25	27
4 STEP	38	68	A4SH	A4SH-TR	20 x 31	34
24" WIDE STEPS						
2 STEP NO RAILS	19	19	A2S30*	-	30 x 19	22
3 STEP NO RAILS	28.5	28.5	A3S30	-	30 x 25	28
4 STEP NO RAILS	38	38	A4S30	-	30 x 31	35
2 STEP	19	49	A2SH30	A2SH30-TR	30 x 19	28
3 STEP	28.5	58.5	A3SH30	A3SH30-TR	30 x 25	34
4 STEP	38	68	A4SH30	A4SH30-TR	30 x 31	41
5 STEP	47.5	77.5	A5SH30	A5SH30-TR	30 x 37	49
6 STEP	57	87	A6SH30	A6SH30-TR	30 x 43	60
7 STEP	66.5	96.5	A7SH30	A7SH30-TR	30 x 49	67

* Eligible for UPS. Tilt and roll casters add 5" to base length.

NOTE: Aluminum ladders are subject to a 50% restocking charge

Specify Tread Type when Ordering:

- Ribbed Tread (R)
- Heavy Duty Serrated Grating (G)



ALUMINUM LADDERS

- **350 LB. CAPACITY**
- All welded
- Aluminum mill finish, industrial grade welds
- Ideal for use in banks, libraries & hospitals and wash down applications
- Lightweight design
- Non-magnetic and non-sparking
- Paint-free for food and pharmaceutical applications
- Solid ribbed tread or heavy duty serrated grating
- 10" standard deep top step
- Optional 20" deep top step
- Built to OSHA & ANSI standards

POPULAR LOCK-N-STOCK - NOW AVAILABLE IN ALUMINUM

The feature is the drastically reduced weight. The benefit is less effort to maneuver the ladder leading to better productivity. Two Versions: a 7" deep top step with 22" high handles and a 10" deep top step with 30" high handles along with a rear guardrail. Lock the ALUMINUM stair section in place and **CLIMB IT- ROLL-IT- FOLD IT AND STORE IT!!**



MODEL NUMBER	STEPS INCLUDING TOP STEP	TOP STEP HEIGHT	WEIGHT LBS.	OPEN WIDTH & LENGTH	FOLDED SIZE	COLOR
ALS3247	3	28.5"	23	24 x 23	10 x 24 x 52	BLUE
ALS4247	4	38"	28	24 x 30	10 x 24 x 65	BLUE
ALS32410	3	28.5"	26	24 x 28	14 x 24 x 62	BLUE
ALS42410	4	38"	31	24 x 35	14 x 24 x 72	BLUE

ALUMINUM LIFT & ROLL WHEELBARROW STYLE LADDERS

Features 10" rubber wheels for easy portability even on rough surfaces. 14"-deep top step provides range of motion when working at higher levels. Nonmagnetic, non-sparking & paint-free, aluminum ladders are acceptable for pharmaceutical & food processing industries. Industrial-grade welds allow them to be used in wash-down applications.

SPECIFY TREAD TYPE WHEN ORDERING: Ribbed Tread (R) • Heavy Duty Serrated Grating (G)

STEPS INCLUDING TOP STEP	HEIGHT INCHES		18" WIDE TREAD	24" WIDE TREAD*	
	TOP STEP	OVER ALL	MODEL #	WGT Lbs.	MODEL #
5 STEP	50"	83"	30 x 47	ALWB5	42
6 STEP	60"	93"	30 x 53	ALWB6	50
7 STEP	70"	103"	30 x 60	ALWB7	58
8 STEP	80"	113"	36 x 66	ALWB8	66
9 STEP	90"	123"	36 x 72	ALWB9	74
10 STEP	100"	133"	36 x 78	ALWB10	82

*Models with 24" wide steps have 36" wide base

14" DEEP TOP STEP



10" RUBBER WHEELS

NEW! ALUMINUM LOCK-N-STOCK

- **300 LB. CAPACITY**
- Welded Construction
- Perforated Tread
- No hinge to break
- Easy to maneuver in the open or closed position
- Locks in the folded or climbing position
- Approx 10" deep when folded and 14" deep on 10" deep top step models
- Built to ANSI standards
- Blue powder coat finish

WHEEL BARROW STYLE ALUMINUM LADDERS

- **300 LB. CAPACITY**
- All welded
- 14" deep top step standard
- 10" rear rubber wheels - Great on rough surfaces
- Lightweight lift and roll wheelbarrow portability
- Built to OSHA and ANSI standards