

BACK BAR COOLER

ERV SERIES



Instagram Facebook LinkedIn InfricoUSA



INFRICO USA CORP
11200 NW 25th Street STE 123
Sweetwater, FL 33172
305-777-9599
sales@infrico.com



BOTTLE COOLERS: NARROW BACK BAR COOLERS



IMD-ERV 15GD
IMD-ERV 25GD
IMD-ERV 35GD



Stainless Steel Exterior
IMD-ERV 15IIGD
IMD-ERV 25IIGD
IMD-ERV 35IIGD



IMD-ERV 15SD
IMD-ERV 25SD
IMD-ERV 35SD



Stainless Steel Exterior
IMD-ERV 15IISD
IMD-ERV 25IISD
IMD-ERV 35IISD

BACK BAR COOLERS: STAINLESS STEEL INTERIOR AND EXTERIOR



IMD-ERV 36IIGD
IMD-ERV 60IIGD
IMD-ERV 84IIGD



IMD-ERV 36IISD
IMD-ERV 60IISD
IMD-ERV 84IISD

GENERAL FEATURES

SANITATION

Quick ability to take off shelves and slides for a quick and efficient cleaning.

DOORS

All doors include door gaskets, easy to remove and snap in.

CONTROL SYSTEMS

Higher precision in managing temperature settings. Greater ability for the adjustment of temperatures ranges as per the end user's requirement.

100% TESTED

All condenser units are tested 100%, in helium chambers for refrigerant leak detections.

CERTIFIED

Audited and Certified by INTERTEK for compliance with UL 471 and NSF 7. EQA audited and certified by internationally recognized firm. ISO 9001:2015 (Quality); ISO 14001:2015 (Environmental); ISO 45001:2018 (Prevention and Worker Safety)

LIGHTING

LED lighting in cabinet sides reduces the energy consumption by 80% and 90% compared to a traditional bulb. Provides a much better light quality.



RGB LED
Lighting (standard)



IMD-ERV25GD



IMD-ERV35IIGD



IMD-ERV25C (sliding doors)

MODEL	DIMENSIONS (INCHES)			DOORS	SHELVES	REF	Ref. Weight (Lbs.)	Temperature Range (°F)	Cond. Unit	Capacity (Cu.Ft.)	Case Amps 115V	Crated weight (Lbs.)
	W	D	H									
IMD-ERV15GD	23-5/8	20-1/8	35-3/4	1	2	R290	0,17	39 °F/54 °F	1/5	5	3,58	152
IMD-ERV25GD	35-3/8	20-1/8	35-3/4	2	4	R290	0,24	39 °F/54 °F	1/5	8	3,89	202
IMD-ERV25C	35-3/8	20-1/8	35-3/4	2	4	R290	0,24	39 °F/54 °F	1/4	8	3,99	202
IMD-ERV35GD	53-1/8	20-1/8	35-3/4	3	6	R290	0,24	39 °F/54 °F	1/3	11,6	3,90	284
IMD-ERV15IIGD	23-5/8	20-1/8	35-3/4	1	2	R290	0,17	39 °F/54 °F	1/5	5	3,58	152
IMD-ERV25IIGD	35-3/8	20-1/8	35-3/4	2	4	R290	0,24	39 °F/54 °F	1/5	8	3,89	202
IMD-ERV35IIGD	53-1/8	20-1/8	35-3/4	3	6	R290	0,24	39 °F/54 °F	1/3	11,6	3,90	284

OPTIONAL FEATURES

Set of 2" Casters, front locking

Electrical connection is 220-230 V / 1ph / 50Hz (plug type varies).

Electrical connection is 220-230 V / 1ph / 60Hz (plug type varies).



IMD-ERV25SD



IMD-ERV35IISD

MODEL	DIMENSIONS (INCHES)			DOORS	SHELVES	REF	Ref. Weight (Lbs.)	Temperature Range (°F)	Cond. Unit	Capacity (Cu.Ft.)	Case Amps 115V	Crated weight (Lbs.)
	W	D	H									
IMD-ERV15SD	23-3/4	20-1/8	35-3/4	1	2	R290	0,17	39 °F/54 °F	1/3	5	3,63	160
IMD-ERV25SD	35-1/2	20-1/8	35-3/4	2	4	R290	0,22	39 °F/54 °F	1/3	8	3,99	187
MD-ERV35SD	53-1/4	20-1/8	35-3/4	3	6	R290	0,24	39 °F/54 °F	1/4	11,6	4,00	213
IMD-ERV15IISD	23-5/8	20-1/8	35-3/4	1	2	R290	0,17	39 °F/54 °F	1/5	5	3,63	152
IMD-ERV25IISD	35-3/8	20-1/8	35-3/4	2	4	R290	0,22	39 °F/54 °F	1/5	8	3,89	202
IMD-ERV35IISD	53-1/8	20-1/8	35-3/4	3	6	R290	0,22	39 °F/54 °F	1/3	11,6	4	284

OPTIONAL FEATURES

Set of 2" Casters, front locking.

Electrical connection is 220-230 V / 1ph / 50Hz (plug type varies).

Electrical connection is 220-230V / 1ph / 60Hz (plug type varies).



IMD ERV 60II GD



IMD ERV 84II GD

MODEL	DIMENSIONS (INCHES)			DOORS	SHELVES	REF	Ref. Weight (Lbs.)	Temperature Range (°F)	Cond. Unit	Capacity (Cu.Ft.)	Case Amps 115V	Crated weight (Lbs.)
	W	D	H									
IMD-ERV36IIGD	36-1/4	23-3/4	34-1/2	1	2	R290	0,24	33 °F/ 38 °F	1/5	5,72	3,59	290
IMD-ERV60IIGD	60-3/4	23-3/4	34-1/2	2	4	R290	0,24	33 °F/ 38 °F	1/5	12,78	5,2	390
IMD-ERV84IIGD	85-1/4	23-3/4	34-1/2	3	6	R290	0,26	33 °F/ 38 °F	1/3	19,85	6	500

OPTIONAL FEATURES

Set of 2" Casters, front locking

Electrical connection is 220-230 V / 1ph / 50Hz (plug type varies).

Electrical connection is 220-230 V / 1ph / 60Hz (plug type varies).



IMD ERV 60II SD



IMD ERV 84II SD

MODEL	DIMENSIONS (INCHES)			DOORS	SHELVES	REF	Ref. Weight (Lbs.)	Temperature Range (°F)	Cond. Unit	Capacity (Cu.Ft.)	Case Amps 115V	Crated weight (Lbs.)
	W	D	H									
IMD-ERV36IISD	36-1/4	23-3/4	34-1/2	1	2	R290	0,24	33 °F/ 38 °F	1/5	5,72	3,59	290
IMD-ERV60IISD	60-3/4	23-3/4	34-1/2	2	4	R290	0,26	33 °F/ 38 °F	1/5	12,78	12,78	390
IMD-ERV84IISD	85-1/4	23-3/4	34-1/2	3	6	R290	0,26	33 °F/ 38 °F	1/3	19,85	19,85	500

OPTIONAL FEATURES

Set of 2" Casters, front locking

Electrical connection is 220-230 V / 1ph / 50Hz (plug type varies).

Electrical connection is 220-230 V / 1ph / 60Hz (plug type varies).



5 YEAR WARRANTY

Parts & Labor - 7 YEAR COMPRESSOR