



Built-In Solutions

Cafeterias • Buffets
Supermarkets & Delis • Restaurants & Cafés



CSSBF-48-S in optional Bermuda Sand built into a Bermuda Sand Simulated Stone countertop *pg. 2*



GRSSB-3618 in standard Night Sky Simulated Stone *pg. 7*



HBGB-3618 shown below a **GR2AHL-42** with *Designer* non-adjustable stands and optional sneeze guards built into a Simulated Stone countertop *pg. 8*



GRSB-30-I Glo-Ray® Built-In Heated Shelf with Recessed Top and accessory food pans shown below a **GRAHL-36** with adjustable tubular stands and optional sneeze guards *pg. 9*



GRSB-54-I with Recessed Top and accessory food pans shown below a **GRAL-96D** with optional sneeze guard *pg. 9*



GRSBF-60-0 Glo-Ray® Built-In Heated Shelf with Flush Top, built into a Bermuda Sand Simulated Stone countertop with accessory food pans shown below a **GR2AL-96D** in *Designer* Black with optional sneeze guards *pg. 10*



Cold Simulated Stone Shelves Built-In

Hatco's new Cold Simulated Stone Shelves are a must for buffet lines in cafeterias, restaurants and much more! These sturdy, foodsafe shelves are available in three attractive Simulated Stone colors.

- Thermal break reduces condensation and temperature transfer (patent pending)
- CSSB Cold Simulated Stone Built-In Shelves match the GRSSB Heated Simulated Stone Built-In Shelves for a fully integrated look
- Control box can be mounted on the front of the cabinet, 4' from center of shelf
- Condensing unit may be mounted up to 4' away from the center of shelf
- Models shipped with Electronic Temperature Control and condensing unit
- Shelf construction utilizes R-404A refrigerant keeping food product cold
- Easy serviceability with a sight glass, service valves, dryer/filter and a receiver. Long, flexible refrigerant line (ability to pullout condensing unit) for service
- Models with Simulated Stone are Swanstone®



CSSB-4818
in Bermuda Sand
Simulated Stone



CSSBF-48-S
in Gray Granite
Simulated Stone

COLD SIMULATED STONE SHELVES BUILT-IN

Model	Dimensions W x D	Voltage Single Phase	Watts	Approx. Ship Weight
CSSB-2418	24" x 18"	120	804	130 lb.
CSSB-3018	30" x 18"	120	804	145 lb.
CSSB-3618	36" x 18"	120	804	160 lb.
CSSB-4818	48" x 18"	120	1044	185 lb.

All Cold Simulated Stone Shelf Built-In Models Feature:
Electronic Temperature Control and condensing unit.

COLD SIMULATED STONE SHELVES BUILT-IN FLUSH TOP


Model	Dimensions W x D	Voltage Single Phase	Watts	Approx. Ship Weight
CSSBF-24-F	24" x 15½"	120	804	115 lb.
CSSBF-24-I	24" x 19½"	120	804	122 lb.
CSSBF-24-S	24" x 24"	120	804	130 lb.
CSSBF-36-F	36" x 15½"	120	804	138 lb.
CSSBF-36-I	36" x 19½"	120	1044	146 lb.
CSSBF-36-S	36" x 24"	120	1044	158 lb.
CSSBF-48-F	48" x 15½"	120	1044	170 lb.
CSSBF-48-I	48" x 19½"	120	1044	182 lb.
CSSBF-48-S	48" x 24"	120	1380	195 lb.

All Cold Simulated Stone Shelf Built-In Flush Top Models Feature:
Electronic Temperature Control, condensing unit, 6' cord and plug (NEMA 5-15P).

COUNTERTOP CUTOUT DIMENSIONS

Model	Width with 3/8" radii	Depth with 3/8" radii
CSSB-2418	24¾"	18¾"
CSSB-3018	30¾"	18¾"
CSSB-3618	36¾"	18¾"
CSSB-4818	48¾"	18¾"
CSSBF-24-F	24¾"	15¾"
CSSBF-24-I	24¾"	19¾"
CSSBF-24-S	24¾"	24¾"
CSSBF-36-F	36¾"	15¾"
CSSBF-36-I	36¾"	19¾"
CSSBF-36-S	36¾"	24¾"
CSSBF-48-F	48¾"	15¾"
CSSBF-48-I	48¾"	19¾"
CSSBF-48-S	48¾"	24¾"
Model	Width	Height
Control Box	9½"	7¾"

OPTIONS AND ACCESSORIES – PAGE 4



ONE YEAR, ON-SITE PARTS AND LABOR WARRANTY. AN ADDITIONAL FOUR YEAR EXTENDED PARTS ONLY WARRANTY ON THE COMPRESSOR AVAILABLE AT THE TIME OF UNIT PURCHASE.

Hot/Cold Shelves Built-In

Give your operation ultimate flexibility with Hatco's innovative Hot/Cold Shelves Built-In (patent pending). Available in our signature Aluminum Hardcoat or in Simulated Stone, they easily transition between a heated to cold and cold to heated shelf!

- Thermal break reduces condensation and temperature transfer (patent pending)
- Shelves change modes from hot to cold or vice versa in as little as 30 minutes, allowing quick change for different day parts
- Hardcoat aluminum models (HCSBF) are top mount while Simulated Stone models (HCSSB, HCSSBF) are bottom mount, flush with counter top
- Control box and the condensing unit may be mounted on the front of the cabinet, 4' from center of shelf
- The flush mount control comes standard with a 4' lead wire
- For an integrated look:
 - HCSBF Hot/Cold Shelves match the GRSSB Heated Built-In Shelves
 - HCSSB Hot/Cold Shelves match the GRSSB Heated Built-In Shelves
 - HCSSBF Hot/Cold Shelves match the GRSSBF Heated Built-In Shelves
- Models with Simulated Stone are Swanstone®

Continued on next page...



HCSSB-4818
in Bermuda Sand
Simulated Stone



HCSSBF-48-S
in Night Sky
Simulated Stone

HOT/COLD SIMULATED STONE SHELVES BUILT-IN

Model	Dimensions W x D	Voltage Single Phase	Watts	Approx. Ship Weight
HCSSB-2418	24" x 18"	120	804	130 lb.
HCSSB-3018	30" x 18"	120	804	145 lb.
HCSSB-3618	36" x 18"	120	804	160 lb.
HCSSB-4818	48" x 18"	120	1044	185 lb.

All Hot/Cold Simulated Stone Shelf Built-In Models Feature:
Electronic Temperature Control and condensing unit.

HOT/COLD SIMULATED STONE SHELVES BUILT-IN FLUSH TOP


Model	Dimensions W x D	Voltage Single Phase	Watts	Approx. Ship Weight
HCSSBF-24-F	24" x 15½"	120	804	139 lbs.
HCSSBF-24-I	24" x 19½"	120	804	146 lbs.
HCSSBF-24-S	24" x 24"	120	804	153 lbs.
HCSSBF-36-F	36" x 15½"	120	804	160 lbs.
HCSSBF-36-I	36" x 19½"	120	1044	167 lbs.
HCSSBF-36-S	36" x 24"	120	1044	180 lbs.
HCSSBF-48-F	48" x 15½"	120	1044	196 lbs.
HCSSBF-48-I	48" x 19½"	120	1044	203 lbs.
HCSSBF-48-S	48" x 24"	120	1380	220 lbs.

All Hot/Cold Simulated Stone Shelf Built-In Flush Top Models Feature:
Electronic Temperature Control, condensing unit, 6' cord and plug (NEMA 5-15P).

COUNTERTOP CUTOUT DIMENSIONS

Model	Width with ⅜" radii	Depth with ⅜" radii
HCSSB-2418	24⅜"	18⅜"
HCSSB-3018	30⅜"	18⅜"
HCSSB-3618	36⅜"	18⅜"
HCSSB-4818	48⅜"	18⅜"
HCSSBF-24-F	24⅜"	15⅞"
HCSSBF-24-I	24⅜"	19⅞"
HCSSBF-24-S	24⅜"	24⅜"
HCSSBF-36-F	36⅜"	15⅞"
HCSSBF-36-I	36⅜"	19⅞"
HCSSBF-36-S	36⅜"	24⅜"
HCSSBF-48-F	48⅜"	15⅞"
HCSSBF-48-I	48⅜"	19⅞"
HCSSBF-48-S	48⅜"	24⅜"
Control Box	14⅝"	7¼"

OPTIONS AND ACCESSORIES – PAGE 4



ONE YEAR, ON-SITE PARTS AND LABOR WARRANTY. AN ADDITIONAL FOUR YEAR EXTENDED PARTS ONLY WARRANTY ON THE COMPRESSOR AVAILABLE AT THE TIME OF UNIT PURCHASE.



Hot/Cold Shelves Built-In *continued*

- Models shipped with Electronic Temperature Control and condensing unit
- The shelf construction utilizes R-404A refrigerant keeping food product cold
- Easy serviceability with a sight glass, service valves, dryer/filter and a receiver
- Long, flexible refrigerant line (ability to pullout condensing unit) for service



HCSBF-48-S



HOT/COLD SHELVES BUILT-IN FLUSH TOP (Aluminum Hardcoat)

Model	Dimensions W x D	Voltage Single Phase	Watts	Approx. Ship Weight
HCSBF-24-F	24" x 15½"	120	804	119 lbs.
HCSBF-24-I	24" x 19½"	120	804	126 lbs.
HCSBF-24-S	24" x 24"	120	804	133 lbs.
HCSBF-36-F	36" x 15½"	120	804	140 lbs.
HCSBF-36-I	36" x 19½"	120	1044	148 lbs.
HCSBF-36-S	36" x 24"	120	1044	160 lbs.
HCSBF-48-F	48" x 15½"	120	1044	172 lbs.
HCSBF-48-I	48" x 19½"	120	1044	185 lbs.
HCSBF-48-S	48" x 24"	120	1380	204 lbs.

All Hot/Cold Shelf Built-In Flush Top Models Feature:

Electronic Temperature Control and condensing unit, 6' cord and plug (NEMA 5-15P).

OPTIONS (available at time of purchase only)

Simulated Stone Colors (CSSBF, CSSB, HCSSBF, HCSSB Models only) –

Non-standard colors are non-returnable – Night Sky Standard –

SS-GGRAN Gray Granite

SS-BSAND Bermuda Sand

SS-NSKY Night Sky

EWC Additional four year extended parts only warranty on the Compressor available at the time of unit purchase

ACCESSORIES (available for purchase at any time)

Self-Adhesive Silicone Gasket (CSSBF, CSSB, HCSSBF, HCSSB Models only) –

SILGASK Gasket only - 18"

SILGASK-SBK Gasket with Black Silicone Caulk

SILGASK-SGRY Gasket with Gray Silicone Caulk

COLORS AND FINISHES – PAGE 11

COUNTERTOP CUTOUT DIMENSIONS

Model	Width		Depth	
	Minimum	Maximum	Minimum	Maximum
HCSBF-24-F	24⅝"	25"	16"	16½"
HCSBF-24-I	24⅝"	25"	20"	20½"
HCSBF-24-S	24⅝"	25"	24⅝"	25"
HCSBF-36-F	36⅝"	37"	16"	16½"
HCSBF-36-I	36⅝"	37"	20"	20½"
HCSBF-36-S	36⅝"	37"	24⅝"	25"
HCSBF-48-F	48⅝"	49"	16"	16½"
HCSBF-48-I	48⅝"	49"	20"	20½"
HCSBF-48-S	48⅝"	49"	24⅝"	25"
Control Box	14⅝"		7¾"	

ONE YEAR, ON-SITE PARTS AND LABOR WARRANTY. AN ADDITIONAL FOUR YEAR EXTENDED PARTS ONLY WARRANTY ON THE COMPRESSOR AVAILABLE AT THE TIME OF UNIT PURCHASE.



Cold Shelves Built-In Flush Top

Hatco's Cold Built-In Flush Top Shelves are designed to keep your pre-chilled beverages, hors d'oeuvres, side dishes, buffet items and more in the perfect chill zone.

- Thermal break reduces condensation and temperature transfer (patent pending)
- Top mounted hard coat aluminum surface
- The CSBF Cold Built-In Shelves match the GRSBF Heated Built-In Shelves for a fully integrated look
- Long, flexible refrigerant line offers the ability to pullout condensing unit for service
- Easy serviceability with a sight glass, service valves, dryer/filter and a receiver
- Control comes standard with a 4' lead wire
- Control box can be mounted on the front of the cabinet, 4' from center of shelf
- Condensing unit may be mounted up to 4' away from the center of shelf
- Shelf construction utilizes R-404A refrigerant keeping food product cold



COLD SHELVES BUILT-IN FLUSH TOP (Aluminum Hardcoat)

Model	Dimensions W x D	Voltage Single Phase	Watts	Approx. Ship Weight
CSBF-24-F	24" x 15½"	120	804	108 lbs.
CSBF-24-I	24" x 19½"	120	804	115 lbs.
CSBF-24-S	24" x 24"	120	804	122 lbs.
CSBF-36-F	36" x 15½"	120	804	130 lbs.
CSBF-36-I	36" x 19½"	120	1044	140 lbs.
CSBF-36-S	36" x 24"	120	1044	147 lbs.
CSBF-48-F	48" x 15½"	120	1044	154 lbs.
CSBF-48-I	48" x 19½"	120	1044	161 lbs.
CSBF-48-S	48" x 24"	120	1380	176 lbs.

All Cold Shelf Built-In Flush Top Models Feature:

Electronic Temperature Control and condensing unit, 6' cord and plug (NEMA 5-15P).

OPTIONS (available at time of purchase only)

EWC Additional four year extended parts only warranty on the Compressor available at the time of unit purchase

COUNTERTOP CUTOUT DIMENSIONS

Model	Width		Depth	
	Min	Max	Min	Max
CSBF-24-F	24¾"	25"	16"	16½"
CSBF-24-I	24¾"	25"	20"	20½"
CSBF-24-S	24¾"	25"	24¾"	25"
CSBF-36-F	36¾"	37"	16"	16½"
CSBF-36-I	36¾"	37"	20"	20½"
CSBF-36-S	36¾"	37"	24¾"	25"
CSBF-48-F	48¾"	49"	16"	16½"
CSBF-48-I	48¾"	49"	20"	20½"
CSBF-48-S	48¾"	49"	24¾"	25"
Model	Width		Height	
Control Box	9½"		7¾"	



ONE YEAR, ON-SITE PARTS AND LABOR WARRANTY. AN ADDITIONAL FOUR YEAR EXTENDED PARTS ONLY WARRANTY ON THE COMPRESSOR AVAILABLE AT THE TIME OF UNIT PURCHASE.



Cold Shelves Undermount

Cold Shelves Undermount offer the same great performance as the Cold Built-In Flush Top Shelves, but are mounted directly against the underside of a granite, quartz, stainless steel or appropriate simulated stone counter top (no cut out required). Cooling transfers through the countertop to the top surface, without puncturing, for a true, seamless look.

- Mounts under appropriate countertop material (e.g. mount under a granite counter top 1 3/8" thick or less.)
- Aluminum surface
- Long, flexible refrigerant line offers the ability to pullout condensing unit for service
- Easy serviceability with a sight glass, service valves, dryer/filter and a receiver
- Control box can be mounted on the front of the cabinet, 4' from center of shelf
- Condensing unit may be mounted up to 4' away from the center of shelf
- Shelf construction utilizes R-404A refrigerant keeping food product cold



CSU-48-S



COLD SHELVES UNDERMOUNT (Aluminum)

Model	Dimensions W x D	Voltage Single Phase	Watts	Approx. Ship Weight
CSU-24-F	24" x 15 1/2"	120	804	108 lbs.
CSU-24-I	24" x 19 1/2"	120	804	115 lbs.
CSU-24-S	24" x 24"	120	804	122 lbs.
CSU-36-F	36" x 15 1/2"	120	804	130 lbs.
CSU-36-I	36" x 19 1/2"	120	1044	140 lbs.
CSU-36-S	36" x 24"	120	1044	147 lbs.
CSU-48-F	48" x 15 1/2"	120	1044	154 lbs.
CSU-48-I	48" x 19 1/2"	120	1044	161 lbs.
CSU-48-S	48" x 24"	120	1380	176 lbs.


All Cold Shelf Undermount Models Feature:

Electronic Temperature Control and condensing unit.

*Make structural modifications or add bracing underneath the countertop to ensure countertop will support the weight of the unit and its contents.

OPTIONS (available at time of purchase only)

EWC Additional four year extended parts only warranty on the Compressor available at the time of unit purchase



ONE YEAR, ON-SITE PARTS AND LABOR WARRANTY. AN ADDITIONAL FOUR YEAR EXTENDED PARTS ONLY WARRANTY ON THE COMPRESSOR AVAILABLE AT THE TIME OF UNIT PURCHASE.

Glo-Ray® Built-In Rectangular Heated Simulated Stone Shelves

Match the heat zone to your countertops with Hatco's Glo-Ray® Heated Simulated Stone Shelves. The built-in foodsafe shelves are ideal for buffet lines or as hors d'oeuvre displays. These unique warmers will safely hold food hot while blending in with your décor.

- Shelves are made of approved foodsafe materials
- Shelves come in 3 Simulated Stone colors: Gray Granite, Bermuda Sand and Night Sky (standard) – non-standard colors are non-returnable
- Models with Simulated Stone are Swanstone®
- Features a lighted rocker switch and thermostatically-controlled heated base
- Includes control box with 3' conduit and 6' cord and plug



GRSSB-3618 Built-In Heated Simulated Stone Shelf built into a Bermuda Sand Simulated Stone countertop



Standard control box

NOTE: For any size GRSSB, the next larger size GRA or GR2A Strip Heater will fit over the top. For example, a GRSSB-3018 will require a GRA-36 or GR2A-36. The GRA will have a tight fit to the frame of the base. The GR2A will have approx. a 4" space.

BUILT-IN RECTANGULAR HEATED SIMULATED STONE SHELVES

Model^	Dimensions W x D x H	Voltage Single Phase	Watts	Plug	Ship Weight
GRSSB-2418	25 $\frac{1}{2}$ " x 19 $\frac{1}{2}$ " x 2 $\frac{1}{4}$ "	120	635	NEMA 5-15P	30 lbs.
GRSSB-3018	31 $\frac{1}{2}$ " x 19 $\frac{1}{2}$ " x 2 $\frac{1}{4}$ "	120	780	NEMA 5-15P	35 lbs.
GRSSB-3618	37 $\frac{1}{2}$ " x 19 $\frac{1}{2}$ " x 2 $\frac{1}{4}$ "	120	930	NEMA 5-15P	40 lbs.
GRSSB-4818	49 $\frac{1}{2}$ " x 19 $\frac{1}{2}$ " x 2 $\frac{1}{4}$ "	120	1270	NEMA 5-15P	51 lbs.
GRSSB-6018	61 $\frac{1}{2}$ " x 19 $\frac{1}{2}$ " x 2 $\frac{1}{4}$ "	120	1560	NEMA 5-20P	56 lbs.
GRSSB-7218	73 $\frac{1}{2}$ " x 19 $\frac{1}{2}$ " x 2 $\frac{1}{4}$ "	120	1860	NEMA 5-20P	70 lbs.

^Recommended for use in a metallic countertop. For other surfaces, verify that the material is suitable for temperatures up to 200°F.

All Built-In Rectangular Heated Simulated Stone Shelf Models Feature:

Cord Location: End of remote enclosure.

OPTIONS (available at time of purchase only)

Designer Colors (Flush Mount Control Box Bezel) – Non-standard colors are non-returnable –

RED	Warm Red
BLACK	Black
GRAY	Gray Granite
WHITE	White Granite
NAVY	Navy Blue
GREEN	Hunter Green
COPPER	Antique Copper

Simulated Stone Colors – Non-standard colors are non-returnable – Night Sky Standard –

SS-GGRAN	Gray Granite
SS-BSAND	Bermuda Sand
SS-NSKY	Night Sky
GRSSB-FLUSH-ITC	Flush Mount Electronic Control Box with Lighted Power Switch
GRSSB-FLUSH-TSTAT	Flush Mount Thermostatic Control Box with Lighted Power Switch
COND-6	6' Conduit in lieu of standard 3' (used with Flush Mount ITC Control Box)
COND-10	10' Conduit in lieu of standard 3' (used with Flush Mount ITC Control Box)
GRSSB-REC	Built-In Heated Simulated Stone Shelf with Recessed Top

Optional **GRSSB-FLUSH-ITC** flush mount recessed *electronic* control box with lighted On/Off rocker switch and angled recessed controls



Optional **GRSSB-FLUSH-TSTAT** flush mount recessed *thermostatic* control box with lighted On/Off rocker switch and angled recessed controls



COLORS AND FINISHES – PAGE 11

BUILT-IN RECTANGULAR HEATED SIMULATED STONE COUNTERTOP CUTOUT DIMENSIONS

Model	Minimum Width	Maximum Width	Minimum Depth	Maximum Depth
GRSSB-2418	24 $\frac{1}{2}$ "	24 $\frac{7}{8}$ "	18 $\frac{5}{8}$ "	18 $\frac{7}{8}$ "
GRSSB-3018	30 $\frac{1}{2}$ "	30 $\frac{7}{8}$ "	18 $\frac{5}{8}$ "	18 $\frac{7}{8}$ "
GRSSB-3618	36 $\frac{1}{2}$ "	36 $\frac{7}{8}$ "	18 $\frac{5}{8}$ "	18 $\frac{7}{8}$ "
GRSSB-4818	48 $\frac{1}{2}$ "	48 $\frac{7}{8}$ "	18 $\frac{5}{8}$ "	18 $\frac{7}{8}$ "
GRSSB-6018	60 $\frac{1}{2}$ "	60 $\frac{7}{8}$ "	18 $\frac{5}{8}$ "	18 $\frac{7}{8}$ "
GRSSB-7218	72 $\frac{1}{2}$ "	72 $\frac{7}{8}$ "	18 $\frac{5}{8}$ "	18 $\frac{7}{8}$ "

OPTIONAL CONTROL BOX CUTOUT DIMENSIONS

Model	Width	Height	Depth
GRSSB-FLUSH-ITC	5 $\frac{7}{8}$ "	6 $\frac{3}{8}$ "	4 $\frac{3}{4}$ "
GRSSB-FLUSH-TSTAT	5 $\frac{7}{8}$ "	6 $\frac{3}{8}$ "	4"

ALL GLO-RAY® BLANKET HEATING ELEMENTS
WARRANTED AGAINST BURNOUT FOR ONE YEAR.





Built-In Rectangular Heated Black Glass Shelves

Hatco Heated Black Glass Shelves have a heated ceramic glass top to create uniform heat across the entire surface and are made of approved foodsafe materials. Adjustable thermostatic controls allow surface temperature to be controlled easily.

- Shelves are made of approved foodsafe materials
- Equipped with an attached stainless steel (standard) trim mounting ring (*Designer Black available*)



Standard control box



HBGB-2418 with optional *Designer Black Trim Ring*

NOTE: For any size HBGB, the next larger size GRA or GR2A Strip Heater will fit over the top. For example, a HBGB-3018 will require a GRA-36 or GR2A-36. The GRA will have a tight fit to the frame of the base. The GR2A will have approximately a 4" space.

BUILT-IN RECTANGULAR HEATED BLACK GLASS SHELVES

Model [^]	Dimensions	Voltage	Watts	Plug	Ship Weight
	W x D x H	Single Phase			
HBGB-2418	25 ³ / ₄ " x 19 ³ / ₄ " x 2 ¹ / ₄ "	120	425	NEMA 5-15P	32 lbs.
HBGB-3018	31 ³ / ₄ " x 19 ³ / ₄ " x 2 ¹ / ₄ "	120	525	NEMA 5-15P	37 lbs.
HBGB-3618	37 ³ / ₄ " x 19 ³ / ₄ " x 2 ¹ / ₄ "	120	630	NEMA 5-15P	40 lbs.
HBGB-4818 ⁺	49 ³ / ₄ " x 19 ³ / ₄ " x 2 ¹ / ₄ "	120	850	NEMA 5-15P	50 lbs.
HBGB-6018 ⁺	61 ³ / ₄ " x 19 ³ / ₄ " x 2 ¹ / ₄ "	120	1050	NEMA 5-15P	63 lbs.
HBGB-7218 ⁺	73 ³ / ₄ " x 19 ³ / ₄ " x 2 ¹ / ₄ "	120	1260	NEMA 5-15P	74 lbs.

[^]Recommended for use in a metallic countertop. For other surfaces, verify that the material is suitable for temperatures up to 200°F.

⁺ Units 48" and larger are constructed of two equal sized pieces of glass which create a seam.

All Built-In Rectangular Heated Black Glass Shelf Models Feature:

Cord Location: End of remote enclosure.

OPTIONS (available at time of purchase only)

Designer Colors (Flush Mount Control Box Bezel) –

BLACK Black

HBGB-TRIM-BLK	Designer Black Powdercoated Trim Ring
HBGB-FLUSH-ITC	Flush Mount Electronic Control Box with Lighted Power Switch (120V only)
HBGB-FLUSH-TSTAT	Flush Mount Thermostatic Control Box with Lighted Power Switch
COND-6	6' Conduit in lieu of standard 3' (used with Flush Mount ITC Control Box)
COND-10	10' Conduit in lieu of standard 3' (used with Flush Mount ITC Control Box)
HBGB-REC	Built-In Heated Black Glass Shelf with Recessed Top

Optional **HBGB-FLUSH-ITC** flush mount recessed *electronic* control box with lighted On/Off rocker switch and angled recessed controls



Optional **HBGB-FLUSH-TSTAT** flush mount recessed *thermostatic* control box with lighted On/Off rocker switch and angled recessed controls




BUILT-IN HEATED BLACK GLASS COUNTERTOP CUTOUT DIMENSIONS

Model	Minimum Width	Maximum Width	Minimum Depth	Maximum Depth
HBGB-2418	24 ⁵ / ₈ "	24 ⁷ / ₈ "	18 ⁵ / ₈ "	18 ⁷ / ₈ "
HBGB-3018	30 ³ / ₈ "	30 ⁵ / ₈ "	18 ⁵ / ₈ "	18 ⁷ / ₈ "
HBGB-3618	36 ⁵ / ₈ "	36 ⁷ / ₈ "	18 ⁵ / ₈ "	18 ⁷ / ₈ "
HBGB-4818	48 ³ / ₈ "	48 ⁵ / ₈ "	18 ⁵ / ₈ "	18 ⁷ / ₈ "
HBGB-6018	60 ⁵ / ₈ "	60 ⁷ / ₈ "	18 ⁵ / ₈ "	18 ⁷ / ₈ "
HBGB-7218	72 ⁵ / ₈ "	72 ⁷ / ₈ "	18 ⁵ / ₈ "	18 ⁷ / ₈ "

OPTIONAL CONTROL BOX CUTOUT DIMENSIONS

Model	Width	Height	Depth
HBGB-FLUSH-ITC	5 ⁵ / ₈ "	6 ³ / ₈ "	4 ⁵ / ₈ "
HBGB-FLUSH-TSTAT	5 ⁵ / ₈ "	6 ³ / ₈ "	4"



ALL GLO-RAY® BLANKET HEATING ELEMENTS WARRANTED AGAINST BURNOUT FOR ONE YEAR.

Glo-Ray® Built-In Rectangular Heated Shelves with Recessed Top

Let Hatco add heat to your serving surface with the Glo-Ray® Rectangular Built-In Heated Shelf. This 1/2" recessed top foodwarmer has a hardcoated aluminum surface and blanket-type element for uniform heat to extend your food holding time.

- Uniform heat distribution with hardcoated aluminum surface and blanket-type element
- 3' flexible conduit channels power lines from the shelf to a control box

- Enclosure includes control thermostat, an illuminated power switch and mounting brackets
- Thermostatically-controlled heated base



Standard control box



GRSB-24-I

NOTE: For any size GRSB, the next larger size GRA or GR2A Strip Heater will fit over the top. For example, a GRSB-30 will require a GRA-36 or GR2A-36. The GRA will have a tight fit to the frame of the base. The GR2A will have approximately a 4" space.

BUILT-IN RECTANGULAR HEATED SHELVES WITH RECESSED TOP

Model [^]	Dimensions W x D x H	Cut-Out Dimensions		Voltage Single Phase	Watts	Ship Weight
		Min.-Max. Width	Min.-Max. Depth			
GRSB-24-F	25 1/2" x 17" x 2 7/8"	24 1/2" - 24 3/4"	16" - 16 1/4"	120	420	20 lbs.
GRSB-24-I	25 1/2" x 21" x 2 7/8"	24 1/2" - 24 3/4"	20" - 20 1/4"	120	550	22 lbs.
GRSB-24-O	25 1/2" x 31 1/2" x 2 7/8"	24 1/2" - 24 3/4"	30 1/2" - 30 3/4"	120	790	26 lbs.
GRSB-30-F	31 1/2" x 17" x 2 7/8"	30 1/2" - 30 3/4"	16" - 16 1/4"	120	505	23 lbs.
GRSB-30-I	31 1/2" x 21" x 2 7/8"	30 1/2" - 30 3/4"	20" - 20 1/4"	120	665	25 lbs.
GRSB-30-O	31 1/2" x 31 1/2" x 2 7/8"	30 1/2" - 30 3/4"	30 1/2" - 30 3/4"	120	950	28 lbs.
GRSB-36-F	37 1/2" x 17" x 2 7/8"	36 1/2" - 36 3/4"	16" - 16 1/4"	120	590	26 lbs.
GRSB-36-I	37 1/2" x 21" x 2 7/8"	36 1/2" - 36 3/4"	20" - 20 1/4"	120	780	29 lbs.
GRSB-36-O	37 1/2" x 31 1/2" x 2 7/8"	36 1/2" - 36 3/4"	30 1/2" - 30 3/4"	120	1110	32 lbs.
GRSB-42-F	43 1/2" x 17" x 2 7/8"	42 1/2" - 42 3/4"	16" - 16 1/4"	120	685	29 lbs.
GRSB-42-I	43 1/2" x 21" x 2 7/8"	42 1/2" - 42 3/4"	20" - 20 1/4"	120	885	32 lbs.
GRSB-42-O	43 1/2" x 31 1/2" x 2 7/8"	42 1/2" - 42 3/4"	30 1/2" - 30 3/4"	120	1270	35 lbs.
GRSB-48-F	49 1/2" x 17" x 2 7/8"	48 1/2" - 48 3/4"	16" - 16 1/4"	120	770	33 lbs.
GRSB-48-I	49 1/2" x 21" x 2 7/8"	48 1/2" - 48 3/4"	20" - 20 1/4"	120	1000	36 lbs.
GRSB-48-O	49 1/2" x 31 1/2" x 2 7/8"	48 1/2" - 48 3/4"	30 1/2" - 30 3/4"	120	1430	39 lbs.
GRSB-54-I	55 1/2" x 21" x 2 7/8"	54 1/2" - 54 3/4"	20" - 20 1/4"	120	1110	43 lbs.
GRSB-60-F	61 1/2" x 17" x 2 7/8"	60 1/2" - 60 3/4"	16" - 16 1/4"	120	950	45 lbs.
GRSB-60-I	61 1/2" x 21" x 2 7/8"	60 1/2" - 60 3/4"	20" - 20 1/4"	120	1220	50 lbs.
GRSB-60-O	61 1/2" x 31 1/2" x 2 7/8"	60 1/2" - 60 3/4"	30 1/2" - 30 3/4"	120	1750	54 lbs.
GRSB-66-I	67 1/2" x 21" x 2 7/8"	66 1/2" - 66 3/4"	20" - 20 1/4"	120	1330	54 lbs.
GRSB-72-F	73 1/2" x 17" x 2 7/8"	72 1/2" - 72 3/4"	16" - 16 1/4"	120	1130	52 lbs.
GRSB-72-I	73 1/2" x 21" x 2 7/8"	72 1/2" - 72 3/4"	20" - 20 1/4"	120	1440	58 lbs.
GRSB-72-O	73 1/2" x 31 1/2" x 2 7/8"	72 1/2" - 72 3/4"	30 1/2" - 30 3/4"	208, 240	2070	64 lbs.

[^]Recommended for use in a metallic countertop. For other surfaces, verify that the material is suitable for temperatures up to 200°F.

All Built-In Rectangular Heated Shelf with Recessed Top Models Feature:

Plugs: All models ending in -F and -I and models 24" through 48" wide ending in -O: NEMA 5-15P.


GRSB-60-O: NEMA 5-20P.

GRSB-72-O: NEMA 6-15P.

Usable Heated Shelf Space: Width of unit minus 1 1/2" x depth of unit minus 1 1/2".

Cord Location: End of remote enclosure.

ALL GLO-RAY® BLANKET HEATING ELEMENTS WARRANTED
AGAINST BURNOUT FOR ONE YEAR.



OPTIONS (available at time of purchase only)

Designer Colors (Flush Mount Control Box Bezel only) – Non-standard colors are non-returnable –

RED	Warm Red	WHITE	White Granite	COPPER	Antique Copper
BLACK	Black	NAVY	Navy Blue		
GRAY	Gray Granite	GREEN	Hunter Green		

GRSB-FLUSH-ITC Flush Mount Electronic Control Box with Lighted Power Switch*

GRSB-FLUSH-TSTAT Flush Mount Thermostatic Control Box with Lighted Power Switch*

COND-6 6' Conduit in lieu of standard 3' (used with Flush Mount ITC Control Box)

COND-10 10' conduit in lieu of standard 3' (used with Flush Mount ITC Control Box)

* See page 7 for Control Box cutout dimensions.

FOOD PANS AND TRIVETS – PAGE 11
COLORS AND FINISHES – PAGE 11

Optional **GRSB-FLUSH-ITC** flush mount recessed *electronic* control box with lighted On/Off rocker switch and angled recessed controls



Optional **GRSB-FLUSH-TSTAT** flush mount recessed *thermostatic* control box with lighted On/Off rocker switch and angled recessed controls





Built-In Solutions

Glo-Ray® Built-In Rectangular Heated Shelves with Flush Top

Let Hatco add heat to your serving surface with the Glo-Ray® Built-In Rectangular Heated Shelf. This flush top foodwarmer has a hardcoated aluminum surface and blanket-type element for uniform heat to extend your food holding time.

NOTE: For any size GRSBF, the next larger size GRA or GR2A Strip Heater will fit over the top. For example, a GRSBF-30 will require a GRA-36 or GR2A-36. The GRA will have a tight fit to the frame of the base. The GR2A will have approx. a 4" space.

- Uniform heat distribution with hardcoated aluminum surface and blanket-type element
- 3' flexible conduit channels power lines from the shelf to a control box
- Thermostatically-controlled heated base
- Enclosure includes control thermostat, an illuminated power switch and mounting brackets
- Model widths from 25½" to 73½"
- Optional stainless steel surface



GRSBF-60-0 Glo-Ray® Built In Heated Shelf with Flush Top, built into a Bermuda Sand Simulated Stone countertop with accessory pans shown below a **GR2AL-96D** in *Designer Black* with optional sneeze guards



Standard control box

BUILT-IN RECTANGULAR HEATED SHELVES WITH FLUSH TOP

Model^	Dimensions W x D x H	Cut-Out Dimensions		Voltage Single Phase	Watts	Ship Weight
		Min.-Max. Width	Min.-Max. Depth			
GRSBF-24-F	25½" x 17" x 2¼"	24½"-24¾"	16"-16¼"	120	420	20 lbs.
GRSBF-24-I	25½" x 21" x 2¼"	24½"-24¾"	20"-20¼"	120	550	22 lbs.
GRSBF-24-S	25½" x 25½" x 2¼"	24½"-24¾"	24½"-24¾"	120	700	24 lbs.
GRSBF-24-0	25½" x 31½" x 2¼"	24½"-24¾"	30½"-30¾"	120	790	26 lbs.
GRSBF-30-F	31½" x 17" x 2¼"	30½"-30¾"	16"-16¼"	120	505	23 lbs.
GRSBF-30-I	31½" x 21" x 2¼"	30½"-30¾"	20"-20¼"	120	665	25 lbs.
GRSBF-30-S	31½" x 25½" x 2¼"	30½"-30¾"	24½"-24¾"	120	825	26 lbs.
GRSBF-30-0	31½" x 31½" x 2¼"	30½"-30¾"	30½"-30¾"	120	950	28 lbs.
GRSBF-36-F	37½" x 17" x 2¼"	36½"-36¾"	16"-16¼"	120	590	26 lbs.
GRSBF-36-I	37½" x 21" x 2¼"	36½"-36¾"	20"-20¼"	120	780	28 lbs.
GRSBF-36-S	37½" x 25½" x 2¼"	36½"-36¾"	24½"-24¾"	120	950	31 lbs.
GRSBF-36-0	37½" x 31½" x 2¼"	36½"-36¾"	30½"-30¾"	120	1110	32 lbs.
GRSBF-42-F	43½" x 17" x 2¼"	42½"-42¾"	16"-16¼"	120	685	29 lbs.
GRSBF-42-I	43½" x 21" x 2¼"	42½"-42¾"	20"-20¼"	120	885	32 lbs.
GRSBF-42-S	43½" x 25½" x 2¼"	42½"-42¾"	24½"-24¾"	120	1100	34 lbs.
GRSBF-42-0	43½" x 31½" x 2¼"	42½"-42¾"	30½"-30¾"	120	1270	35 lbs.
GRSBF-48-F	49½" x 17" x 2¼"	48½"-48¾"	16"-16¼"	120	770	33 lbs.
GRSBF-48-I	49½" x 21" x 2¼"	48½"-48¾"	20"-20¼"	120	1000	36 lbs.
GRSBF-48-S	49½" x 25½" x 2¼"	48½"-48¾"	24½"-24¾"	120	1225	38 lbs.
GRSBF-48-0	49½" x 31½" x 2¼"	48½"-48¾"	30½"-30¾"	120	1430	39 lbs.
GRSBF-60-F	61½" x 17" x 2¼"	60½"-60¾"	16"-16¼"	120	950	45 lbs.
GRSBF-60-I	61½" x 21" x 2¼"	60½"-60¾"	20"-20¼"	120	1220	50 lbs.
GRSBF-60-S	61½" x 25½" x 2¼"	60½"-60¾"	24½"-24¾"	120	1500	53 lbs.
GRSBF-60-0	61½" x 31½" x 2¼"	60½"-60¾"	30½"-30¾"	120	1750	54 lbs.
GRSBF-72-F	73½" x 17" x 2¼"	72½"-72¾"	16"-16¼"	120	1130	52 lbs.
GRSBF-72-I	73½" x 21" x 2¼"	72½"-72¾"	20"-20¼"	120	1440	58 lbs.
GRSBF-72-S	73½" x 25½" x 2¼"	72½"-72¾"	24½"-24¾"	120	1750	62 lbs.
GRSBF-72-0	73½" x 31½" x 2¼"	72½"-72¾"	30½"-30¾"	208, 240	2070	64 lbs.

^Recommended for use in a metallic countertop. For other surfaces, verify that the material is suitable for temperatures up to 200°F.

All Built-In Rectangular Heated Shelves with Flush Top Models Feature:


Plugs: All models ending in -F and -I and models 24" through 48" wide ending in -S and -0: NEMA 5-15P.

GRSBF-60-S, GRSBF-60-0 and GRSBF-72-S: NEMA 5-20P. GRSBF-72-0: NEMA 6-15P.

Usable Heated Shelf Space: Entire surface.

Cord Location: End of remote enclosure.

ALL GLO-RAY® BLANKET HEATING ELEMENTS WARRANTED AGAINST BURNOUT FOR ONE YEAR.



OPTIONS (available at time of purchase only)

Designer Colors (Flush Mount Control Box Bezel only) – Non-standard colors are non-returnable –

RED Warm Red	WHITE White Granite	COPPER Antique Copper
BLACK Black	NAVY Navy Blue	
GRAY Gray Granite	GREEN Hunter Green	

GRSBF-SS Stainless Steel Surface in lieu of Hardcoat (GRSBF Models only)

GRSB-FLUSH-ITC Flush Mount Electronic Control Box with Lighted Power Switch*

GRSB-FLUSH-TSTAT Flush Mount Thermostatic Control Box with Lighted Power Switch*

COND-6 6' Conduit in lieu of standard 3' (used with Flush Mount ITC Control Box)

COND-10 10' Conduit in lieu of standard 3' (used with Flush Mount ITC Control Box)

* See page 7 for Control Box cutout dimensions.

FOOD PANS AND TRIVETS – PAGE 11

COLORS AND FINISHES – PAGE 11

Optional **GRSB-FLUSH-ITC** flush mount recessed electronic control box with lighted On/Off rocker switch and angled recessed controls



Optional **GRSB-FLUSH-TSTAT** flush mount recessed thermostatic control box with lighted On/Off rocker switch and angled recessed controls



Food Pans And Trivets



ALUM PAN

18" SHEET PAN



PIZZA PANS
14" PIZZA PAN
16" PIZZA PAN
18" PIZZA PAN




ST PANS
ST PAN 1/3
ST PAN 1/2
ST PAN 2
ST PAN 4

FOOD PANS

Model	Description
ALUM PAN	Half-Size Sheet Pan – 18"W x 13"D
18" SHEET PAN	Full-Size Sheet Pan – 18"W x 26"D
14" PIZZA PAN	Perforated Pizza Pan – 14" Diameter
16" PIZZA PAN	Perforated Pizza Pan – 16" Diameter
18" PIZZA PAN	Perforated Pizza Pan – 18" Diameter
ST PAN 1/3	Third-Size Stainless Steel Pan – 12¾"W x 6⅞"D x 2½"H
ST PAN 1/2	Half-Size Stainless Steel Pan – 12¾"W x 10⅞"D x 2½"H
ST PAN 2	Full-Size Stainless Steel Pan – 12¾"W x 20¾"D x 2½"H
ST PAN 4	Full-Size Stainless Steel Pan – 12¾"W x 20¾"D x 4"H

TRIVETS


Model	Description
Wire Trivets Stainless –	
TRIVET (1/2)SS	Half-Size – 10⅜"W x 7⅞"D
TRIVET SS	Full Size – 10⅞"W x 18"D



TRIVETS
TRIVET (1/2)SS
TRIVET SS

Paint Chip and Stone Sample Colors

DESIGNER COLORS



Warm Red

Black

Gray
Granite

White
Granite

Navy
Blue

Hunter
Green

Antique
Copper

HEATED STONE COLORS*



Gray
Granite

Bermuda
Sand

Night Sky

*Colors are a representation and may not exactly match our colors.
Consult factory for possible color matching options on these colors.
Non-standard colors are non-returnable.*

To order a Hatco Paint Chip & Stone Sample Colors Sheet, visit www.hatcocorp.com / Order Literature / Sales Literature / Sell Sheets.

* Simulated Stone

Sturgeon Bay, WI 54235 U.S.A. Telephone: (800) 558-0607 or (414) 671-6350 www.hatcocorp.com



Scan with web-enabled
mobile device to visit
www.hatcocorp.com



Hatco Corporation

P.O. Box 340500 | Milwaukee WI 53234-0500 USA
800-558-0607 | 414-671-6350 | Fax: 800-543-7521
www.hatcocorp.com | equipsales@hatcocorp.com