




Designer line

Reach-Ins & Pass-Thrus

REFRIGERATORS, FREEZERS & WARMERS



Continental[®]
Refrigerator

INNOVATIVE DESIGNS FOR YOUR FOODSERVICE NEEDS

Reach-Ins & Pass-Thrus

Refrigerators, Freezers & Warmers

Continental Refrigerator has one of the most diversified commercial Reach-In product lines in the industry with standard features not found on other units. Our Designer Line models are equipped with both top and side air distribution ducts which allow for constant, uniform temperature throughout the cabinet.

Functionality

The refrigeration/heating systems on our Designer Line Reach-Ins & Pass-Thrus are accessible on top of the cabinet and separate from the food zone, increasing food storage capacity.

Performance & Reliability

Performance-run tested for a minimum of 12 hours providing a highly sophisticated temperature analysis recording, exclusive to each cabinet.





Modifications Made Easy.

At Continental Refrigerator, we know the foodservice industry is an ever-changing environment. We are reminded of this every day through feedback from our customers, both directly and through our network of representatives. In fact, customer feedback has often lead to our custom engineering modifications becoming standard product features.

For this reason, we pride ourselves in delivering feature-rich refrigeration equipment solutions designed specifically for the commercial foodservice market. Whether it's kitchen ambient, food safety, limited space or storage challenges, our products are packed with flexible options that provide **real** operator benefits out of the box. This flexibility, a key differentiator of our products, enables our customers to modify base product features strategic to the way they operate their kitchen or bar environment.

Shown: DL2R-PT

Standard Model



Half Doors



Laminated Doors



Glass Doors



Pan Slide Assemblies (On Right)



5" Casters

...

...

...

...

Consult factory for other modifications

www.continentalrefrigerator.com

Overview of Models & Refrigerator/Freezer Standard Features

Standard Features

Stainless steel front, aluminum end panels & interior

Environmentally-safe R-290 refrigerant
(except 3-section Freezer models)

Environmentally-safe R404A refrigerant
(3-section Freezer models only)

Self-contained, performance-rated "Plug" refrigeration system

Environmentally-safe R-134a refrigerant (some refrigerators); R404A refrigerant (freezers)

3" Non-CFC polyurethane foam insulation

Smooth, polished chrome door handles (solid doors)

Cam-action, lift-off hinges

Heavy-duty, epoxy-coated steel shelves

Automatic, hot gas condensate evaporator (Standard models)

Automatic, electric condensate evaporator (Shallow Depth models)

Magnetic snap-in door gaskets

Cylinder lock in each door (hinged doors)

Adjustable 6" stainless steel legs

Self-closing doors

LED interior lighting

Electronic controller w/ digital display & hi-low alarm

Expansion valve system
(some refrigerator models)


Automatic electric defrost (freezers/dual temperature freezer section)

Triple-pane, tempered glass doors (hinged glass refrigerators)


Double-pane, low-e, tempered glass doors (sliding glass doors)

High efficiency PVC frame (sliding glass doors)


Widths




Depths



Door Styles



Optional Pan Slide Assemblies (not available for Shallow Depth models)



Optional Models:

-SA: Stainless steel exterior, aluminum interior
-SS: Stainless steel exterior & interior

Call us toll free at (800) 523-7138

Specifications - Standard & Slim Line Refrigerators

Reach-In Models

MODEL TYPE	STANDARD	SUFFIX "SA"	SUFFIX "SS"	EXTERIOR DIMENSIONS INCHES W x D x H	CAPACITY BTU/HR*	H.P.	SHIP WEIGHT**
FULL DOORS	D1RN	D1RNSA	D1RNSS	26 x 35 3/8 x 83 1/4	1940	1/4+	320
	D2RN	D2RNSA	D2RNSS	52 x 35 3/8 x 83 1/4	2560	1/3+	535
	D3RN	D3RNSA	D3RNSS	78 x 35 3/8 x 83 1/4	4010	1/2	740
HALF DOORS	D1RNHD	D1RNSAHD	D1RNSSHD	26 x 35 3/8 x 83 1/4	1940	1/4+	320
	D2RNHD	D2RNSAHD	D2RNSSHD	52 x 35 3/8 x 83 1/4	2560	1/3+	535
	D3RNHD	D3RNSAHD	D3RNSSHD	78 x 35 3/8 x 83 1/4	4010	1/2	740
FULL DOORS SHALLOW DEPTH	D1RSN ¹	D1RSNSA ¹	D1RSNSS ¹	26 x 29 1/4 x 83 1/4	1940	1/4	300
	D2RSN ¹	D2RSNSA ¹	D2RSNSS ¹	52 x 29 1/4 x 83 1/4	2560	1/3	495
HALF DOORS SHALLOW DEPTH	D1RSNHD ¹	D1RSNSAHD ¹	D1RSNSSHD ¹	26 x 29 1/4 x 83 1/4	1940	1/4	300
	D2RSNHD ¹	D2RSNSAHD ¹	D2RSNSSHD ¹	52 x 29 1/4 x 83 1/4	2560	1/3	495

Pass-Thru Models

FULL DOORS	D1RNPT	D1RNSAPT	D1RNSSPT	26 x 38 3/4 x 83 1/4	1940	1/4+	350
	D2RNPT	D2RNSAPT	D2RNSSPT	52 x 38 3/4 x 83 1/4	2560	1/3+	595
	D3RNPT	D3RNSAPT	D3RNSSPT	78 x 38 3/4 x 83 1/4	4010	1/2	825
HALF DOORS	D1RNPTHD	D1RNSAPTHD	D1RNSSPTHD	26 x 38 3/4 x 83 1/4	1940	1/4+	350
	D2RNPTHD	D2RNSAPTHD	D2RNSSPTHD	52 x 38 3/4 x 83 1/4	2560	1/3+	595
	D3RNPTHD	D3RNSAPTHD	D3RNSSPTHD	78 x 38 3/4 x 83 1/4	4010	1/2	825

Slim Line Reach-In Models

FULL DOORS	D1RSEN ¹	D1RSENSA ¹	D1RSENSS ¹	17 3/4 x 35 3/8 x 83 1/4	1940	1/4+	290
	D2RSEN	D2RSENSA	D2RSENSS	36 1/4 x 35 3/8 x 83 1/4	2560	1/3+	450
HALF DOORS	D1RSENHD ¹	D1RSENSAHD ¹	D1RSENSSHD ¹	17 3/4 x 35 3/8 x 83 1/4	1940	1/4+	290
	D2RSENHD	D2RSENSAHD	D2RSENSSHD	36 1/4 x 35 3/8 x 83 1/4	2560	1/3+	450
FULL DOORS SHALLOW DEPTH	D1RSES ¹	D1RSES-SA ¹	D1RSES-SS ¹	17 3/4 x 29 1/4 x 83 1/4	1940	1/4+	270
	D2RSES	D2RSES-SA	D2RSES-SS	36 1/4 x 29 1/4 x 83 1/4	2560	1/3+	410
HALF DOORS SHALLOW DEPTH	D1RSESNHD ¹	D1RSESNSAHD ¹	D1RSESNSSHD ¹	17 3/4 x 29 1/4 x 83 1/4	1940	1/4+	270
	D2RSESNHD	D2RSESNSAHD	D2RSESNSSHD	36 1/4 x 29 1/4 x 83 1/4	2560	1/3+	410

Specifications - Extra Wide Refrigerators & Standard Freezers (0°F)

Extra-Wide Reach-In Models

MODEL TYPE	STANDARD	SUFFIX "SA"	SUFFIX "SS"	EXTERIOR DIMENSIONS INCHES W x D x H	CAPACITY BTU/HR*	H.P.	SHIP WEIGHT**
FULL DOORS	D1REN	D1RENSA	D1RENSS	28 1/2 x 35 3/8 x 83 1/4	1940	1/4+	340
	D1RXN	D1RXNSA	D1RXNSS	36 1/4 x 35 3/8 x 83 1/4	2560	1/3+	440
	D2REN	D2RENSA	D2RENSS	57 x 35 3/8 x 83 1/4	2560	1/3+	575
	D3REN	D3RENSA	D3RENSS	85 1/2 x 35 3/8 x 83 1/4	4010	1/2	795
HALF DOORS	D1RENHD	D1RENSAHD	D1RENSSHD	28 1/2 x 35 3/8 x 83 1/4	1940	1/4+	340
	D1RXNHD	D1RXNSAHD	D1RXNSSHD	36 1/4 x 35 3/8 x 83 1/4	2560	1/3+	440
	D2RENHD	D2RENSAHD	D2RENSSHD	57 x 35 3/8 x 83 1/4	2560	1/3+	575
	D3RENHD	D3RENSAHD	D3RENSSHD	85 1/2 x 35 3/8 x 83 1/4	4010	1/2	795
FULL DOORS SHALLOW DEPTH	D1RESN	D1RESNSA	D1RESNSS	28 1/2 x 29 1/4 x 83 1/4	1940	1/4	340
	D1RXSN	D1RXSNSA	D1RXSNSS	36 1/4 x 29 1/4 x 83 1/4	2190	1/4	440
	D2RESN	D2RESNSA	D2RESNSS	57 x 29 1/4 x 83 1/4	2560	1/3	575
HALF DOORS SHALLOW DEPTH	D1RESNHD	D1RESNSAHD	D1RESNSSHD	28 1/2 x 29 1/4 x 83 1/4	1940	1/4	340
	D1RXSNHD	D1RXSNSAHD	D1RXSNSSHD	36 1/4 x 29 1/4 x 83 1/4	2190	1/4	440
	D2RESNHD	D2RESNSAHD	D2RESNSSHD	57 x 29 1/4 x 83 1/4	2560	1/3	575

Extra-Wide Pass-Thru Models

FULL DOORS	D1RENPT	D1RENSAPT	D1RENS-PT	28 1/2 x 38 3/4 x 83 1/4	1940	1/4+	370
	D1RXNPT	D1RXNSAPT	D1RXNSSPT	36 1/4 x 38 3/4 x 83 1/4	2560	1/3+	445
	D2RENPT	D2RENSAPT	D2RENSSPT	57 x 38 3/4 x 83 1/4	2560	1/3+	645
	D3RENPT	D3RENSAPT	D3RENSSPT	85 1/2 x 38 3/4 x 83 1/4	4010	1/2	865
HALF DOORS	D1RENPTH	D1RENSAPTH	D1RENSSPTH	28 1/2 x 38 3/4 x 83 1/4	1940	1/4+	370
	D1RXNPTH	D1RXNSAPTH	D1RXNSSPTH	36 1/4 x 38 3/4 x 83 1/4	2560	1/3+	445
	D2RNPTH	D2RENSAPTH	D2RENSSPTH	57 x 38 3/4 x 83 1/4	2560	1/3+	645
	D3RENPTH	D3RENSAPTH	D3RENSSPTH	85 1/2 x 38 3/4 x 83 1/4	4010	1/2	865

Note: Consult factory for Shallow Depth models.

BTU/HR Rating @ +25°F, 90°F ambient
10 ft. cord and plug attached
115-60-1 volts

Reach-In Freezer (0°F) Models

MODEL TYPE	STANDARD	SUFFIX "SA"	SUFFIX "SS"	EX. DIMENSIONS INCHES W x D x H	CAPACITY BTU/HR*	H.P.	SHIP WEIGHT**
FULL DOORS	D1FN	D1FNSA	D1FNSS	26 x 35 3/8 x 83 1/4	1590	1/3	335
	D2FN	D2FNSA	D2FNSS	52 x 35 3/8 x 83 1/4	2470	1/2	570
	DL3F	DL3F-SA	DL3F-SS	78 x 35 3/8 x 83 1/4	3575	3/4 [§]	805
HALF DOORS	D1FNHD	D1FNSAHD	D1FNSSHD	26 x 35 3/8 x 83 1/4	1590	1/3	335
	D2FNHD	D2FNSAHD	D2FNSSHD	52 x 35 3/8 x 83 1/4	2470	1/2	570
	DL3F-HD	DL3F-SA-HD	DL3F-SS-HD	78 x 35 3/8 x 83 1/4	3575	3/4 [§]	805
FL DRS SHLW DPH	D1FSN ¹	D1FSNSA ¹	D1FSNSS ¹	26 x 29 1/4 x 83 1/4	1590	1/3	290
	D2FSN ¹	D2FSNSA ¹	D2FSNSS ¹	52 x 29 1/4 x 83 1/4	2470	1/2	480
HF DRS SHLW DTH	D1FSNHD ¹	D1FSNSAHD ¹	D1FSNSSHD ¹	26 x 29 1/4 x 83 1/4	1590	1/3	290
	D2FSNHD ¹	D2FSNSAHD ¹	D2FSNSSHD ¹	52 x 29 1/4 x 83 1/4	2470	1/2	480

BTU/HR Rating @ -15°F, 90°F ambient
10 ft. cord and plug attached (115-60-1 volts)
[§]No cord and plug attached (115/208-230-60-1 volts)

¹ Coil housing in cabinet zone and automatic, electric condensate in lieu of hot gas condensate.

** Ship Weight for Suffix "SA" and Suffix "SS" models is on average 5% higher than Standard models. Refer to Specification Sheet for Shipping Weight of these models.

Call us toll free at (800) 523-7138

Specifications - Standard (cont.), Slim Line & Extra Wide Freezers (0°F)

Pass-Thru Models

MODEL TYPE	STANDARD	SUFFIX "SA"	SUFFIX "SS"	EXT. DIMENSIONS INCHES W x D x H	CAPACITY BTU/HR*	H.P.	SHIP WEIGHT**
FULL DOORS	D1FNPT	D1FNSAPT	D1FNSSPT	26 x 38 3/4 x 83 1/4	1590	1/3	365
	D2FNPT	D2FNSAPT	D2FNSSPT	52 x 38 3/4 x 83 1/4	2470	3/4 [§]	680
	DL3F-PT	DL3F-SA-PT	DL3F-SS-PT	78 x 38 3/4 x 87 1/4	3575	1 [§]	900
HALF DOORS	D1FNPTH	D1FNSAPTH	D1FNSSPTH	26 x 38 3/4 x 83 1/4	1590	1/3	365
	D2FNPTH	D2FNSAPTH	D2FNSSPTH	52 x 38 3/4 x 83 1/4	2470	3/4 [§]	680
	DL3F-PT-HD	DL3F-SA-PT-HD	DL3F-SS-PT-HD	78 x 38 3/4 x 87 1/4	3575	1 [§]	900

Slim Line Reach-In Models

FULL DOORS	D1FSEN ¹	D1FSENSA ¹	D1FSENSS ¹	17 3/4 x 35 3/8 x 83 1/4	1590	1/3	305
	D2FSEN	D2FSENSA	D2FSENSS	36 1/4 x 35 3/8 x 83 1/4	1840	1/2	465
HALF DOORS	D1FSENHD ¹	D1FSENSAHD ¹	D1FSENSSHD ¹	17 3/4 x 35 3/8 x 83 1/4	1590	1/3	305
	D2FSENHD	D2FSENSAHD	D2FSENSSHD	36 1/4 x 35 3/8 x 83 1/4	1840	1/2	465

Extra-Wide Reach-In Models

MODEL TYPE	STANDARD	SUFFIX "SA"	SUFFIX "SS"	EXT. DIMENSIONS INCHES W x D x H	CAPACITY BTU/HR*	H.P.	SHIP WEIGHT**
FULL DOORS	D1FEN	D1FENSA	D1FENSS	28 1/2 x 35 3/8 x 83 1/4	1590	1/3	355
	D1FXN	D1FXNSA	D1FXNSS	36 1/4 x 35 3/8 x 83 1/4	1840	1/2	455
	D2FEN	D2FENSA	D2FENSS	57 x 35 3/8 x 83 1/4	2470	1/2	610
	DL3FE	DL3FE-SA	DL3FE-SS	85 1/2 x 35 3/8 x 83 1/4	3575	3/4 [§]	860
HALF DOORS	D1FENHD	D1FENSAHD	D1FENSSHD	28 1/2 x 35 3/8 x 83 1/4	1590	1/3	355
	D1FXNHD	D1FXNSAHD	D1FXNSSHD	36 1/4 x 35 3/8 x 83 1/4	1840	1/2	455
	D2FENHD	D2FENSAHD	D2FENSSHD	57 x 35 3/8 x 83 1/4	2470	1/2	610
	DL3FE-HD	DL3FE-SA-HD	DL3FE-SS-HD	85 1/2 x 35 3/8 x 83 1/4	3575	3/4 [§]	860
FULL DOORS SHALLOW DEPTH	D1FESN ¹	D1FESNSA ¹	D1FESNSS ¹	28 1/2 x 29 1/4 x 83 1/4	1590	1/3	330
	D1FXSN ¹	D1FXSNSA ¹	D1FXSNSS ¹	36 1/4 x 29 1/4 x 83 1/4	1840	1/2	415
	D2FESN	D2FESNSA	D2FESNSS	57 x 29 1/4 x 83 1/4	2470	1/2	570
HALF DOORS SHALLOW DEPTH	D1FESNHD ¹	D1FESNSAHD ¹	D1FESNSSHD ¹	28 1/2 x 29 1/4 x 83 1/4	1590	1/3	330
	D1FXSNHD ¹	D1FXSNSAHD ¹	D1FXSNSSHD ¹	36 1/4 x 29 1/4 x 83 1/4	1840	1/2	415
	D2FESNHD	D2FESNSAHD	D2FESNSSHD	57 x 29 1/4 x 83 1/4	2470	1/2	570

Extra-Wide Pass-Thru Models

FULL DOORS	D1FENPT	D1FENSAPT	D1FENSSPT	28 1/2 x 38 3/4 x 83 1/4	1590	1/3	385
	D1FXNPT	D1FXNSAPT	D1FXNSSPT	36 1/4 x 38 3/4 x 83 1/4	1840	1/2	460
	D2FENPT	D2FENSAPT	D2FENSSPT	57 x 38 3/4 x 83 1/4	2470	3/4 [§]	720
	DL3FE-PT	DL3FE-SA-PT	DL3FE-SS-PT	85 1/2 x 38 3/4 x 87 1/4	3575	1 [§]	960
HALF DOORS	D1FENPTH	D1FENSAPTH	D1FENSSPTH	28 1/2 x 38 3/4 x 83 1/4	1590	1/3	385
	D1FXNPTH	D1FXNSAPTH	D1FXNSSPTH	36 1/4 x 38 3/4 x 83 1/4	1840	1/2	460
	D2FENPTH	D2FENSAPTH	D2FENSSPTH	57 x 38 3/4 x 83 1/4	2470	3/4 [§]	720
	DL3FE-PT-HD	DL3FE-SA-PT-HD	DL3FE-SS-PT-HD	85 1/2 x 38 3/4 x 87 1/4	3575	1 [§]	960

Note: Consult factory for Shallow Depth models.

BTU/HR Rating @ -15°F, 90°F ambient

10 ft. cord and plug attached (115-60-1 volts)

[§]No cord and plug attached (115/208-230-60-1 volts)

¹ Coil housing in cabinet zone and automatic, electric condensate in lieu of hot gas condensate.

** Ship Weight for Suffix "SA" and Suffix "SS" models is on average 5% higher than Standard models. Refer to Specification Sheet for Shipping Weight of these models.

Standard Features & Specifications - Warmers

Standard Features

Stainless steel front, aluminum end panels & interior

Self-contained, performance-rated warming system

90°F to 180°F temperature range

Top mounted heating plenum "plug" w/ circulating fan

3" non-CFC polyurethane foam insulation

Smooth, polished chrome workflow door handles

Cam-action, lift-off hinges

Humidity relief vent

Electronic controller w/ digital display & hi-low alarm

Heavy duty, chrome-plated steel shelves

Stainless steel strip heaters (located at the base of the interior)

Magnetic snap-in door gaskets

Cylinder lock in each door

Adjustable 6" stainless steel legs

Self-closing doors

Automatic interior lighting

Rehinging of door in field (1-section, full door only) (not available on DL1RX model)

Reach-In Models

MODEL TYPE	STANDARD	SUFFIX "SA"	SUFFIX "SS"	EXTERIOR DIMENSIONS INCHES W x D x H	TOTAL WATT.	SHIP WEIGHT**
STANDARD DEPTH FULL DOORS	DL1W	DL1W-SA	DL1W-SS	26 x 35 3/8 x 83 1/4	1500 [§]	270
	DL2W	DL2W-SA	DL2W-SS	52 x 35 3/8 x 83 1/4	2250 [§]	470
	DL3W	DL3W-SA	DL3W-SS	78 x 35 3/8 x 83 1/4	3000 [§]	650
STANDARD DEPTH HALF DOORS	DL1W-HD	DL1W-SA-HD	DL1W-SS-HD	26 x 35 3/8 x 83 1/4	1500 [§]	270
	DL2W-HD	DL2W-SA-HD	DL2W-SS-HD	52 x 35 3/8 x 83 1/4	2250 [§]	470
	DL3W-HD	DL3W-SA-HD	DL3W-SS-HD	78 x 35 3/8 x 83 1/4	3000 [§]	650
EXTRA WIDE FULL DOORS	DL1WE	DL1WE-SA	DL1WE-SS	28 1/2 x 35 3/8 x 83 1/4	1500 [§]	290
	DL2WE	DL2WE-SA	DL2WE-SS	57 x 35 3/8 x 83 1/4	2250 [§]	510
	DL3WE	DL3WE-SA	DL3WE-SS	85 1/2 x 35 3/8 x 83 1/4	3000 [§]	710
EXTRA WIDE HALF DOORS	DL1WE-HD	DL1WE-SA-HD	DL1WE-SS-HD	28 1/2 x 35 3/8 x 83 1/4	1500 [§]	290
	DL2WE-HD	DL2WE-SA-HD	DL2WE-SS-HD	57 x 35 3/8 x 83 1/4	2250 [§]	510
	DL3WE-HD	DL3WE-SA-HD	DL3WE-SS-HD	85 1/2 x 35 3/8 x 83 1/4	3000 [§]	710

Pass-Thru Models

STANDARD DEPTH FULL DOORS	DL1W-PT	DL1W-SA-PT	DL1W-SS-PT	26 x 38 3/4 x 83 1/4	1500 [§]	300
	DL2W-PT	DL2W-SA-PT	DL2W-SS-PT	52 x 38 3/4 x 83 1/4	2250 [§]	570
	DL3W-PT	DL3W-SA-PT	DL3W-SS-PT	78 x 38 3/4 x 83 1/4	3000 [§]	780
STANDARD DEPTH HALF DOORS	DL1W-PT-HD	DL1W-SA-PT-HD	DL1W-SS-PT-HD	26 x 38 3/4 x 83 1/4	1500 [§]	300
	DL2W-PT-HD	DL2W-SA-PT-HD	DL2W-SS-PT-HD	52 x 38 3/4 x 83 1/4	2250 [§]	570
	DL3W-PT-HD	DL3W-SA-PT-HD	DL3W-SS-PT-HD	78 x 38 3/4 x 83 1/4	3000 [§]	780
EXTRA WIDE FULL DOORS	DL1WE-PT	DL1WE-SA-PT	DL1WE-SS-PT	28 1/2 x 38 3/4 x 83 1/4	1500 [§]	320
	DL2WE-PT	DL2WE-SA-PT	DL2WE-SS-PT	57 x 38 3/4 x 83 1/4	2250 [§]	570
	DL3WE-PT	DL3WE-SA-PT	DL3WE-SS-PT	85 1/2 x 38 3/4 x 83 1/4	3000 [§]	800
EXTRA WIDE HALF DOORS	DL1WE-PT-HD	DL1WE-SA-PT-HD	DL1WE-SS-PT-HD	28 1/2 x 38 3/4 x 83 1/4	1500 [§]	320
	DL2WE-PT-HD	DL2WE-SA-PT-HD	DL2WE-SS-PT-HD	57 x 38 3/4 x 83 1/4	2250 [§]	570
	DL3WE-PT-HD	DL3WE-SA-PT-HD	DL3WE-SS-PT-HD	85 1/2 x 38 3/4 x 83 1/4	3000 [§]	800

[§]No cord and plug attached (115/208-230-60-1 volts)

^{**} Ship Weight for Suffix "SA" and Suffix "SS" models is on average 5% higher than Standard models. Refer to Specification Sheet for Shipping Weight of these models.

Specifications - Standard Dual Temperature

Refrigerator/Freezer (0°F) Reach-In Models

MODEL TYPE	STANDARD	SUFFIX "SA"	SUFFIX "SS"	EXTERIOR DIMENSIONS INCHES W x D x H	CAPACITY BTU/HR*	H.P.	SHIP WEIGHT**
FULL DOORS	D2RFN	D2RFNSA	D2RFNSS	52 x 35 3/8 x 83 1/4	1940, 1590	1/4, 1/3	580
	D3RRFN	D3RRFNSA	D3RRFNSS	78 x 35 3/8 x 83 1/4	2560, 1590	1/3, 1/3	825
	D3RFFN	D3RFFNSA	D3RFFNSS	78 x 35 3/8 x 83 1/4	1940, 2470	1/4, 1/2	825
HALF DOORS	D1RFNHD ¹	D1RFNSAHD ¹	D1RFNSSHD ¹	26 x 35 3/8 x 83 1/4	1625, 1800	1/5, 1/3	420
	D2RFNHD	D2RFNSAHD	D2RFNSSHD	52 x 35 3/8 x 83 1/4	1940, 1590	1/4, 1/3	580
	D3RRFNHD	D3RRFNSAHD	D3RRFNSSHD	78 x 35 3/8 x 83 1/4	2560, 1590	1/3, 1/3	825
	D3RFFNHD	D3RFFNSAHD	D3RFFNSSHD	78 x 35 3/8 x 83 1/4	1940, 2470	1/4, 1/2	825
FULL DOORS SHALLOW DEPTH	D2RFSN ¹	D2RFSNSA ¹	D2RFSNSS ¹	52 x 29 1/4 x 83 1/4	1940, 1590	1/4, 1/3	540
HALF DOORS SHALLOW DEPTH	D1RFSNHD ¹	D1RFSNSAHD ¹	D1RFSNSSHD ¹	26 x 29 1/4 x 83 1/4	1725, 1250	1/5, 1/4	400
	D2RFSNHD ¹	D2RFSNSAHD ¹	D2RFSNSSHD ¹	52 x 29 1/4 x 83 1/4	1940, 1590	1/4, 1/3	540

Refrigerator/Freezer (0°F) Pass-Thru Models

FULL DOORS	D2RFNPT	D2RFNSAPT	D2RFNSSPT	52 x 38 3/4 x 83 1/4	1940, 1590	1/4, 1/3	640
	D3RRFNP	D3RRFNSAPT	D3RRFNSSPT	78 x 38 3/4 x 83 1/4	2560, 1590	1/3, 1/3	910
	D3RFFNP	D3RFFNSAPT	D3RFFNSSPT	78 x 38 3/4 x 83 1/4	1940, 2470	1/4, 1/2	910
HALF DOORS	D2RFNPETHD	D2RFNSAPETHD	D2RFNSSPETHD	52 x 38 3/4 x 83 1/4	1940, 1590	1/4, 1/3	640
	D3RRFNPETHD	D3RRFNSAPETHD	D3RRFNSSPETHD	78 x 38 3/4 x 83 1/4	2560, 1590	1/3, 1/3	910
	D3RFFNPETHD	D3RFFNSAPETHD	D3RFFNSSPETHD	78 x 38 3/4 x 83 1/4	1940, 2470	1/4, 1/2	910

Note: Consult factory for Glass Door models.

Refrigerator/Warmer Reach-In Models

MODEL TYPE	STANDARD	SUFFIX "SA"	SUFFIX "SS"	EXTERIOR DIMENSIONS INCHES W x D x H	REFRIG. CAPACITY BTU/HR*, HEATER WATTS	H.P.	SHIP WEIGHT**
FULL DOORS	DL2RW	DL2RW-SA	DL2RW-SS	52 x 35 3/8 x 83 1/4	1940, 2250	1/4, - ^s	580
HALF DOORS	DL2RW-HD	DL2RW-SA-HD	DL2RW-SS-HD	52 x 35 3/8 x 83 1/4	1940, 2250	1/4, - ^s	580

Refrigerator/Warmer Pass-Thru Models

FULL DOORS	DL2RW-PT	DL2RW-SA-PT	DL2RW-SS-PT	52 x 38 3/4 x 83 1/4	1940, 2250	1/4, - ^s	595
HALF DOORS	DL2RW-PT-HD	DL2RW-SA-PT-HD	DL2RW-SS-PT-HD	52 x 38 3/4 x 83 1/4	1940, 2250	1/4, - ^s	595

BTU/HR Rating @ +25°F, 90°F ambient (refrigerators)

BTU/HR Rating @ -15°F, 90°F ambient (freezers)

Refrigerator/Freezer: (2) 10 ft. cords and plugs attached (115-60-1 volts); Refrigerator/Warmer: 10 ft. cord and plug attached (refrigerators, 115-60-1 volts)⁸ No cord and plug attached (warmers, 115/208-230-60-1 volts)

¹ Coil housing in cabinet zone and automatic, electric condensate in lieu of hot gas condensate.

** Ship Weight for Suffix "SA" and Suffix "SS" models is on average 5% higher than Standard models. Refer to Specification Sheet for Shipping Weight of these models.

Specifications - Extra Wide Dual Temperature

Extra-Wide Refrigerator/Freezer (0°F) Reach-In Models

MODEL TYPE	STANDARD	SUFFIX "SA"	SUFFIX "SS"	EXTERIOR DIMENSIONS INCHES W x D x H	CAPACITY BTU/HR*, HEATER WATTS (Warmers)	H.P.	SHIP WEIGHT**
FULL DOORS	D2RFEN	D2RFENSA	D2RFENSS	57 x 35 3/8 x 83 1/4	1940, 1590	1/4, 1/3	620
	D3RRFEN	D3RRFENSA	D3RRFENSS	85 1/2 x 35 3/8 x 83 1/4	2560, 1590	1/3, 1/3	885
	D3RFFEN	D3RFFENSA	D3RFFENSS	85 1/2 x 35 3/8 x 83 1/4	1940, 2470	1/4, 1/2	885
HALF DOORS	D1RFENHD ¹	D1RFENSAHD ¹	D1RFENSSHD ¹	28 1/2 x 35 3/8 x 83 1/4	1625, 1800	1/5, 1/3	435
	D1RFXNHD ¹	D1RFXNSAHD ¹	D1RFXNSSHD ¹	36 1/4 x 35 3/8 x 83 1/4	1725, 1250	1/4, 1/3	555
	D2RFENHD	D2RFENSAHD	D2RFENSSHD	57 x 35 3/8 x 83 1/4	1940, 1590	1/4, 1/3	620
	D3RRFENHD	D3RRFENSAHD	D3RRFENSSHD	85 1/2 x 35 3/8 x 83 1/4	2560, 1590	1/3, 1/3	885
	D3RFFENHD	D3RFFENSAHD	D3RFFENSSHD	85 1/2 x 35 3/8 x 83 1/4	1940, 2470	1/4, 1/2	885
FULL DOORS SHALLOW DEPTH	D2RFESN	D2RFESNSA	D2RFESNSS	57 x 29 1/4 x 83 1/4	1940, 1590	1/4, 1/3	580
	D3RRFESN	D3RRFESNSA	D3RRFESNSS	85 1/2 x 29 1/4 x 83 1/4	2560, 1590	1/3, 1/3	885
	D3RFFESN	D3RFFESNSA	D3RFFESNSS	85 1/2 x 29 1/4 x 83 1/4	1940, 2470	1/4, 1/2	885
HALF DOORS SHALLOW DEPTH	D1RFESNHD ¹	D1RFESNSAHD ¹	D1RFESNSSHD ¹	28 1/2 x 29 1/4 x 83 1/4	1725, 1250	1/5, 1/4	415
	D1RFXSNHD ¹	D1RFXSNSAHD ¹	D1RFXSNSSHD ¹	36 1/4 x 29 1/4 x 83 1/4	1725, 1250	1/4, 1/3	515
	D2RFESNHD	D2RFESNSAHD	D2RFESNSSHD	57 x 29 1/4 x 83 1/4	1940, 1590	1/4, 1/3	580
	D3RRFESNHD	D3RRFESNSAHD	D3RRFESNSSHD	85 1/2 x 29 1/4 x 83 1/4	2560, 1590	1/3, 1/3	885
	D3RFFESNHD	D3RFFESNSAHD	D3RFFESNSSHD	85 1/2 x 29 1/4 x 83 1/4	1940, 2470	1/4, 1/2	885

Extra-Wide Refrigerator/Freezer (0°F) Pass-Thru Models

FULL DOORS	D2RFENPT	D2RFENSAPT	D2RFENSSPT	57 x 38 3/4 x 83 1/4	1940, 1590	1/4, 1/3	680
	D3RRFENPT	D3RRFENSAPT	D3RRFENSSPT	85 1/2 x 38 3/4 x 83 1/4	2560, 1590	1/3, 1/3	970
	D3RFFENPT	D3RFFENSAPT	D3RFFENSSPT	85 1/2 x 38 3/4 x 83 1/4	1940, 2470	1/4, 1/2	970
HALF DOORS	D2RFENPTHD	D2RFENSAPTHD	D2RFENSSPTHD	57 x 38 3/4 x 83 1/4	1940, 1590	1/4, 1/3	680
	D3RRFENPTHD	D3RRFENSAPTHD	D3RRFENSSPTHD	85 1/2 x 38 3/4 x 83 1/4	2560, 1590	1/3, 1/3	970
	D3RFFENPTHD	D3RFFENSAPTHD	D3RFFENSSPTNHD	85 1/2 x 38 3/4 x 83 1/4	1940, 2470	1/4, 1/2	970

Extra-Wide Refrigerator/Warmer Reach-In Models

FULL DOORS	DL2RWE	DL2RWE-SA	DL2RWE-SS	57 x 35 3/8 x 83 1/4	1940, 2250	1/4, - ^s	580
HALF DOORS	DL2RWE-HD	DL2RWE-SA-HD	DL2RWE-SS-HD	57 x 35 3/8 x 83 1/4	1940, 2250	1/4, - ^s	580

Extra-Wide Refrigerator/Warmer Pass-Thru Models

FULL DOORS	DL2RWE-PT	DL2RWE-SA-PT	DL2RWE-SS-PT	57 x 38 3/4 x 83 1/4	1940, 2250	1/4, - ^s	595
HALF DOORS	DL2RWE-PT-HD	DL2RWE-SA-PT-HD	DL2RWE-SS-PT-HD	57 x 38 3/4 x 83 1/4	1940, 2250	1/4, - ^s	595

BTU/HR Rating @ +25°F, 90°F ambient (refrigerators); BTU/HR Rating @ -15°F, 90°F ambient (freezers)

Refrigerator/Freezer: (2) 10 ft. cords and plugs attached (115-60-1 volts); Refrigerator/Warmer: 10 ft. cord and plug attached (refrigerators, 115-60-1 volts)/[®]No cord and plug attached (warmers, 115/208-230-60-1 volts)

¹ Coil housing in cabinet zone and automatic, electric condensate in lieu of hot gas condensate.

** Ship Weight for Suffix "SA" and Suffix "SS" models is on average 5% higher than Standard models. Refer to Specification Sheet for Shipping Weight of these models.

Specifications - Standard & Extra Wide Display Refrigerators

Reach-In Models w/ Hinged Glass Doors

MODEL TYPE	STANDARD	SUFFIX "SA"	SUFFIX "SS"	EXTERIOR DIMENSIONS INCHES W x D x H	CAPACITY BTU/HR*	H.P.	SHIP WEIGHT**
FULL DOORS	D1RNGD	D1RNSAGD	D1RNSSGD	26 x 35 3/8 x 83 1/4	1940	1/4+	325
	D2RNGD	D2RNSAGD	D2RNSSGD	52 x 35 3/8 x 83 1/4	2560	1/3+	545
	D3RNGD	D3RNSAGD	D3RNSSGD	78 x 35 3/8 x 86 3/4	5930	1 [§]	755
HALF DOORS	D1RNGDHD	D1RNSAGDHD	D1RNSSGDHD	26 x 35 3/8 x 83 1/4	1940	1/4+	325
	D2RNGDHD	D2RNSAGDHD	D2RNSSGDHD	52 x 35 3/8 x 83 1/4	2560	1/3+	545
	D3RNGDHD	D3RNSAGDHD	D3RNSSGDHD	78 x 35 3/8 x 86 3/4	5930	1 [§]	755
FL DRS SHLW DPH	D1RSNGD ¹	D1RNSAGD ¹	D1RNSSGD ¹	26 x 29 1/4 x 83 1/4	2560	1/3	305
	D2RSNGD ¹	D2RNSAGD ¹	D2RNSSGD ¹	52 x 29 1/4 x 83 1/4	4010	1/2	505
HF DRS SHLW DPH	D1RSNGDHD ¹	D1RNSAGDHD ¹	D1RNSSGDHD ¹	26 x 29 1/4 x 83 1/4	2560	1/3	305
	D2RSNGDHD ¹	D2RNSAGDHD ¹	D2RNSSGDHD ¹	52 x 29 1/4 x 83 1/4	4010	1/2	505

Extra-Wide Reach-In Models w/ Hinged Glass Doors

MODEL TYPE	STANDARD	SUFFIX "SA"	SUFFIX "SS"	EXTERIOR DIMENSIONS INCHES W x D x H	CAPACITY BTU/HR*	H.P.	SHIP WEIGHT**
FULL DOORS	D1RENGD	D1RENSAGD	D1RENSSGD	28 1/2 x 35 3/8 x 83 1/4	2560	1/4+	345
	D1RXNGD	D1RXNSAGD	D1RXNSSGD	36 1/4 x 35 3/8 x 83 1/4	2810	1/3+	450
	D2RENGD	D2RENSAGD	D2RENSSGD	57 x 35 3/8 x 83 1/4	4010	1/3+	585
	D3RENGD	D3RENSAGD	D3RENSSGD	85 1/2 x 35 3/8 x 86 3/4	5930	1 [§]	810
HALF DOORS	D1RENGDHD	D1RENSAGDHD	D1RENSSGDHD	28 1/2 x 35 3/8 x 83 1/4	2560	1/4+	345
	D1RXNGDHD	D1RXNSAGDHD	D1RXNSSGDHD	36 1/4 x 35 3/8 x 83 1/4	2810	1/3+	450
	D2RENGDHD	D2RENSAGDHD	D2RENSSGDHD	57 x 35 3/8 x 83 1/4	4010	1/3+	585
	D3RENGDHD	D3RENSAGDHD	D3RENSSGDHD	85 1/2 x 35 3/8 x 86 3/4	5930	1 [§]	810
FULL DOORS SHALLOW DEPTH	D1RESNGD	D1RESNSAGD	D1RESNSSGD	28 1/2 x 29 1/4 x 83 1/4	2560	1/3	325
	D1RXSNGD	D1RXSNSAGD	D1RXSNSSGD	36 1/4 x 29 1/4 x 83 1/4	2810	1/3	410
	D2RESNGD	D2RESNSAGD	D2RESNSSGD	57 x 29 1/4 x 83 1/4	4010	1/2	545
HALF DOORS SHALLOW DEPTH	D1RESNGDHD	D1RESNSAGDHD	D1RESNSSGDHD	28 1/2 x 29 1/4 x 83 1/4	2560	1/3	325
	D1RXSNGDHD	D1RXSNSAGDHD	D1RXSSSGDHD	36 1/4 x 29 1/4 x 83 1/4	2810	1/3	410
	D2RESNGDHD	D2RESNSAGDHD	D2RESNSSGDHD	57 x 29 1/4 x 83 1/4	4010	1/2	545

Note: Consult factory for Pass-Thru models

Reach-In Models w/ Sliding Glass Doors

MODEL TYPE	STANDARD	SUFFIX "SA"	SUFFIX "SS"	EXTERIOR DIMENSIONS INCHES W x D x H	CAPACITY BTU/HR*	H.P.	SHIP WEIGHT**
FL DRS	D2RNSGD	D2RNSASGD	D2RNSSSGD	52 x 34 x 83 1/4	4010	1/2	545
HF DRS	D2RNSGDHD	D2RNSASGDHD	D2RNSSSGDHD	52 x 34 x 83 1/4	4010	1/2	545
FL DRS SHLW DPH	D2RSNSGD ¹	D2RSNSASGD ¹	D2RSNSSSGD ¹	52 x 27 7/8 x 83 1/4	4010	1/2	505
HF DRS SHLW DPH	D2RSNSGDHD ¹	D2RSNSASGDHD ¹	D2RSNSSSGDHD ¹	52 x 27 7/8 x 83 1/4	4010	1/2	505

Extra-Wide Reach-In Models w/ Sliding Glass Doors

FL DRS	D2RENSGD	D2RENSASGD	D2RENSSSGD	57 x 34 x 83 1/4	4010	1/2	585
HF DRS	D2RENSGDHD	D2RENSASGDHD	D2RENSSSGDHD	57 x 34 x 83 1/4	4010	1/2	585
FL DRS SHLW DPH	D2RESNSGD ¹	D2RESNSASGD ¹	D2RESNSSGD ¹	57 x 27 7/8 x 83 1/4	4010	1/2	545
HF DRS SHLW DPH	D2RESNSGDHD ¹	D2RESNSASGDHD ¹	D2RESNSSGDHD ¹	57 x 27 7/8 x 83 1/4	4011	1/2	545

BTU/HR Rating @ +25°F, 90°F ambient
10 ft. cord and plug attached (115-60-1 volts)
[§]No cord and plug attached (115/208-230-60-1 volts)

** Ship Weight for Suffix "SA" and Suffix "SS" models is on average 5% higher than Standard models. Refer to Specification Sheet for Shipping Weight of these models.

Specifications - Standard & Extra Wide Display Freezers (0°F)

Reach-In Models w/ Hinged Glass Doors

MODEL TYPE	STANDARD	SUFFIX "SA"	SUFFIX "SS"	EXTERIOR DIMENSIONS INCHES W x D x H	CAPACITY BTU/HR*	H.P.	SHIP WEIGHT**
FULL DOORS	D1FNGD ¹	D1FNSAGD ¹	D1FNSSGD ¹	26 x 35 3/8 x 83 1/4	2470	1/2	340
	D2FNGD	D2FNSAGD	D2FNSSGD	52 x 35 3/8 x 88 1/4	4325	1 [§]	580
	DL3F-GD	DL3F-SA-GD	DL3F-SS-GD	78 x 35 3/8 x 88 1/4	6050	1 1/2 [§]	820
HALF DOORS	D1FNGDHD ¹	D1FNSAGDHD ¹	D1FNSSGDHD ¹	26 x 35 3/8 x 83 1/4	2470	1/2	340
	D2FNGDHD	D2FNSAGDHD	D2FNSSGDHD	52 x 35 3/8 x 88 1/4	4325	1 [§]	580
	DL3F-GD-HD	DL3F-SA-GD-HD	DL3F-SS-GD-HD	78 x 35 3/8 x 88 1/4	6050	1 1/2 [§]	820
FULL DOORS SHALLOW DEPTH	D1FSNGD ¹	D1FSNSAGD ¹	D1FSNSSGD ¹	26 x 29 1/4 x 83 1/4	2470	1/2	320
	D2FSNGD ¹	D2FSNSAGD ¹	D2FSNSSGD ¹	52 x 29 1/4 x 88 1/4	4325	1 [§]	540
HALF DOORS SHALLOW DEPTH	D1FSNGDHD ¹	D1FSNSAGDHD ¹	D1FSNSSGDHD ¹	26 x 29 1/4 x 83 1/4	2470	1/2	320
	D2FSNGDHD ¹	D2FSNSAGDHD ¹	D2FSNSSGDHD ¹	52 x 29 1/4 x 88 1/4	4325	1 [§]	540

Note: Consult factory for Pass-Thru models.

Extra-Wide Reach-In Models w/ Hinged Glass Doors

MODEL TYPE	STANDARD	SUFFIX "SA"	SUFFIX "SS"	EXTERIOR DIMENSIONS INCHES W x D x H	CAPACITY BTU/HR*	H.P.	SHIP WEIGHT**
FULL DOORS	D1FENG ¹	D1FENSAGD ¹	D1FENSSGD ¹	28 1/2 x 35 3/8 x 83 1/4	2470	1/2	355
	D1FXNGD	D1FXNSAGD	D1FXNSSGD	36 1/4 x 35 3/8 x 88 1/4	2720	3/4 [§]	465
	D2FENG	D2FENSAGD	D2FENSSGD	57 x 35 3/8 x 88 1/4	4325	1 [§]	620
	DL3FE-GD	DL3FE-SA-GD	DL3FE-SS-GD	85 1/2 x 35 3/8 x 88 1/4	6050	2 [§]	870
HALF DOORS	D1FENGHD ¹	D1FENSAGDHD ¹	D1FENSSGDHD ¹	28 1/2 x 35 3/8 x 83 1/4	2470	1/2	355
	D1FXNGDHD	D1FXNSAGDHD	D1FXNSSGDHD	36 1/4 x 35 3/8 x 88 1/4	2720	3/4 [§]	465
	D2FENGHD	D2FENSAGDHD	D2FENSSGDHD	57 x 35 3/8 x 88 1/4	4325	1 [§]	620
	DL3FE-GD-HD	DL3FE-SA-GD-HD	DL3FE-SS-GD-HD	85 1/2 x 35 3/8 x 88 1/4	6050	2 [§]	870
FULL DOORS SHALLOW DEPTH	D1FESNGD ¹	D1FESNSAGD ¹	D1FESNSSGD ¹	28 1/2 x 29 1/2 x 83 1/4	2470	1/2	335
HALF DOORS SHALLOW DEPTH	D1FESNGDHD ¹	D1FESNSAGDHD ¹	D1FESNSSGDHD ¹	28 1/2 x 29 1/2 x 83 1/4	2470	1/2	335

BTU/HR Rating @ -15°F, 90°F ambient

10 ft. cord and plug attached (115-60-1 volts)

[§]No cord and plug attached (115/208-230-60-1 volts)

¹ Coil housing in cabinet zone and automatic, electric condensate in lieu of hot gas condensate.

** Ship Weight for Suffix "SA" and Suffix "SS" models is on average 5% higher than Standard models. Refer to Specification Sheet for Shipping Weight of these models.

Chrome or stainless steel shelves
 Add'l epoxy-coated steel shelves (Not available in Warmers)
 Wine racks (Refrigerators)
 Pan slide assemblies (not available on all models)
 Casters
 Rehing of doors (consult factory)
 Correctional facility package
 Expansion valve system (some Refrigerators & all Freezers)
 Custom laminates
 Stainless steel case back
 Glass door on Pass-Thru models (consult factory)

Correctional Facility Package



Coverless hinges



Security screws



Locking hasp (lock not included)



Stainless steel mesh security cover

Engineering, Manufacturing & Quality Control



Top and side air distribution ducts



Plug refrigeration system

Continental Refrigerator engineers build our Reach-Ins and Pass-Thrus to meet the most stringent specifications demanded by consultants and service operators. All cabinets are constructed of top quality materials and components, attributing to their genuine ruggedness and durability. Our Reach-Ins and Pass-Thrus are designed with enhancements to endure everyday use in typical commercial kitchen environments.

Prior to factory shipping, all models are performance-run tested for a minimum of 12 hours, providing a highly sophisticated temperature analysis recording, exclusive to each individual cabinet. This recording is then supplied, along with the unit's operation manual, for the customer. A final leak test, vibration check, noise level and visual examination is made by our quality control team, to assure a superior product is shipped from our factory.

Air Flow

All models are equipped with both top and side air distribution ducts to keep product load at a uniformly constant temperature.

"Plug" Refrigeration

Designer Line Refrigerators and Freezers utilize a "Plug" refrigeration system where the assembly is outside the food storage zone. The "Plug" system can be removed for servicing, cleaning or converting from a refrigerator to freezer in the field.

Condensate water goes into a drain pan constructed with corrosion resistant 300 Series stainless steel. The condensate water is then evaporated by a non-electric, corrosion resistant 300 Series stainless steel hot gas discharge condensate loop.

Product design and specifications are subject to change without prior notice.

How to Buy

LOCAL SALES REPRESENTATIVES			STATES COVERED
Dave Swain Associates	Westford, MA	(978) 392-8401	ME, RI, NH, MA, VT, CT
Link 2 Hospitality Solutions	Rochester, NY	(585) 254-1780	Upstate NY
Pecinka Ferri Associates	Fairfield, NJ	(973) 812-4277	N. NJ, New York City
Schmid Dewland & Associates	Marlton, NJ	(856) 783-3400	E. PA, DE, S. & Central NJ
Link 2 Hospitality Solutions	Pittsburg, PA	(412) 341-2020	W. PA, W. VA (except Panhandle)
High Sabatino Associates, Inc.	Jessup, MD	(301) 470-7051	DC, MD, VA, W. VA (Panhandle)
Stiefel Associates, Inc.	Lansing, MI	(517) 393-3019	MI (except Upper Peninsula)
Dick Stanley & Associates	Pickerington, OH	(800) 833-0797	OH, KY
Gabriel Group	Fishers, IN	(800) 832-6442	IN
Jay Mark Group, LTD	Elk Grove Village, IL	(847) 545-1918	N. IL
North Star Agency	Edina, MN	(763) 545-1400	MN, ND, SD
Mirkovich & Associates	Waukesha, WI	(630) 792-0080	WI, MI (Upper Peninsula)
Select Marketing	St. Louis, MO	(314) 961-3332	MO, KS, IA, NE, S. IL
Master Marketing Carolina	High Shoals, NC	(704) 860-0092	NC, SC
Pro-Quip Foodservice	Little Rock, AR	(501) 221-7120	AR, LA, MS, W. TN (W. of Tenn. River)
The Veitch Group	Ft. Lauderdale, FL	(954) 316-6162	FL (except Panhandle)
Merkolat	Wellington, FL	(561) 594-7153	Latin America, Caribbean
Carman-Girard Associates	Atlanta, GA	(770) 457-6548	AL, FL (Panhandle), GA, E. TN (E. of Tenn River)
Ignite Foodservice Solutions	Denver, CO	(303) 433-0124	CO, S. ID, MT, UT WY
Roller & Associates	Seattle, WA	(206) 547-3555	WA, OR, AK, N. ID
Foodservice Equipment Agents	Anaheim, CA	(714) 693-3329	AZ (Bull Head City), S. CA, S. NV
Inform Marketing Group	Walnut Creek, CA	(510) 337-0420	N. CA, N. NV
Ignite Foodservice Solutions	Denver, CO	(303) 433-0124	AZ (except Bull Head City), NM, TX (El Paso)
Forbes Hever & Wallace, Inc.	Coppell, TX	(972) 219-8898	OK, TX (except El Paso)



A Division of National Refrigeration & Air Conditioning Products

Continental Refrigerator | Local: (215) 244-1400
539 Dunksferry Road | Toll Free: (800) 523-7138
Bensalem, PA 19020 | Fax: (215) 244-9579

www.continentalrefrigerator.com

Continental®

Refrigerator

INNOVATIVE DESIGNS FOR YOUR FOODSERVICE NEEDS



REVISED 9/6/2022