

## R-290 Cold Built-In Flush Top Shelves

Hatco's R-290 Cold Shelves Built-In Flush Top, in our signature Hardcoat Aluminum, are designed to keep your pre-chilled beverages, hors d'oeuvres, side dishes, buffet items and more, perfectly chilled.

- Condenser utilizes environmentally friendly R-290 refrigerant
- Patented thermal break reduces condensation and temperature transfer on adjacent surfaces
- All models are top mounted with an Hardcoat Aluminum surface
- All models match the GRSBF Heated Built-In Shelves for a fully integrated look
- Control Box comes standard with a 4' lead wire
- Condenser utilizes an environmentally friendly R-290 refrigerant, which has a 90% higher heat absorption capacity than other refrigerants, resulting in quicker temperature recovery and lower energy consumption



**CSBFP-48-S**  
(Flush Top)

### R-290 COLD BUILT-IN FLUSH TOP SHELVES (Hardcoat Aluminum)

Model	Overall Shelf Dimensions W x D	Usable Shelf Space W x D	Voltage Single Phase	Watts	Comp. Size HP	Hz	Approx. Ship Weight
CSBFP-24-F	25½" x 17"	24" x 15½"	120	345	1/5	60	108 lbs.
CSBFP-24-I	25½" x 21"	24" x 19½"	120	345	1/5	60	116 lbs.
CSBFP-24-S	25½" x 25½"	24" x 24"	120	345	1/5	60	117 lbs.
CSBFP-36-F	37½" x 17"	36" x 15½"	120	345	1/5	60	130 lbs.
CSBFP-36-I	37½" x 21"	36" x 19½"	120	440	1/3	60	130 lbs.
CSBFP-36-S	37½" x 25½"	36" x 24"	120	440	1/3	60	151 lbs.
CSBFP-48-F	49½" x 17"	48" x 15½"	120	440	1/3	60	138 lbs.
CSBFP-48-I	49½" x 21"	48" x 19½"	120	440	1/3	60	157 lbs.
CSBFP-48-S	49½" x 25½"	48" x 24"	120	560	1/2	60	177 lbs.

#### All R-290 Cold Built-In Flush Top Shelf Models Feature:

Electronic Temperature Control and a condensing unit, 6' cord and plug (NEMA 5-15P).

#### OPTIONS (available at time of purchase only)

**EWC** (Additional four year extended Parts Only Warranty on the compressor available at the time of unit purchase CSSB, CSSBR models only)

#### COUNTERTOP CUTOUT DIMENSIONS

Model	Width		Depth	
	Min	Max	Min	Max
CSBFP-24-F	24⅝"	25"	16⅞"	16½"
CSBFP-24-I	24⅝"	25"	20⅞"	20½"
CSBFP-24-S	24⅝"	25"	24⅝"	25"
CSBFP-36-F	36⅝"	37"	16⅞"	16½"
CSBFP-36-I	36⅝"	37"	20⅞"	20½"
CSBFP-36-S	36⅝"	37"	24⅝"	25"
CSBFP-48-F	48⅝"	49"	16⅞"	16½"
CSBFP-48-I	48⅝"	49"	20⅞"	20½"
CSBFP-48-S	48⅝"	49"	24⅝"	25"

**NOTE:** The installation kit, including the intake bracket, duct clamp, flexible duct, and duct collar, will be shipped separately.

