



R-290 Cold Built-In Flush Top Simulated Stone Shelves

Hatco's new R-290 Cold Built-In Flush Top Simulated Stone Shelves are a must for buffet lines in cafeterias, restaurants and more!

- Condenser utilizes environmentally friendly R-290 refrigerant
- Patented thermal break reduces condensation and temperature transfer on adjacent surfaces
- All models are bottom mount units
- Control Box can be mounted 4' from center of the shelf
- Simulated stone is Swanstone®



CSSBFP-48-S
in standard Night Sky
simulated stone

R-290 COLD BUILT-IN FLUSH TOP SIMULATED STONE SHELVES

Model	Overall Shelf Dimensions (includes brackets) W x D	Shelf Space W x D	Voltage Single Phase	Watts	Hz	Comp. Size HP	Approx. Ship Weight
CSSBFP-24-F	27" x 18½"	24" x 15½"	120	345	60	1/5	119 lbs.
CSSBFP-24-I	27" x 22½"	24" x 19½"	120	345	60	1/5	124 lbs.
CSSBFP-24-S	27" x 27"	24" x 24"	120	345	60	1/5	134 lbs.
CSSBFP-36-F	39" x 18½"	36" x 15½"	120	345	60	1/5	138 lbs.
CSSBFP-36-I	39" x 22½"	36" x 19½"	120	440	60	1/3	155 lbs.
CSSBFP-36-S	39" x 27"	36" x 24"	120	440	60	1/3	164 lbs.
CSSBFP-48-F	51" x 18½"	48" x 15½"	120	440	60	1/3	159 lbs.
CSSBFP-48-I	51" x 22½"	48" x 19½"	120	440	60	1/3	171 lbs.
CSSBFP-48-S	51" x 27"	48" x 24"	120	560	60	1/2	189 lbs.

All Cold Built-In Flush Top Simulated Stone Shelf Models Feature:

Electronic Temperature Control and a condensing unit, 6' cord and plug (NEMA 5-15P).

OPTIONS (available at time of purchase only)

Simulated stone colors – Non-standard colors are non-returnable – Night Sky standard –

SS-GGRAN	Gray Granite
SS-BSAND	Bermuda Sand
EWC	(Additional four year extended Parts Only Warranty on the compressor available at the time of unit purchase CSSB, CSSBR models only)

COLORS AND FINISHES – INSIDE BACK COVER OF CURRENT PRICE LIST

COUNTERTOP CUTOUT DIMENSIONS

Model	Width with ⅜" corner radii	Depth with ⅜" corner radii
CSSBFP-24-F	24⅜"	15⅞"
CSSBFP-24-I	24⅜"	19⅞"
CSSBFP-24-S	24⅜"	24⅜"
CSSBFP-36-F	36⅜"	15⅞"
CSSBFP-36-I	36⅜"	19⅞"
CSSBFP-36-S	36⅜"	24⅜"
CSSBFP-48-F	48⅜"	15⅞"
CSSBFP-48-I	48⅜"	19⅞"
CSSBFP-48-S	48⅜"	24⅜"

NOTE: The installation kit, including the intake bracket, duct clamp, flexible duct, and duct collar, will be shipped separately.

