

DISCOVER BALLYMORE'S NEWEST 2 OCCUPANT DRIVABLE SCISSOR LIFTS

INNOVATION DRIVEN TO NEW HEIGHTS



**Featuring
An Extendable
Roll Out Cantilever
Platform**

The roll-out cantilevered platform provides safer access to machinery and equipment.



Gradeability



0° Turn Radius



DRIVABLE SCISSOR LIFTS

Features:

- Extendable Roll-Out Cantilever Platform
- Drivable at full heights
- Self-Locking safety gate
- Emergency Stop Button
- Emergency Lowering System
- Forklift Pockets
- Powder Coat finish
- DMSL-10 & DMSL-12 Maximum Occupants = 1
- Meets or Exceeds ANSI Standards

**NEW
MINI
DRIVABLE
19'**



Model Number	Weight Capacity	Working Height	Platform Height		Platform W x L (Outer Dimension)	Platform Extension	Base W x L	Overall Height	Weight (lbs)	Power - Batteries
			Max	Min						
DMSL-10	500	16'	10'	36"	28" x 50"	22"	30" x 57"	80"	1825	2 - 12V
DMSL-12	500	18'	12'	36"	28" x 50"	22"	30" x 57"	80"	1900	2 - 12V
DMSL-19	500	25'	19'	42"	29" x 66"	36"	30" x 74"	86"	3164	4 - 6V
DMSL-19C	500	25'	19'	42"	28" x 53"	24"	32" x 60"	83"	2733	2-12V
DMSL-26	500	32'	26'	48"	32" x 90"	36"	32" x 98"	92"	4718	4 - 6V
DMSL-26(W)	1000	32'	26'	48"	44" x 90"	36"	46" x 98"	92"	4884	4 - 6V
DSL-32	700	38'	32'	48"	44" x 90"	36"	46" x 98"	96"	5533	4 - 6V
DSL-40	550	46'	40'	58"	44" x 90"	36"	47" x 98"	102"	6834	4 - 12V
DSL-45	500	51'	45'	58"	44" x 104"	36"	55" x 112"	102"	7320	4 - 12V