



## MSLA017MB CONDENSING UNIT



Note: Pictures are for illustration only,  
and may not reflect the listed model.

GENERAL						
REFRIGERANT	VOLTAGE	COMPRESSOR TYPE	COMPRESSOR MODEL	HP	AWEF	LISTINGS
R-454A	208-230/60/1	Scroll	YF06KAE-PFV	1.75	2.95	UL/CUL

BTUH CAPACITY (At Saturated Suction Temperature (SST) and 90° Ambient at Condenser)							
-30	-20	-10	20	25	30	35	45
5,278	6,793	8,635	-	-	-	-	-

BTUH CAPACITY (At Saturated Suction Temperature (SST) and 100° Ambient at Condenser)							
-30	-20	-10	20	25	30	35	45
4,539	6,046	7,685	-	-	-	-	-

DIMENSIONAL DATA							
OVERALL (to nearest inch)			WT (lbs)	BASE SIZE		BASE/HOOD	
L	W	H		M2	021M		
38	27	18	240				

INSTALLATION							
REFRIGERANT	RECEIVER TANK (lbs) 90%/90°F	CONNECTIONS				ESTIMATED TOTAL HEAT REJECTION (BTUH)	
		LIQUID	SUCTION			12,224	
R-454A	10.1	3/8	7/8				

MCA	MOP	COMP VOLTS	COMP PHASE	COMP HZ	COMP RLA	COMP LRA	OTHER LOAD
22.1	25	208-230	1	60	12.2	68	DATA
FAN PHASE	FAN HZ	FAN FLA	FAN HP	FAN QUANTITY	MAX EVAP FAN AMPS	MAX EVAP DEF HEATER AMPS	VOLTS 208-230
1	60	0.67	1/20	2	5	15.0	PHASE 1 AMPS 0.5

