

SLOWSTOP 5 INCH BOLLARD ROUND BASE

Phone: +1.210.736.4477
www.SlowStop.com



SLOWSTOP
GUARDING
SYSTEMS
LLC



REBOUNDING TECHNOLOGY

During a collision, the kinetic energy of the impact is absorbed by an elastomer hidden in the base of the post. The post is able to tilt approximately 20° as it progressively absorbs energy, softening the impact. After the impact, the post returns upright, leaving your guard intact and ready to perform again.



Installs with six (6) 5/8"
x 5-1/2" Concrete Screw
Anchors

DESIGNED WITH A SMALLER FOOTPRINT TO FIT IN TIGHT SPACES AND BUILT TO PROTECT ANCHORS

SPECIFICATIONS:

- Meets IBC 1607.8.3 requirements to resist 6,000 pounds of force at 27" height
- No Damage Rating: 7,000 joules / 5,163 ft.-lb.
- Stopping Power: 14,000 joules / 10,326 ft.-lb.

RECOMMENDED USES:

- Where forks or cantilevers typically shear bolts
- Medium to heavy duty
- Dock door protection
- Post-tensioned concrete
- Pedestrian safety

MASS (LBS)	5000	7500	10000	15000	20000	25000	30000	40000	80000
SPEED (MPH)									
1.0									
1.5									
2.0									
2.5									
3.0									
3.5									
4.0									
4.5									
5.0									
5.5									
6.0									
6.5									
7.0									

No Damage / Negligible Damage
Will Stop / Potential Damage to Guard
Guard is under-sized

4955 Stout Dr. San Antonio, TX 78219 | Phone: +210.736.4477 | www.SlowStop.com

©2020 SlowStop Guarding Systems. All Rights Reserved. SlowStop is a trademarks of Impact Recovery Systems, Inc.