

## STEEL ROLLING SAFETY LADDERS

- **450 lb. Rated Capacity**
- Perforated or Grip Strut tread
- Ships unassembled
- 1" tubular steel construction
- Powder-coat gray finish
- Spring-loaded casters 2-5 step models
- Step lock 6-16 step models
- Complies with applicable OSHA & ANSI standards



## ALL DIRECTION ROLLING LADDERS

- **450 lb. Rated Capacity**
- Ladder turns within its own radius
- Perforated or Grip Strut tread
- Ships unassembled
- 1" tubular steel rails
- Powder-coat gray finish
- Step lock all models
- Complies with applicable OSHA & ANSI standards



MODEL #	# of Steps	Platform Height	OVERALL HEIGHT	Platform W x L	Base W x D	Weight
<b>16" Step Width</b>						
KDSR102166	2	20"	62"	16" x 10"	21" x 21"	77
KDSR103166	3	30"	72"	16" x 10"	24" x 28"	89
KDSR104166	4	40"	82"	16" x 10"	24" x 35"	100
KDSR105166	5	50"	86"	16" x 10"	24" x 42"	110
KDSR106166	6	60"	102"	16" x 10"	27" x 50"	159
KDSR107166	7	70"	112"	16" x 10"	27" x 57"	155
<b>24" Step Width</b>						
KDSR102246	2	20"	62"	24" x 10"	28" x 21"	85
KDSR103246	3	30"	72"	24" x 10"	30" x 28"	96
KDSR104246	4	40"	82"	24" x 10"	30" x 35"	109
KDSR105246	5	50"	86"	24" x 10"	30" x 42"	121
KDSR106246	6	60"	102"	24" x 10"	35" x 50"	176
KDSR107246	7	70"	112"	24" x 10"	35" x 57"	188
KDSR108246	8	80"	122"	24" x 10"	35" x 64"	245
KDSR109246	9	90"	132"	24" x 10"	35" x 69"	256
KDSR110246	10	100"	142"	24" x 10"	35" x 76"	281
KDSR111246	11	110"	152"	24" x 10"	35" x 83"	296
KDSR112246	12	120"	162"	24" x 10"	35" x 90"	323
KDSR113246	13	130"	172"	24" x 10"	40" x 96"	341
KDSR114246	14	140"	182"	24" x 10"	40" x 103"	363
KDSR115246	15	150"	192"	24" x 10"	40" x 110"	383

NOTE: Models Listed are for Perforated Treads  
Specify Tread Type when ordering

MODEL #	# OF STEPS	OVERALL HEIGHT	PLATFORM W x L	BASE W x D	WEIGHT
KDED107246	7	112"	24" x 10"	35" x 57"	216
KDED108246	8	122"	24" x 10"	35" x 64"	273
KDED109246	9	132"	24" x 10"	35" x 69"	282
KDED110246	10	142"	24" x 10"	35" x 76"	311
KDED111246	11	152"	24" x 10"	35" x 83"	334
KDED112246	12	162"	24" x 10"	35" x 90"	360
KDED113246	13	172"	24" x 10"	35" x 96"	387
KDED114246	14	182"	24" x 10"	40" x 103"	411
KDED115246	15	192"	24" x 10"	40" x 110"	454

NOTE: Models Listed are for Perforated Treads

50° SAFETY ANGLE

FORWARD DESCENT




**SAFETY ANGLE ROLLING LADDERS**

- 450 lb. Rated Capacity
- 17" deep top platform
- 50° safety angle incline
- Perforated or Grip strut tread
- Ships unassembled
- 1" tubular steel rails
- 1" x 2" reinforced back & bottom frame
- 8.5" deep steps, 10" deep 1st step
- Powder-coat gray finish
- Step lock on all models
- Complies with applicable OSHA & ANSI standards

MODEL #	# of Steps	Overall Height	Platform W x L	Base W x D	Weight
KDEC103166	3	72	16" x 17"	27" x 41"	122
KDEC103246	3	72	24" x 17"	35" x 41"	139
KDEC104166	4	82	16" x 17"	27" x 49"	137
KDEC104246	4	82	24" x 17"	35" x 49"	150
KDEC105166	5	92	16" x 17"	27" x 58"	170
KDEC105246	5	92	24" x 17"	35" x 58"	185
KDEC106166	6	102	16" x 17"	27" x 66"	184
KDEC106246	6	102	24" x 17"	35" x 66"	201
KDEC107166	7	112	16" x 17"	27" x 74"	228
KDEC107246	7	112	24" x 17"	35" x 74"	245
KDEC108246	8	122	24" x 17"	35" x 82"	391
KDEC109246	9	132	24" x 17"	35" x 91"	306
KDEC110246	10	142	24" x 17"	35" x 99"	320
KDEC111246	11	152	24" x 17"	35" x 107"	352
KDEC112246	12	162	24" x 17"	35" x 116"	377
KDEC113246	13	172	24" x 17"	40" x 124"	405
KDEC114246	14	182	24" x 17"	40" x 132"	425
KDEC115246	15	192	24" x 17"	40" x 141"	521

Models Listed are for Perforated Treads

Also Available in Safety Yellow



**ALL-DIRECTIONAL SAFETY ANGLE ROLLING LADDERS**

- 450 lb. Rated Capacity
- Ladder turns within its own radius
- 17" deep top platform
- Gradual descent 50° incline
- Perforated or Grip Strut tread
- Ships unassembled
- 1" tubular steel rails
- 1" x 2" reinforced back & bottom frame
- 8.5" deep steps, 10" deep 1st step
- Powder-coated gray finish
- Step lock on all models
- Complies with applicable OSHA & ANSI standards



MODEL #	# of Steps	Overall Height	Platform W x L	Base W x D	Weight
KDAD107246	7	112	24" x 17"	35" x 74"	274
KDAD108246	8	122	24" x 17"	35" x 82"	310
KDAD109246	9	132	24" x 17"	35" x 91"	336
KDAD110246	10	142	24" x 17"	35" x 99"	350
KDAD111246	11	152	24" x 17"	35" x 107"	383
KDAD112246	12	162	24" x 17"	35" x 116"	408
KDAD113246	13	172	24" x 17"	40" x 124"	430
KDAD114246	14	182	24" x 17"	40" x 132"	525
KDAD115246	15	192	24" x 17"	40" x 141"	569

Ideal for ease of maneuvering in tight spaces or narrow aisles.

# POWDER COATED STEEL



## 600# HEAVY DUTY ROLLING LADDERS

- 600 lb. Rated Capacity
- Additional bracing
- Perforated or Grip Strut tread
- Ships unassembled
- 1" tubular steel construction
- Powder-coated gray finish
- Step lock on all models
- Complies with applicable OSHA & ANSI standards



MODEL #	# OF STEPS	OVERALL HEIGHT	PLATFORM W x L	BASE W x D	WEIGHT
KDHD106246	6	102	24" x 10"	35" x 70"	197
KDHD107246	7	112	24" x 10"	35" x 57"	212
KDHD108246	8	122	24" x 10"	35" x 64"	275
KDHD109246	9	132	24" x 10"	35" x 69"	297
KDHD110246	10	142	24" x 10"	35" x 76"	317
KDHD111246	11	152	24" x 10"	35" x 83"	337
KDHD112246	12	162	24" x 10"	35" x 90"	364



## 600# HEAVY DUTY SAFETY ANGLE ROLLING LADDERS

- 600 lb. Rated Capacity
- Additional bracing
- Safety angle incline
- Perforated or Grip strut tread
- Ships unassembled
- 1" tubular steel construction
- 1" x 2" reinforced back & bottom frame
- Powder coat gray finish
- Step lock on all models
- Complies with applicable OSHA & ANSI standards



MODEL #	# of Steps	Overall Height	Platform W x L	Base W x D	Weight
KDHS106246	6	102	24" x 17"	35" x 66"	215
KDHS107246	7	112	24" x 17"	35" x 66"	257
KDHS108246	8	122	24" x 17"	35" x 82"	295
KDHS109246	9	132	24" x 17"	35" x 91"	322
KDHS110246	10	142	24" x 17"	35" x 99"	337
KDHS111246	11	152	24" x 17"	35" x 107"	371
KDHS112246	12	162	24" x 17"	35" x 116"	397

