Save up to 50% of your frying oil





Frying oil filter & oil tester

Your solution - the VITO product line

The world's most innovative frying oil filtration system!

The VITO oil filter system cleans your oil, ensures your oil quality and saves up to 50% of your oil costs.





You will save money, oil, labor, storage space and delivery costs with VITO!



Easy & safe handling Get clean oil in 4,5 minutes. Put VITO in the fryer at service temperature. Push the button and you're done!



Simple cleaning

VITO is made of stainless steel and therefore dishwasher safe! VITO disassembles to fit easily in any dishwasher!



Constant quality

VITO ensures you always fry in clean oil which means great quality fried food.










The VITO effect

What is VITO doing?

Used daily, VITO filters remove food particles and carbon from your frying oil. Frying in clean, filtered oil will result in a better tasting and better looking fried product. Oil life increases and workload decreases due to less oil changes and fryer cleanings.




VITO portable

The world's best in-tank pressure oil filtration system!

Track the usage of your VITO VL and VITO VM remotely and protect your investment (Wi-Fi capable device necessary)











VITO 30
1-3 fryers up to 121 / 22lbs
For light sediment



398mm

15.7in

VITO VM 1-4 fryers up to 201 / 37lbs For light to medium sediment²



All fryers with heavy duty
For medium to heavy sediment³

Filtration Filtration Particle Work Suction Weight Temperature Material **Particle** VITO power efficiency uptake cycle depth filter **VITO 30** up to 30I /min up to 5um 0,8kg1 4.5min ~ 20cm 6.3ka max. 200°C Stainless steel Cellulose 66 lbs/min 200 uinch 1.8lbs1 ~ 7.9in 14lbs max. 392°F 1.4301 FDA-CFR 21 **VITO VM** up to 60l/min up to 5um 1.3kg² 4.5min ~ 35cm 7.7ka max. 200°C Stainless steel Cellulose 130 lbs/min 200 yinch 2.9lbs² ~ 13.8in 17lbs max. 392°F 1.4301 FDA-CFR 21 **VITO VL** up to 100l/min 2,5kg3 ~ 45cm max. 200°C Stainless steel Cellulose up to 5um 4.5min 8,8kg 220 lbs/min 200 uinch 5.5lbs3 ~ 17.7in 19 4lbs max 392°F 1 4301 FDA-CFR 21







VITO mobile

The world's most innovative vacuum filtration system!













	Filtration power	Filtration efficiency	Particle uptake	Pumping power	Tank	Weight	Temperature	Material VITO	Particle filter
VITO XS	up to 30l /min	up to 5ųm	10,7kg	35I/min	401 /	45kg /	max. 200°C	Stainless steel	Cellulose
	66 lbs/min	200 ųinch	23.6 lbs	77Ibs	73lbs	100lbs	max. 392°F	1.4301	FDA-CFR 21
VITO XM	up to 30l/min	up to 5ųm	10,7kg	35I/min	75I /	55,8kg /	max. 200°C	Stainless steel	Cellulose
	66 lbs/min	200 ųinch	23.6 lbs	77Ibs	137lbs	123lbs	max. 392°F	1.4301	FDA-CFR 21
VITO XL	up to 30l/min	up to 5ųm	10,7kg	35I/min	120l /	64kg /	max. 200°C	Stainless steel	Cellulose
	66 lbs/min	200 ųinch	23.6 lbs	77Ibs	220lbs	141lbs	max. 392°F	1.4301	FDA-CFR 21








Data reader Read out the usage of VITO


FT 440 frying oil tester

Measuring oil quality increases your savings!

Change your oil as needed - never too early, never too late.



The optimal frying range



FT 440 example:







	Parameter	Resolution	Measuring range TPM	Measuring range °C / °F	Accuracy	Battery	IP format	Alarm function
FT 440	%TPM °C/°F	0.5% TPM 0.1°C/°F	0 40% TPM	+50°C +200°C +122°F +392°F	±2.0% TPM ±1°C / °F	3V Lithium (CR 2477)	IP 67	3-color traffic light function





VITO

Seen in 150 countries - used in over 50.000 kitchens



















































































































Your benefits with VITO:

- Save up to 50% of your frying oil
- **Ensure optimal oil quality**
- Less workload around your fryer



























VITO Fryfilter 5422 Carrier Drive Ste 102 Orlando, FL 32819 (847) 859 0398 info@vitofryfilter.com www.vitofryfilter.com

VITO® is a registered trademark of VITO AG, Germany V 5.5









