

Countertop Range



351RCPG12NL, 351RCPG24NL, 351RCPG36NL

REVISED 12/2022

Congratulations on your purchase of Cooking Performance Group commercial cooking equipment! At Cooking Performance Group, we take pride in the design, innovation, and quality of our products. To ensure optimal performance, we have outlined the following instructions and guidelines in this manual carefully for your review. Cooking Performance Group declines any responsibility in the event users do not follow the instructions or guidelines stated here.

Contents

Safety Precautions	2
Parts List & Diagram	3-5

Safety Precautions

CAUTION:

Failure to comply with the following operation instructions could lead to potential hazards and/or unsafe practice and could result in injury and damage to product and property.

NOTICE:

- Local codes regarding installation vary greatly from one area to another. The National Fire Protection Association, Inc., states in its NFPA96 latest edition that Local codes are “Authority Having Jurisdiction” when it comes to requirement for installation of equipment. Therefore, installation should comply with all Local codes.
- This product is intended for commercial use only. Not for residential use.

WARNING:

- Do not store or use gasoline or other flammable vapors and liquids in the vicinity of this or any other equipment.
- Improper installation, adjustment, alteration, service or maintenance could lead to property damage, injury or death. Read the installation, operating and maintenance instructions thoroughly before installing or servicing CPG equipment. This manual must be retained for future reference.
- A factory authorized agent must handle all maintenance and repair.

GAS PRESSURE:

The appliance and its individual shutoff valve (to be supplied by user) must be disconnected from the gas supply piping system during any pressure testing of that system at test pressures in excess of ½ PSI (3.45 kPa). The appliance must be isolated from the gas supply piping system by closing its individual manual shut-off valve during any pressure testing of the gas supply piping system at test pressures equal to or less than ½ PSI (3.45 kPa).



Intertek
3182799



Intertek

Conforms to ANSI STD Z83.11b-2009 (R2011)
Conforms to CSA STD 1.8b-2009 (R2011)
NSF Tested by ETL

Parts Manual



Key	Item Number	Qty	Description
1	351RCPG12NL	2	Grate
	351RCPG24NL	4	
	351RCPG36NL	6	
2	351RCPG12NL	2	Burner
	351RCPG24NL	4	
	351RCPG36NL	6	
3	351RCPG12NL	1	Regulator
	351RCPG24NL	1	
	351RCPG36NL	1	
4	351RCPG12NL	1	Tray
	351RCPG24NL	1	
	351RCPG36NL	1	
5	351RCPG12NL	4	Foot
	351RCPG24NL	4	
	351RCPG36NL	4	
6	351RCPG12NL	1	Main Pipe Assy.-Front
	351RCPG24NL	2	
	351RCPG36NL	3	
7	351RCPG12NL	1	Pilot Pipe Assy.-Front
	351RCPG24NL	2	
	351RCPG36NL	3	

Parts Manual



Key	Item Number	Qty	Description
8	351RCPG12NL	1	Pilot Pipe assy.-Rear
	351RCPG24NL	2	
	351RCPG36NL	3	
9	351RCPG12NL	1	Pilot Valve
	351RCPG24NL	2	
	351RCPG36NL	3	
10	351RCPG12NL	1	Main Pipe Assy.-Rear
	351RCPG24NL	2	
	351RCPG36NL	3	
11	351RCPG12NL	1	Valve
	351RCPG24NL	2	
	351RCPG36NL	3	
12	351RCPG12NL-NAT	2	Orifice
	351RCPG24NL-NAT	4	
	351RCPG36NL-NAT	6	
	351RCPG12NL-LPG	2	
	351RCPG24NL-LPG	4	
13	351RCPG12NL	2	Dial
	351RCPG24NL	4	
	351RCPG36NL	6	
14	351RCPG12NL	2	Connector
	351RCPG24NL	4	
	351RCPG36NL	6	

Parts Manual

