
## **HEATER CLEARANCE REQUIREMENTS**

SEE 'HEATER SPECIFICATIONS' TABLE





**ISOMETRIC VIEW** 


STANDARD MOUNTING **BRACKETS INCLUDED** 

6'7 SUPPLIED CABLE, NO PLUG: 240V UNITS 8' SUPPLIED CABLE, NO PLUG: 120V UNIS


STAINLESS STEEL OPTION AVAILABLE **SAME OVERALL DIMENSIONS** 


## SUITABLE MOUNTING CONFIGURATIONS

- 1. WALL MOUNTED
- 2. VERTICAL TILTED





## **OVERALL SIZE AND MOUNTING DIMENSIONS**





(X)





MODEL	A (FEET)	B (FEET)	C (FEET)	D (FEET)	HEAT ZONE* (SQUAR E FEET)	HEAT DENSITY* (WATTS/ SQUARE FEET)
SCOSYXL15120	6.6	9	8	11	90	16
SCOSYXL15240	6.6	9	8	11	90	16
SCOSYXL15240-L1	6.6	9	8	11	90	16

## **↑** SHORTWAVE INFRARED HEATERS FOR:

INDOOR USE - RESIDENTIAL (1500W ONLY\*), COMMERCIAL AND INDUSTRIAL OUTDOOR USE - RESIDENTIAL, COMMERCIAL AND INDUSTRIAL FOR USE IN NON-HAZARDOUS AREAS ONLY

\*2000W HEATER IS NOT SUITIBLE FOR INDOOR RESIDENTIAL USE

**HEATER SPECIFICATIONS																
			240V				208V									
DESCRIPTION	SKU	WEIGHT (LBS/KG)	POWER (WATTS)	HEAT DELIVERED (BTU)	VOLTAGE (VOLTS)	CURRENT (AMPS)	MINIMUM HEIGHT (INCH/cm) (Y1)	CEILING CLEARANCE (INCH/cm) (Y2)	SIDE WALL CLEARANCE (INCH/cm) (X)	POWER (WATTS)	HEAT DELIVERED (BTU)	VOLTAGE (VOLTS)	CURRENT (AMPS)	MINIMUM HEIGHT (INCH/cm) (Y1)	CEILING CLEARANCE (INCH/cm) (Y2)	SIDE WALL CLEARANCE (INCH/cm) (X)
COSY XL - 1500W / 120V	SCOSYXL15120*	6.8/2.8	1500	5100	120	12.5	79/201	11.75/30	40/100				N/A	•	•	'
COSY XL - 1500W / 240V	SCOSYXL15240*	6.8/2.8	1500	5100	240	6.3	79/201	11.75/30	40/100	1125	3825	208	5.4	79/201	11.75/30	40/100
COSY XL - 2000W / 240V	SCOSYXL20240*	6.8/2.8	2000	6800	240	8.7	79/201	11.75/30	40/100	1500	5100	208	7.2	79/201	6/15	40/100
COSY XL CANDEL - 1500 / 240V	SCOSYXL30240-L1*	6.8/2.8	1500	5100	240	6.3	79/201	11.75/30	40/100	1125	3825	208	5.4	79/201	11.75/30	40/100
COSY XL CANDEL - 2000 / 240V	SCOSYXL40240-L1*	6.8/2.8	2000	6800	240	8.7	79/201	11.75/30	40/100	1500	5100	208	7.2	79/201	6/15	40/100
KU NOTES: *SEE PRODUCT CATALOGUE FOR STANDARD COLOR OPTIONS. STAINLESS STEEL OPTIONS AVAILABLE. L1 DENOTES CANDEL LOW LIGHT LAMP. ALL HEATERS COME WITH STANDARD 3" L BRACKETS   ** SPECIFICATIONS SUBJECT TO SHANGE WITHOUT NOTICE																

B1	2021-11-23						
REVISION	DATE: YYYY-MM-DD						

US Certified to UL2021 and CSA 22.2 46-13

MODEL

**SOLAIRA XL H1** 

SHEET NO.

SHEET SCALE

SHEET SIZE 1:8

11X17

NOTICE: THIS DOCUMENT IS NOT A SUBSTITUTE FOR APPROVED MANUAL. Failure to follow instruction manual may cause fire, electric shock or injury to persons. SolairaTM is a registered trademark of Inforesight Consumer Products. Customer, contractor specifier and installer understands that some or all products provided by Inforesight Consumer Products Inc. may not be available for purchase or installation in certain jurisdictions or geographical areas. Inforesight Consumer Products Inc. reserves the right, in its sole discretion, to exclude or otherwise limit the provision of any product to a person or entity residing and exclusively residence and installer must strictly adhere to another exclusively residing to exclude or otherwise limit the products inc. Instruction manuals are included with the product packaging and copies of our instruction manuals are available upon request. Under no circumstances shall Inforesight Consumer Products Inc. or its affiliated entitles, employees, agents, shareholders, officers or directors be label and customer or any third party for any product installations and customer or any third party for any product installations and customer or any third party for any product installations and customer or any third party for any product installations and actions of any kind arising from the Customer's installation and use of the product, whether the installation manual and/or in compliance with applicable local laws. Solaira products are to be installed by liscensed technicians per instruction manuals and to all provincial/state and national (N.E.C.) code requirements; specifications subject to change without notice.