

DoughXpress has closed. Find the customer's DoughXpress model, then quote the Proluxe press it points to.
-SS (stainless) and **-W** / **-WH** (white) versions match the same Proluxe model.

CUSTOMER HAS (DOUGHXPRESS)

QUOTE (PROLUXE)



DM-18

Manual clamshell

- Heated upper platen, to 200°F
- 18" max diameter
- 120V



PP1818 FLEX X1

- Manual clamshell
 - Heated upper platen, to 425°F
 - 120 / 208 / 240V · 50–100 pies/hr
- Needs thickness control or more volume? Step up to the DP1100 Endurance X1.



DM-18NH

Manual clamshell, cold press

- No heat
- 18" max diameter
- No electrical



PP1818 FLEX X1

- Same clamshell format
 - Adds a heated upper platen, to 425°F
 - 120 / 208 / 240V · 50–100 pies/hr
- Heat helps cold dough press out and keeps it from shrinking back.



DMS-18

Manual swing-away

- Heated, analog control to 400°F
- 18" max diameter
- 120V



PP1818 FLEX X1

- Manual clamshell
 - Heated upper platen, to 425°F
 - 120 / 208 / 240V · 50–100 pies/hr
- Needs thickness control or more volume? Step up to the DP1100 Endurance X1.



DXM-SS · DXM-W

Manual, lower platen swings out

- Upper heat, to 200°F
- Interchangeable platens 8"–17"
- 120V



DP1100M ENDURANCE X1M

- Manual, interchangeable LPMI molds 8"–16"
 - Upper heat, to 425°F
 - 120 / 208 / 240V · 100–200 pies/hr
- Replaces the interchangeable platens. Order the mold sizes the customer runs.



DXA-SS · DXA-W

Air automatic

- Air compressor required
- Upper heat, to 200°F
- 120V



DP1350 APEX PRO X1

- Fully automatic, hydraulic
 - Self-contained: no compressor
 - Upper heat to 425°F · 150–250 pies/hr
- Store already runs shop air and wants to keep it? The DP1300 pneumatic press fits that setup.



DXE-SS · DXE-W

Electro-mechanical automatic

- Upper heat, to 200°F
- Interchangeable platens 8"–17"
- 120V



DP3300M IMPACT X1M

- Fully automatic, electro-mechanical
 - Interchangeable LPMI molds 8"–16"
 - Upper heat, to 425°F
 - 120 / 208 / 240V · 150–250 pies/hr
- Replaces the interchangeable platens. Order the mold sizes the customer runs.

Hotter platens

Proluxe presses heat to 425°F. DoughXpress upper-heat presses top out at 200°F.

Embedded elements

Cast into the platen, with a limited lifetime warranty on the element.

Cast aluminum body

DoughXpress used sheet-metal housings.

Ceramic platens

Ceramic-coated platens available, and 120, 208 or 240V on most models.

CUSTOMER HAS (DOUGHXPRESS)

QUOTE (PROLUXE)



DMS-2-18

Manual swing-away, dual heat

- Upper and lower heat, to 400°F
- 18" max diameter
- 240V



PP2018 FLEX X2

- Manual clamshell
- Upper and lower heat
- 208 / 240V · 50–100 pies/hr

Higher volume or thickness control? Step up to the DP2000 Endurance X2.



D-TXM-2-18

Manual, dual heat

- Upper and lower heat, to 450°F
- 18" pizza or tortilla
- 220V



DP2000 ENDURANCE X2

- Manual, dual heat, auto leveling
- Pizza or tortilla
- 208 / 240V · 100–200 pies/hr

Tortillas only, lower budget? PP2020 Flex X2T. Wants molds? DP2010M Endurance Pro X2M.



TXM-20

Manual clamshell tortilla press

- Dual heat, to 450°F
- 16" × 20" platens, about 6 tortillas a press
- 220V



PP2020 FLEX X2T

- Manual clamshell tortilla press
- Upper and lower heat
- 208 / 240V

Our platen is 18" round, not 16" × 20". Confirm tortillas per press. Higher volume or auto leveling? Step up to the DP2000 Endurance X2.



TXM-15

Manual swing-away tortilla press

- Dual heat, to 400°F
- 15" × 15" platens
- 220V



DP2000 ENDURANCE X2

- Manual, dual heat, auto leveling
- 18" round platen
- 208 / 240V · 100–200 pies/hr

Lower budget? Alternate: PP2020 Flex X2T dual-heat clamshell tortilla press.



D-TXA-2-18

Air automatic, dual heat

- Air compressor required
- Upper and lower heat, to 450°F
- 18" pizza or tortilla · 220V



DP2350M APEX PRO X2M

- Fully automatic, hydraulic
- Self-contained: no compressor
- Dual heat · 208 / 240V · 150–250 pies/hr

Interchangeable MID molds 8"–16" sold separately.



D-TXE-2-18

Electro-mechanical automatic, dual heat

- Upper and lower heat
- 18" pizza or tortilla
- 220V



DP2350M APEX PRO X2M

- Fully automatic, hydraulic
- Dual heat · auto leveling
- 208 / 240V · 150–250 pies/hr

Proluxe has no electro-mechanical dual-heat press. The Apex Pro X2M is our automatic dual-heat match.