

Flexiwell 1-6 well ShelleySteel:

Provide Delfield Flexiwell ShelleySteel model, mobile hot, cold and freeze combination serving counters. Units available from 1 well up to 6 wells, individually controlled hot/cold/freeze option; Top is constructed of one-piece, 14 ga. stainless steel. Interior liner is constructed of aluminum with flush mount flange for heating, cooling and freeze operations, to accommodate up to 6" deep, 12" x 20" pans, supplied by others. Top surface must not exceed 139° F – no UL® "caution hot" sticker required. Dry operation only, no water required. Exterior liner body is constructed of galvanized steel with high density environmentally friendly Kyoto Protocol compliant, non-ODP/GWP polyurethane foam throughout; Exterior unit body is constructed of 18-gauge stainless steel side panels and 14-gauge galvanized bottom. All exterior sides are reinforced with overlapping corners and are welded in place. All body cutouts are reinforced with 14-gauge galvanized channel supports. Unit utilizes GreenGenius™ R290 refrigeration system; Temperature controlled by 3-way hot/cold/off power switch and thermostat for heated, cold and freeze operations, located in control panel. Units are mounted on 5" diameter swivel casters with plate brakes and supplied with 14-20P cord and plug; 2-year full parts/labor warranty with standard parts warranty.