

groen. STEAMERS

LEED® CHART

These Groen steamers contribute toward satisfying WE Credit Indoor Water Use Reduction under LEED®

MODEL	PSI	INITIAL FILL GALLONS	TREATED GPH	UNTREATED GPH	TOTAL GPH	GPH PER PAN	LEED REQUIREMENTS PER PAN
INTEK CONNECTIONLESS STEAMERS							
XS Electric	-	3	<1.5	NA	<1.5	≤ .25	≤ 2 gph
SMARTSTEAM PRO BOILERLESS STEAMERS							
GSSP-BL-3E/ES	30	3.2	5.2	7.8	13	4.3	≤ 5 gph
GSSP-BL-5E/ES	30	3.2	5.2	11.8	17	3.4	
	60	3.2	5.4	12.3	17.7	3.5	
GSSP-BL-10ES	30	6.1	5.2	14.8	20	2	
GSSP-BL-3G/GS	30	3.2	5.2	7.8	13	4.3	
GSSP-BL-5G/GS	30	3.2	5.2	11.8	17	3.4	
	60	3.2	5.4	12.3	17.7	3.5	
GSSP-BL-10GS	30	6.1	5.2	14.8	20	2	
(2)GSSP-BL-3ES	30	6.4	10.4	15.6	26	4.3	
(2)GSSP-BL-5ES	30	6.4	10.4	23.6	34	3.4	
	60	6.4	10.8	24.6	35.4	3.5	
(2)GSSP-BL-10ES	30	12.2	10.4	29.6	40	2	
(2)GSSP-BL-3GS	30	6.4	10.4	15.6	26	4.3	
(2)GSSP-BL-5GS	30	6.4	10.4	23.6	34	3.4	
	60	6.4	10.8	24.6	35.4	3.5	
(2)GSSP-BL-10GS	30	12.2	10.4	29.6	40	2	

Note: Incoming water pressure must be between 30psi and 60psi.

This data is subject to change at any time.

Part of



888.994.7636 unifiedbrands.net

© 2023 Electrolux Professional, Inc. All Rights Reserved. 08/18/23