



A CSW Industrials Company

INSTALLATION INSTRUCTIONS

GUARDIAN DRAIN LOCK®

DOME-D-LOCK®

FOR MODELS GDL DOME2000, GDL DOME3000 & GDL DOME4000

Installation Instructions

TOOLS NEEDED:

The following tools to properly secure the Guardian Dome-D-Lock:

- 3/8" Ratchet
- 3/8" Ratchet Extension
- Tamperproof Torx Key (GDLT40 for 2" and GDLT45 for 3" & 4" drain locks)
- Rag

HOW TO INSTALL

1. Clean the floor sink of debris and grime build up within the throat of drain. *(Photo #1)*
2. Determine the appropriate size Guardian Dome-D-Lock to be installed: 2", 3" or 4". Once size is validated, place the Dome-D-Lock in the hole of the floor sink.

Note: If the drain lock has too tight of a fit, the rubber banding can be removed.

3. Assemble the ratchet, ratchet extension and tamperproof key. Determine which tamperproof key will be needed to secure the desired Dome-D-Lock. GDLT40 key for 2" and GDLT45 for 3" and 4".
4. While holding down the Dome-D-Lock with one hand, insert the driver and key into the tamperproof bolt and tighten (clockwise) until firmly secured. Do not over tighten. *(Photo #2)*

MONITORING THE DOME-D-LOCK

1. Once the Dome-D-Lock is properly secured and locked, there should be no need to remove it other than for sanitation purposes. As needed, use hot soapy water and a plastic brush to clean any built up grime or debris. If the Dome-D-Lock is to be removed for cleaning, wash it by hand or run it through your dish machine. Before re-installing, make certain all parts are in good condition.
2. Monitor that your Guardian Dome-D-Lock's are secured/locked in place once a month to guarantee protection of your drain pipes.

PHOTO #1



PHOTO #2



Limited Warranty



For more information on our product warranty, visit RectorSeal.com

Manufactured by

RectorSeal, LLC

2601 Spenwick Drive, Houston, TX 77055, USA • 800-231-3345 • Fax 800-441-0051 • rectorseal.com

3255 Wyandotte St. East, Windsor, ON N8Y 1E9, Canada • 519-966-4901