




Installation Instructions

Hands-Free Arm Door Opener



Item No.	Description
ARMPULL-V	Hands-Free Arm Door Opener

INSTALLATION

Kit Contents

Part	Quantity
ARMPULL-V (arm door opener bracket) 1 $\frac{3}{4}$ "W x 3"D x 2 $\frac{5}{8}$ "H	1
Sheet Metal Screw, 1-1/4"	4

Tools You Will Need

- Drill and 5/32" drill bit
- Phillips head screwdriver

1. Place the bracket at the desired height on the swinging edge of the door. We recommend placement 44"-48" above the ground spaced 2" in from the edge of the door.
2. Drill a hole in one of the two top mounting holes using a 5/32" drill bit. Drill in 1"-1 1/4" depth while being careful not to drill through the opposite side of the door.
3. Insert and tighten one of the provided sheet metal screws.
4. Make sure the bracket is level, then drill out the other top hole using the bracket as a template. Install one of the provided sheet metal screws.
5. Drill the remaining bottom two holes and install the remaining sheet metal screws.



www.vollrathfoodservice.com

The Vollrath Company, L.L.C.
1236 North 18th Street
Sheboygan, WI 53081-3201 U.S.A.
Main Tel: 800.624.2051 or 920.457.4851
Main Fax: 800.752.5620 or 920.459.6573
Customer Service: 800.628.0830
Canada Customer Service: 800.695.8560

Technical Services
techservicereps@vollrathco.com
Induction Products: 800.825.6036
Countertop Warming Products: 800.354.1970
Toasters: 800-309-2250
All Other Products: 800.628.0832