



Hot Drop-Ins



Top-Mount Fabricator Well

- Designed for top-mount installation and requires hard-wiring
- High-density glass fiber insulation allows use of 1,000W elements
- Zero clearance for flexibility in installation
- Available for 120V, 208-240V power
- Beveled edge for easy cleaning
- Thermostatic control
- 4-foot flexible control cable
- Hard-wired input power connections
- Recommend using up to 4" (10.2 cm) deep pans – full and fractional sizes



ITEM #	OVERALL DIMENSIONS (W X D): IN (CM)	WATTS	VOLTAGE: AC	AMPS
36368	15 x 23 (38.1 x 58.4)	1000	120	8.3
36369	15 x 23 (38.1 x 58.4)	750-1000	208-240	3.6-4.2

*With 3/8" (2.2 cm) corner radius Note: Modular drop-ins cannot be canceled or returned





Modular Dry Hot Drop-Ins

- Zero clearance installation – no trim rings required for installation in nonmetallic countertops
- Waterless – no need to manage water and drainage
- Accommodate pans up to 6" in depth
- Choice of infinite or thermostatic controls
- Cord and plug installation
- Open-element design
- Standard one-year warranty



ITEM #	DESCRIPTION	CONTROL TYPE	VOLTAGE: AC
FC-4DH-01120-I	1-well hot dry drop-in	Infinite	120
FC-4DH-01208-I	1-well hot dry drop-in	Infinite	208-240
FC-4DH-01120-T	1-well hot dry drop-in	Thermostatic	120
FC-4DH-01208-T	1-well hot dry drop-in	Thermostatic	208-240
FC-4DH-02120-I	2-well hot dry drop-in	Infinite	120
FC-4DH-02208-I	2-well hot dry drop-in	Infinite	208-240
FC-4DH-02120-T	2-well hot dry drop-in	Thermostatic	120
FC-4DH-02208-T	2-well hot dry drop-in	Thermostatic	208-240
FC-4DH-03120-I	3-well hot dry drop-in	Infinite	120
FC-4DH-03120-I	3-well hot dry drop-in	Infinite	208-240
FC-4DH-03120-T	3-well hot dry drop-in	Thermostatic	120
FC-4DH-03208-T	3-well hot dry drop-in	Thermostatic	208-240
FC-4DH-04208-I	4-well hot dry drop-in	Infinite	208-240
FC-4DH-04208-T	4-well hot dry drop-in	Thermostatic	208-240
FC-4DH-05208-I	5-well hot dry drop-in	Infinite	208-240
FC-4DH-05208-T	5-well hot dry drop-in	Thermostatic	208-240
FC-4DH-06208-I	6-well hot dry drop-in	Infinite	208-240
FC-4DH-06208-T	6-well hot dry drop-in	Thermostatic	208-240

*Items are made to order and cannot be canceled or returned



Bottom-Mount Fabricator Well

- Designed for bottom-mount installation and requires hard-wiring
- Beveled edge for easy cleaning
- Thermostatic control
- Deep drawn well is 20-gauge 18-8 stainless steel
- Meets NSF performance standards
- Allows use of full-size and fractional pans up to 6" (15.2 cm) deep while still providing moist heat



ITEM #	WELL*	OVERALL DIMENSIONS (W X D): IN (CM)	REMOTE CONTROL LEADS: IN (CM)	WATTS	VOLTAGE: AC	AMPS
36352	I	14 ³ / ₃₂ x 22 ¹ / ₈ (35.8 x 56.2)	36 (91.4)	1000	120	8.3
36353	I	14 ³ / ₃₂ x 22 ¹ / ₈ (35.8 x 56.2)	72 (182.9)	1000	120	8.3
36354	I	14 ³ / ₃₂ x 22 ¹ / ₈ (35.8 x 56.2)	36 (91.4)	1000	208-240	3.6-4.2
36355	I	14 ³ / ₃₂ x 22 ¹ / ₈ (35.8 x 56.2)	72 (182.9)	1000	208-240	3.6-4.2
36356	V	14 ³ / ₃₂ x 22 ¹ / ₈ (35.8 x 56.2)	36 (91.4)	1000	120	8.3
36360	V	14 ³ / ₃₂ x 22 ¹ / ₈ (35.8 x 56.2)	72 (182.9)	1000	120	8.3
36358	V	14 ³ / ₃₂ x 22 ¹ / ₈ (35.8 x 56.2)	36 (91.4)	1000	208-240	3.6-4.2
36359	V	14 ³ / ₃₂ x 22 ¹ / ₈ (35.8 x 56.2)	72 (182.9)	1000	208-240	3.6-4.2

*I = Industry and V = Vollrath wells Note: Modular drop-ins cannot be canceled or returned



**NEW**

Half-Size Drop-In Warmer

- Drop-in half-size warmer fits seamlessly in a metal counter/cabinet
- Infinite control dial provides flexible heating options
- Indicator light notifies users when water is needed
- Meets NSF 4 performance standards for hot food holding
- Durable, easy-to-clean stainless steel well and flange
- Holds half-size-long, fourth-size, or sixth-size pans up to 6 inches deep
- Remote-control box and 3-foot lead wires for mounting options



ITEM #	DESCRIPTION	DIMENSIONS (W X D X H): IN (CM)	CUTOUT DIMENSIONS: IN (CM)	VOLTAGE: AC	WATTS	AMPS
FC-4H-HLF120	Drop-In Half-Size Warmer	6.39 x 20.65 x 8.51 (16.24 x 52.44 x 21.62)	6.39 x 20.65 x 8.51 (16.24 x 52.44 x 21.62)	120	500	4.2
FC-4H-HLF230	Drop-In Half-Size Warmer	6.39 x 20.65 x 8.51 (16.24 x 52.44 x 21.62)	6.39 x 20.65 x 8.51 (16.24 x 52.44 x 21.62)	230	500	2.2



Cayenne® Drop-In Warmers

- Thermoset fiber-reinforced resin well – self-insulating for maximum energy efficiency
- 6-foot cord and plug or hard-wired
- Top mounts
- Low-water indicator light eliminates guesswork
- Drain models allow for easy cleaning
- Recommend using up to 4" (10.2 cm) deep pans – full and fractional sizes



ITEM #	DESCRIPTION	DIMENSIONS (L X W X H): IN (CM)	VOLTAGE: AC	WATTS	AMPS	PLUG
US MODELS**						
72105	Model 3001D drop-in warmer with drain, unit-mounted control	21¾ x 13¾ x 9 (55 x 33 x 23)	120	700	5.8	5-15P
72107	Model 3002D drop-in warmer with drain, front-mounted control panel with flexible conduit control panel cutout dimensions: 5" x 3½" (12.7 x 8.9 cm), no low-water indicator light	21¾ x 13¾ x 9 (55 x 33 x 23)	120	700	5.8	Hard Wire
72109*	Model TD43R-DI 4/3 thermoset drop-in warmer with integral drain, front-mounted control panel with flexible conduit control panel dimensions: 5⅝" x 5½" (14.3 x 14 cm)	28¾ x 13¾ x 13⅞ (73 x 34.9 x 33.2)	120	1600	13.3	5-15P
72112****	Model TD43R-DI 4/3 thermoset drop-in warmer with integral drain, front-mounted control panel with flexible conduit control panel dimensions: 5⅝" x 5½" (14.3 x 14 cm)	28¾ x 13¾ x 13⅞ (73 x 34.9 x 33.2)	240	1600	7.7	6-15P
CANADA MODELS — AVAILABLE FOR CANADA ONLY**						
72111	Model TD43R-DI 4/3 thermoset drop-in warmer with integral drain, front-mounted control panel with flexible conduit control panel dimensions: 5⅝" x 5½" (14.3 x 14 cm)	28¾ x 13¾ x 13⅞ (73 x 34.9 x 33.2)	120	1600	13.3	5-20P
INTERNATIONAL MODELS — AVAILABLE FOR EXPORT ONLY***						
72610	Model 3001 drop-in warmer	21¾ x 13¾ x 9 (55 x 33 x 23)	230	700	3.0	Schuko
72560	Model 3001D drop-in warmer with drain	21¾ x 13¾ x 9 (55 x 33 x 23)	230	700	3.0	UK

*5-foot cord and plug **cULus certified ***CE certified ****U.S. and Canadian model Note: Modular drop-ins cannot be canceled or returned



*International models only



Cayenne® Model 2001 Drop-In Warmer

- Stainless steel 6½" (16.6 cm) deep well
- Durable stainless steel exterior for longer life
- Instant drop-in without permanent wiring, plumbing, or installation costs
- Positioning pins hold unit in place
- 6-foot cord and plug – no wiring required
- Meets NSF 4 performance standards
- Recommend using up to 4" (10.2 cm) deep pans – full and fractional sizes



ITEM #	DIMENSIONS (L X W X H): IN (CM)	VOLTAGE: AC	WATTS	AMPS	PLUG
72001	24 x 15 x 8½ (61 x 38.1 x 21.9)	120	1000	8.3	5-15P

Note: Modular drop-ins cannot be canceled or returned



Round Modular Hot Drop-Ins

- 6-foot (183 cm) power cord and 4-foot (122 cm) control cord
- Double-wall construction
- Deep-drawn stainless wells
- High-density glass fiber insulation
- ¾" (1.9 cm) drain with ball valve shut-off
- Well height: 7¼" (19.5 cm)



INFINITE CONTROL ITEM #	THERMOSTATIC CONTROL ITEM #	HOLDS INSET SIZE: QT (L)	DIAMETER OVER FLANGE: IN (CM)	WELL OUTER DIAMETER: IN (CM)	WATTS	VOLTAGE: AC	AMPS	PLUG
36462	3646210	7¼ (6.9)	11¾ (28.4)	10¾ (26.2)	720	120	6	5-15P
36464	3646410	11 (10.5)	12¾ (32.5)	12 (30.5)	720	120	6	5-15P
36463	3646310	7¼ (6.9)	11¾ (28.4)	10¾ (26.2)	720-960	208-240	3.5-4	6-15P
36465	3646510	11 (10.5)	12¾ (32.5)	12 (30.5)	720-960	208-240	3.5-4	6-15P

Note: Modular drop-ins cannot be canceled or returned



Bain-Marie Hot Drop-Ins

- Open design allows for use of templates
- Thermostat controls temperature accurately and maintains steam for safe food warming
- Well depth: 6⅝" (16.8 cm)



DESCRIPTION	WATTS	120V ITEM #	AMPS	PLUG	208V ITEM #	AMPS	PLUG	240V ITEM #	AMPS	PLUG	OVERALL DIMENSIONS (W X D): IN (CM)	INTERIOR LENGTH: IN (CM)
2-pan	1250	36500	10.4	5-15P	36501208	6	6-15P	36501240	5.2	6-15P	29 x 26 (73.7 x 66)	24¾ (62.9)
3-pan	1875	36502	15.6	5-20P	36503208	9	6-15P	36503240	7.8	6-15P	41½ x 26 (105.4 x 66)	37½ (95.3)
4-pan	2500	—	—	—	36504208	12	6-20P	36504240	10.4	6-15P	54¾ x 26 (139.1 x 66)	50¼ (127.6)
5-pan	3125	—	—	—	36505208	15	6-20P	36505240	13	6-20P	68 x 26 (172.7 x 66)	63 (160)
6-pan	3750	—	—	—	36506208	18	6-30P	36506240	15.6	6-20P	81¼ x 26 (206.4 x 66)	75¾ (192.4)

With ⅝" (2.2 cm) corner radius Designed for warming food pans only – not for use as a rethermalizing water vessel

Note: Modular drop-ins cannot be canceled or returned

