

## **Fabricated Sinks**

| Diagon | +-   | +   | _     _   | fahricated | aimles. | infoundati | <b></b> |
|--------|------|-----|-----------|------------|---------|------------|---------|
| Please | noie | men | niinwiine | ranncared  | SIMKS   | miorma     | HOIL.   |

- All sink tops and bowls 304 S/S.
- All supports (support kit and welded supports) 304 S/S.
- Standard gauge for sink tops is 16 unless specified differently.
- Standard edge for all sinks is raised rolled edge.

| 1. What is the overall length of the sink needed?                                | 2. 9" rear splash is the standard<br>height. Do you need a different<br>size? If so, please verify. | 9. Larger sink bowls often require more than one faucet to either reduce the sink fill time (quicker) or to maintain a shorter fill spout. Would you like provisions for one or two faucets? |  |  |  |
|--|---|--|--|--|--|
| inches   | inches  | One Two  |  |  |  |
| 3. What # of sink bowls/<br>compartments are needed?                             | 4. Are drainboards needed? If so, what location?  | 10. Where does the faucet provision(s) need to be located?   |  |  |  |
| bowl/compartments  |   |  |  |  |  |
| 5. What size sink bowls/compartme  | nts are needed?   | 11. If faucet is other than 8" on-center, please specify:  |  |  |  |
| Other:   | Lx Dx W   |  |  |  |  |
| 6. What gauge stainless steel is need  | ded for the table (please verify)?  | 12. Is a lever twist drain needed? (Recommended)   |  |  |  |
| 16 Gauge (Default) 1.  | 4 Gauge   | Yes No   |  |  |  |
| 7. Is the end or ends of the sink agai<br>where the sink is against a side wall. |   | 13. Do you wish to add an overflow kit? (NOTE: For field installation post-receipt of sink.)   |  |  |  |
| Yes No   |   | Yes  |  |  |  |
| If yes, which end of the sink is against the                                     | wall?   | No No  |  |  |  |
| 8. What bracing/support is desired f options below:                              | or the sink? Please choose from the   |  |  |  |  |
|  | d installation. Contains tubular<br>ool for attaching gussets to sink legs.                         |  |  |  |  |
| Fully Welded Support - Done  | at the factory during production.   |  |  |  |  |

## Comments/Questions: